



Application

04774 - 2016 Roadway Modernization

05308 - CSAH 31 (Pilot Knob Rd) at CSAH 32 (Cliff Rd) Intersection in Eagan

Regional Solicitation - Roadways Including Multimodal Elements

Status: Submitted  
Submitted Date: 07/14/2016 4:06 PM

---

## Primary Contact

**Name:\*** Ms. Holly Jo Anderson  
Salutation First Name Middle Name Last Name

**Title:** P.E.S.

**Department:** Dakota County Transportation Dept

**Email:** Holly.Anderson@co.dakota.mn.us

**Address:** 14955 Galaxie Avenue

**\*** Apple Valley Minnesota 55124  
City State/Province Postal Code/Zip

**Phone:\*** 952-891-7090  
Phone Ext.

**Fax:**

**What Grant Programs are you most interested in?** Regional Solicitation - Roadways Including Multimodal Elements

---

## Organization Information

**Name:** DAKOTA COUNTY

**Jurisdictional Agency (if different):**

**Organization Type:**

County Government

**Organization Website:**

**Address:**

TRANSPORTATION DEPT  
14955 GALAXIE AVE

\*

APPLE VALLEY    Minnesota    55124  
City                      State/Province              Postal Code/Zip

**County:**

Dakota

**Phone:\***

952-891-7100  
Ext.

**Fax:**

**PeopleSoft Vendor Number**

0000002621A15

---

## Project Information

**Project Name**

CSAH 31 (Pilot Knob Rd) at CSAH 32 (Cliff Rd) Intersection Improvements

**Primary County where the Project is Located**

Dakota

**Jurisdictional Agency (If Different than the Applicant):**

The project improves safety and mobility at the intersection of County State Aid Highway (CSAH) 31 (Pilot Knob Rd) and CSAH 32 (Cliff Rd) in the City of Eagan. CSAH 31 is a four-lane divided, A-Minor Expander roadway. The northbound/southbound approach geometrics consist of an exclusive left turn lane, two through lanes, and a right turn lane. The 2014 Average Annual Daily Traffic AADT 2014 (2030) is 20,700 (28,000) north of CSAH 32 and 21,200 (32,000) to the south. The current speed limit is 45 miles per hour.

County State Aid Highway (CSAH) 32 (Cliff Rd) is a four-lane divided, A-Minor Expander roadway. The eastbound/westbound approach geometrics consist of an exclusive left turn lane, two through lanes, and a right turn lane. The 2014 Average Annual Daily Traffic AADT 2014 (2030) is 18,300 (23,000) west of CSAH 31 and 13,400 (20,000) to the east. The current speed limit is 50 miles per hour.

**Brief Project Description (Limit 2,800 characters; approximately 400 words)**

This is a heavily traveled intersection providing regional access westerly to I-35E (1.7 miles); TH 77 (2.7 miles); TH 13 (3.7 miles) and I-35 (6.2 miles); and access northerly to I-35E (2.7 miles); I-494 (4.9 miles) and TH 55 (5.9 miles).

The project objectives are to improve safety and operations, and facilitate transit, bicycle and pedestrian movements through the area.

The project includes the following elements:

10-Ton pavement design;

Intersection improvements, including dual left turn lanes on all four approaches;

Replacement of aged Traffic Signal, median, ADA compliant ramps, turn lanes and lighting.

Installation of the required ADA compliant crossing elements at the intersection, some examples of

crossing elements include: pedestrian ramps, countdown timers, median islands, accessible pedestrian signals

Replacement of curb & gutter, sidewalks, storm sewer and lighting. This includes removal of identified sidewalk/trail obstructions currently located within the pedestrian access route. The CSAH 31 and CSAH 32 corridors are both identified on the Regional Bicycle Transportation Network (RBTN) Corridors as Tier I (CSAH 31) and Tier II (CSAH 32). The project area trails connect users to recreational opportunities (Lebanon Hills Regional Park & various city parks), commercial, business and industrial areas.

Dakota County is committed to operating and maintaining this facility for it's useful life of the improvement.

*Include location, road name/functional class, type of improvement, etc.*

**TIP Description Guidance (will be used in TIP if the project is selected for funding)**

CSAH 31 (Pilot Knob Rd) at CSAH 32 (Cliff Rd) Intersection Improvements in Eagan

**Project Length (Miles)**

0.36

---

## Project Funding

**Are you applying for funds from another source(s) to implement this project?**

No

**If yes, please identify the source(s)**

**Federal Amount**

\$3,134,000.00

**Match Amount**

\$784,700.00

*Minimum of 20% of project total*

**Project Total**

\$3,918,700.00

**Match Percentage**

20.02%

*Minimum of 20%*

*Compute the match percentage by dividing the match amount by the project total*

**Source of Match Funds**

Dakota County, City of Eagan

*A minimum of 20% of the total project cost must come from non-federal sources; additional match funds over the 20% minimum can come from other federal sources*

**Preferred Program Year**

**Select one:**

2020



For TDM projects, select 2018 or 2019. For Roadway, Transit, or Trail/Pedestrian projects, select 2020 or 2021.

Additional Program Years:

2019

Select all years that are feasible if funding in an earlier year becomes available.

---

## Specific Roadway Elements

CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES	Cost
Mobilization (approx. 5% of total cost)	\$151,300.00
Removals (approx. 5% of total cost)	\$77,300.00
Roadway (grading, borrow, etc.)	\$405,400.00
Roadway (aggregates and paving)	\$905,200.00
Subgrade Correction (muck)	\$0.00
Storm Sewer	\$541,000.00
Ponds	\$0.00
Concrete Items (curb & gutter, sidewalks, median barriers)	\$250,000.00
Traffic Control	\$11,850.00
Striping	\$50,100.00
Signing	\$18,700.00
Lighting	\$0.00
Turf - Erosion & Landscaping	\$48,350.00
Bridge	\$0.00
Retaining Walls	\$804,700.00
Noise Wall (do not include in cost effectiveness measure)	\$0.00
Traffic Signals	\$608,500.00
Wetland Mitigation	\$0.00
Other Natural and Cultural Resource Protection	\$0.00
RR Crossing	\$0.00
Roadway Contingencies	\$0.00
Other Roadway Elements	\$0.00
<b>Totals</b>	<b>\$3,872,400.00</b>

---

## Specific Bicycle and Pedestrian Elements

CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES	Cost
Path/Trail Construction	\$39,900.00

Sidewalk Construction	\$0.00
On-Street Bicycle Facility Construction	\$0.00
Right-of-Way	\$0.00
Pedestrian Curb Ramps (ADA)	\$6,400.00
Crossing Aids (e.g., Audible Pedestrian Signals, HAWK)	\$0.00
Pedestrian-scale Lighting	\$0.00
Streetscaping	\$0.00
Wayfinding	\$0.00
Bicycle and Pedestrian Contingencies	\$0.00
Other Bicycle and Pedestrian Elements	\$0.00
<b>Totals</b>	<b>\$46,300.00</b>

## Specific Transit and TDM Elements

<b>CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES</b>	<b>Cost</b>
Fixed Guideway Elements	\$0.00
Stations, Stops, and Terminals	\$0.00
Support Facilities	\$0.00
Transit Systems (e.g. communications, signals, controls, fare collection, etc.)	\$0.00
Vehicles	\$0.00
Contingencies	\$0.00
Right-of-Way	\$0.00
Other Transit and TDM Elements	\$0.00
<b>Totals</b>	<b>\$0.00</b>

## Transit Operating Costs

Number of Platform hours	0
Cost Per Platform hour (full loaded Cost)	\$0.00
Subtotal	\$0.00
Other Costs - Administration, Overhead, etc.	\$0.00

## Totals

<b>Total Cost</b>	<b>\$3,918,700.00</b>
-------------------	-----------------------

Construction Cost Total	\$3,918,700.00
Transit Operating Cost Total	\$0.00

---

## Requirements - All Projects

### All Projects

*1. The project must be consistent with the goals and policies in these adopted regional plans: Thrive MSP 2040 (2014), the 2040 Transportation Policy Plan, the 2040 Regional Parks Policy Plan (2015), and the 2040 Water Resources Policy Plan (2015).*

**Check the box to indicate that the project meets this requirement. Yes**

*2. The project must be consistent with the 2040 Transportation Policy Plan. Reference the 2040 Transportation Plan objectives and strategies that relate to the project.*

Goal: A. Transportation System Stewardship (p. 2.17)

Sustainable investments in the transportation system are protected by strategically preserving, maintaining, and operating system assets.

Objectives: A. Efficiently preserve and maintain the regional transportation system in a state of good repair.: A1. Regional transportation partners will pace the highest priority for transportation investments on strategically preserving, maintaining, and operating the transportation system. A2. Regional transportation partners should regularly review planned preservation and maintenance projects to identify cost-effective opportunities to incorporate improvements for safety, lower-cost congestion management and mitigation, transit, bicycle, and pedestrian facilities. (p. 2.18)

**List the goals, objectives, strategies, and associated pages:**

Goal: B Safety and Security (p. 2.20) The regional transportation system is safe and secure for all users.

Objectives: A. Reduce crashes and improve safety and security for all modes of passenger travel and freight transport. Strategies: B1. Regional transportation partners will incorporate safety and security considerations for all modes and users throughout the processes of planning, funding, construction, operations. (p. 2.20) B6. Regional transportation partners will use best practices to provide and improve facilities for safe walking and bicycling, since pedestrians and bicyclists are the most vulnerable users of the transportation system. (p. 2.23)

Goal: C. Access to Destinations People and businesses prosper by using a reliable, affordable, and efficient multimodal transportation system that connects them to destinations throughout the

region and beyond.

Objectives: B. Increase travel time reliability and predictability for travel on highway and transit systems.

E. Improve multimodal travel options for people of all ages and abilities to connect to jobs and other opportunities, particularly for historically under-represented populations. Strategies: C2. Local units of government should provide a system of interconnected arterial roads, streets, bicycle facilities, and pedestrian facilities to meet local travel needs using Complete Streets principles. (p. 2.25)

*3. The project or the transportation problem/need that the project addresses must be in a local planning or programming document. Reference the name of the appropriate comprehensive plan, regional/statewide plan, capital improvement program, corridor study document [studies on trunk highway must be approved by the Minnesota Department of Transportation and the Metropolitan Council], or other official plan or program of the applicant agency [includes Safe Routes to School Plans] that the project is included in and/or a transportation problem/need that the project addresses.*

Dakota County 2030 Transportation Plan, June 2012

Goal 1: Limited Resources are Directed to the Highest Priority Needs of the Transportation System. The emphasis of this goal is for the County to develop the best transportation system to provide for safe movement of people and goods within financial constraints. p. 1-4

Goal 4: Management to Increase Transportation System Efficiency, Improve Safety and Maximize Existing Highway Capacity

The strategies and policies within this goal aim to optimize the capacity and safety of the existing transportation system with recognition that fiscal, social and environmental constraints limit the ability of construction only accelerated road construction to achieve safe travel.

List the applicable documents and pages:

CIP Investment Categories - Safety & management, Signal Projects p. 1-9

Goal 5: Replace Deficient Elements of the System

This goal provides measures, strategies and policies aimed at replacement of four important elements of the transportation system - bridges, highways, traffic signals and gravel roads.

Dakota County Highway Capacity Deficiencies 2030, Figure 5 p. 2-16 (& Figure 43 p. 9-6)

In 2030 CSAH 31 (Pilot Knob Rd) will be over capacity

Intersections Approaching Capacity Figure 45 p. 9-13

4. The project must exclude costs for studies, preliminary engineering, design, or construction engineering. Right-of-way costs are only eligible as part of bicycle/pedestrian projects, transit stations/stops, transit terminals, park-and-ride facilities, or pool-and-ride lots. Noise barriers, drainage projects, fences, landscaping, etc., are not eligible for funding as a standalone project, but can be included as part of the larger submitted project, which is otherwise eligible.

**Check the box to indicate that the project meets this requirement. Yes**

5. Applicants that are not cities or counties in the seven-county metro area with populations over 5,000 must contact the MnDOT Metro State Aid Office prior to submitting their application to determine if a public agency sponsor is required.

**Check the box to indicate that the project meets this requirement. Yes**

6. Applicants must not submit an application for the same project elements in more than one funding application category.

**Check the box to indicate that the project meets this requirement. Yes**

7. The requested funding amount must be more than or equal to the minimum award and less than or equal to the maximum award. The cost of preparing a project for funding authorization can be substantial. For that reason, minimum federal amounts apply. Other federal funds may be combined with the requested funds for projects exceeding the maximum award, but the source(s) must be identified in the application. Funding amounts by application category are listed below.

**Roadway Expansion:** \$1,000,000 to \$7,000,000

**Roadway Reconstruction/ Modernization:** \$1,000,000 to \$7,000,000

**Roadway System Management** \$250,000 to \$7,000,000

**Bridges Rehabilitation/ Replacement:** \$1,000,000 to \$7,000,000

**Check the box to indicate that the project meets this requirement. Yes**

8. The project must comply with the Americans with Disabilities Act.

**Check the box to indicate that the project meets this requirement. Yes**

9. The project must be accessible and open to the general public.

**Check the box to indicate that the project meets this requirement. Yes**

10. The owner/operator of the facility must operate and maintain the project for the useful life of the improvement.

**Check the box to indicate that the project meets this requirement. Yes**

11. The project must represent a permanent improvement with independent utility. The term independent utility means the project provides benefits described in the application by itself and does not depend on any construction elements of the project being funded from other sources outside the regional solicitation, excluding the required non-federal match. Projects that include traffic management or transit operating funds as part of a construction project are exempt from this policy.

**Check the box to indicate that the project meets this requirement. Yes**

12. The project must not be a temporary construction project. A temporary construction project is defined as work that must be replaced within five years and is ineligible for funding. The project must also not be staged construction where the project will be replaced as part of future stages. Staged construction is eligible for funding as long as future stages build on, rather than replace, previous work.

**Check the box to indicate that the project meets this requirement. Yes**

13. The project applicant must send written notification regarding the proposed project to all affected state and local units of government prior to submitting the application.

**Check the box to indicate that the project meets this requirement. Yes**

---

## Roadways Including Multimodal Elements

1. All roadway and bridge projects must be identified as a Principal Arterial (Non-Freeway facilities only) or A-Minor Arterial as shown on the latest TAB approved roadway functional classification map.

**Check the box to indicate that the project meets this requirement. Yes**

**Roadway Expansion and Reconstruction/Modernization projects only:**

2. The project must be designed to meet 10-ton load limit standards.

Check the box to indicate that the project meets this requirement. Yes

**Bridge Rehabilitation/Replacement projects only:**

3. Projects requiring a grade-separated crossing of a Principal Arterial freeway must be limited to the federal share of those project costs identified as local (non-MnDOT) cost responsibility using MnDOTs Cost Participation for Cooperative Construction Projects and Maintenance Responsibilities manual. In the case of a federally funded trunk highway project, the policy guidelines should be read as if the funded trunk highway route is under local jurisdiction.

Check the box to indicate that the project meets this requirement.

4. The bridge must carry vehicular traffic. Bridges can carry traffic from multiple modes. However, bridges that are exclusively for bicycle or pedestrian traffic must apply under one of the Bicycle and Pedestrian Facilities application categories. Rail-only bridges are ineligible for funding.

Check the box to indicate that the project meets this requirement.

5. The length of the bridge must equal or exceed 20 feet.

Check the box to indicate that the project meets this requirement.

6. The bridge must have a sufficiency rating less than 80 for rehabilitation projects and less than 50 for replacement projects. Additionally, the bridge must also be classified as structurally deficient or functionally obsolete.

Check the box to indicate that the project meets this requirement.

---

## Requirements - Roadways Including Multimodal Elements

---

### Project Information-Roadways

<b>County, City, or Lead Agency</b>	Dakota County - 19
<b>Functional Class of Road</b>	A Minor Arterial - Expander (CSAH 31)
<b>Road System</b>	A Minor Arterial - Expander (CSAH 32)
<i>TH, CSAH, MSAS, CO. RD., TWP. RD., CITY STREET</i>	County State Aid Highway (CSAH)
<b>Road/Route No.</b>	31
<i>i.e., 53 for CSAH 53</i>	CSAH 31 (Pilot Knob Road)
<b>Name of Road</b>	CSAH 32 (Cliff Road)
<i>Example; 1st ST., MAIN AVE</i>	
<b>Zip Code where Majority of Work is Being Performed</b>	55122
<b>(Approximate) Begin Construction Date</b>	02/01/2019
<b>(Approximate) End Construction Date</b>	11/24/2019



**TERMINI:(Termini listed must be within 0.3 miles of any work)**

**From:**  
**(Intersection or Address)**

**To:**  
**(Intersection or Address)**

*DO NOT INCLUDE LEGAL DESCRIPTION*

**Or At** CSAH 31 at CSAH 32 Intersection

**Primary Types of Work**

grade, agg base, bit base, bit surf, bike/ped trail, curb & gutter, storm sewer, signal, retaining wall, ped ramps, ADA elements

*Examples: GRADE, AGG BASE, BIT BASE, BIT SURF, SIDEWALK, CURB AND GUTTER, STORM SEWER, SIGNALS, LIGHTING, GUARDRAIL, BIKE PATH, PED RAMPS, BRIDGE, PARK AND RIDE, ETC.*

**BRIDGE/CULVERT PROJECTS (IF APPLICABLE)**

**Old Bridge/Culvert No.:** n/a

**New Bridge/Culvert No.:**

**Structure is Over/Under**  
**(Bridge or culvert name):**

---

**Expander/Augmentor/Connector/Non-Freeway Principal Arterial**

<b>Select one:</b>	Expander
<b>Area</b>	1.503
<b>Project Length</b>	0.36
<b>Average Distance</b>	4.175
<b>Upload Map</b>	1467479130417_CSAH31-RAD.pdf

---

**Reliever: Relieves a Principal Arterial that is a Freeway Facility**

**Facility being relieved**

**Number of hours per day volume exceeds capacity (based on the Congestion Report)** 0

---

**Reliever: Relieves a Principal Arterial that is a Non-Freeway Facility**

**Facility being relieved**

**Number of hours per day volume exceeds capacity (based on the table below)** 0

---

**Non-Freeway Facility Volume/Capacity Table**

Hour	NB/EB Volume	SB/WB Volume	Capacity	Volume exceeds capacity
12:00am - 1:00am			0	
1:00am - 2:00am			0	
2:00am - 3:00am			0	
3:00am - 4:00am			0	
4:00am - 5:00am			0	
5:00am - 6:00am			0	
6:00am - 7:00am			0	
7:00am - 8:00am			0	
8:00am - 9:00am			0	
9:00am - 10:00am			0	
10:00am - 11:00am			0	
11:00am - 12:00pm			0	
12:00pm - 1:00pm			0	
1:00pm - 2:00pm			0	
2:00pm - 3:00pm			0	
3:00pm - 4:00pm			0	
4:00pm - 5:00pm			0	
5:00pm - 6:00pm			0	
6:00pm - 7:00pm			0	
7:00pm - 8:00pm			0	
8:00pm - 9:00pm			0	
9:00pm - 10:00pm			0	
10:00pm - 11:00pm			0	
11:00pm - 12:00am			0	

---

### Measure B: Project Location Relative to Jobs, Manufacturing, and Education

Existing Employment within 1 Mile:	1187
Existing Manufacturing/Distribution-Related Employment within 1 Mile:	46
Existing Students:	0
Upload Map	1467479202873_CSAH31-RegEcon.pdf

---

### Measure C: Current Heavy Commercial Traffic

Location:	CSAH 31 (Pilot Knob ) south of CSAH 32 (Cliff Rd) in Eagan
Current daily heavy commercial traffic volume:	433
Date heavy commercial count taken:	06/14/2016

---

## Measure D: Freight Elements

Response (Limit 1,400 characters; approximately 200 words)

Freight will be safely integrated within the corridor. Utilizing the following freight elements will improve efficiency, security or safety. The CSAH 32 at CSAH 31 intersection will be designed/constructed to 10-ton, include longer/dual left turning lanes, and accommodate turning radius needs of larger trucks. Dakota County 2030 Transportation Plan (Figure 32) identifies CSAH 31 (Pilot Knob) as a proposed 10 Ton Highway and CSAH 32 (Cliff Rd) a proposed/contingent 10 ton highway. Implementation of traffic management technologies on county highways, such as signal operations and signal coordination benefit/improve freight efficiencies by maintaining delivery schedules/traffic flow. Currently, fiber optic cable for signal interconnection is being installed along three miles of CSAH 32 (Cliff Rd) from Slater Rd (Burnsville/Eagan border) including the high volume TH 77 on/off ramp signalized intersection and I-35 on/off ramp signalized intersection to CSAH 31 (project area) in Eagan. In 2019 fiber optic cable for signal interconnection will be installed along four miles of CSAH 31 (Pilot Knob) from CSAH 32 (Cliff Rd) to CSAH 26 (Lone Oak) in Eagan. The installation of fiber optic cable will provide for enhanced traffic management, improved traffic flow, reduced traffic congestion and reduce harmful vehicle emissions along the project corridor

---

## Measure A: Current Daily Person Throughput

Location	CSAH 31 (Pilot Knob) south of CSAH 32 (Cliff)
Current AADT Volume	21200

Existing Transit Routes on the Project N/A

*For New Roadways only, list transit routes that will be moved to the new roadway*

Upload Transit Map 1467131368338\_CSAH31-Transit.pdf

---

## Response: Current Daily Person Throughput

Average Annual Daily Transit Ridership	0
Current Daily Person Throughput	27560.0

---

## Measure B: 2040 Forecast ADT

Use Metropolitan Council model to determine forecast (2040) ADT volume

If checked, METC Staff will provide Forecast (2040) ADT volume

OR

Identify the approved county or city travel demand model to determine forecast (2040) ADT volume	Dakota County Traffic Department 32,000 ADT 2030_using MnDOT projection factor 1.2 Dakota County
--	---

Forecast (2040) ADT volume	35000
----------------------------	-------

---

## Measure A: Project Location and Impact to Disadvantaged Populations

Select one:

Project located in Area of Concentrated Poverty with 50% or more of residents are people of color (ACP50):

Project located in Area of Concentrated Poverty:

Projects census tracts are above the regional average for population in poverty or population of color:

Project located in a census tract that is below the regional average for population in poverty or populations of color or includes children, people with disabilities, or the elderly:	Yes
--	-----

The northerly project area contains areas of above average concentration of race and poverty as shown in census tracts 246, 252 & 253. The project corridor connects areas of employment, commercial, industrial, residential & natural (Lebanon Hills Regional Park, multiple city park) areas. The primary benefit to the community will be realized through increased safety and reduced delays at the intersection for motorists, pedestrian, & transit users. A shared multi-use trail on both sides of the major/minor legs of the intersection will provide for ADA compliant safe crossings for all users. Trails along CSAH 31 Tier I & CSAH 32 Tier II are shown in the Regional Bicycle Transportation Network (RBTN) Corridor map.

The project will include improvements to the multi-use trail, pedestrian ramps and traffic signals which will provide a benefit to those who rely on walking as a mode of transportation, ADA compliant pedestrian ramps will be installed to provide smooth transitions from the sidewalk to the roadway at intersections. Countdown timers will be installed at the intersection to display the time remaining in the pedestrian crossing phase to pedestrians.

Dakota County began a study to help transit planners focus on new east-to-west connections in Dakota County. The CSAH 32 (Cliff Rd) corridor will be evaluated as part of this study. The demand for suburb-to-suburb routes in Dakota County has the potential to be high. According to U.S. census data from 2013?recent year available-nearly half of Dakota county workers live in the county.

Areas below the regional average (poverty/color/disability/elderly) rely heavily on transit. Minnesota Valley Transit Authority (MVTA) provides transit in the project area. At the northerly limits of the project area, the Eagan Transit Station serves bus routes #437,445,446,470,480, & 484. Routes 470 & 480 are direct routes to/from St Paul. Route 446 provides connectivity between the USPS

Response (Limit 2,800 characters; approximately 400 words)

National Distribution Center, Pro Act, Eagandale Center, Mendota Heights Business Park, Brown College, Eagan City Hall, Library, High School & Middle School. Route 484 provides connectivity between multi-housing areas (apartment), senior living, to Cedar Grove Transit Station (Cedar BRT Red Line) and access to business campus areas (Blue Cross/Blue Shield, Delta Dental). Approximately 1.4 miles to the west of the intersection is the Blackhawk Park & Ride serving MVTA routes 438,470,472, & 480. Route 470 runs along the employment corridors of 35E,494,I-35. Route 438 connects to the Cedar Grove Transit Station (Cedar BRT Red Line).

*The response should address the benefits, impacts, and mitigation for the populations affected by the project.*

Upload Map

1468333268999\_CSAH31-SocEcon.pdf

### Measure B: Affordable Housing

City/Township	Segment Length in Miles (Population)
City of Eagan	0.36
	0

### Total Project Length

Total Project Length (Total Population)	0.36
---	------

### Affordable Housing Scoring - To Be Completed By Metropolitan Council Staff

City/Township	Segment Length (Miles)	Total Length (Miles)	Score	Segment Length/Total Length	Housing Score Multiplied by Segment percent
		0	0	0	0

### Affordable Housing Scoring - To Be Completed By Metropolitan Council Staff

Total Project Length (Miles)	0.36
Total Housing Score	0

## Measure A: Year of Roadway Construction

Year of Original Roadway Construction or Most Recent Reconstruction	Segment Length	Calculation	Calculation 2
1988	0.36	715.68	1988.0
	<b>0</b>	<b>716</b>	<b>1988</b>

### Average Construction Year

Weighted Year 1988

### Total Segment Length (Miles)

Total Segment Length 0.36

## Measure B: Geometric, Structural, or Infrastructure Improvements

Improving a non-10-ton roadway to a 10-ton roadway:

Yes

Response (Limit 700 characters; approximately 100 words)

The project will construct the CSAH 31 (Pilot Knob) and CSAH 32 (Cliff Rd) intersection to 10-ton roadway standards. Dakota County 2030 Transportation Plan (Figure 32) identifies CSAH 31 (Pilot Knob) as a proposed 10 Ton Highway and CSAH 32 (Cliff Rd) a proposed/contingent 10 ton highway. As opportunities present themselves, the roadways in their entirety will be reconstructed to 10-ton standards. Dakota County 2030 Transportation Plan, Management Policy M4, 10-Ton Route System Implementation: Work with local jurisdictions in implementing a 10-ton route system.

Improved clear zones or sight lines:

Yes

Response (Limit 700 characters; approximately 100 words)

The project is designed for clear zones that allow a driver to stop safely, or regain control of a vehicle that has left the roadway. Sign supports within the clear zone will be breakaway or shielded by a barrier. Trees are the single most commonly struck objects in serious roadside collisions; all trees will be removed from the clear zone. Left turns from main highways across two or three lanes will be designed-aligned to provide good visibility. Intersection sight lines, visibility will be improved with updated LED intersection lighting.

Improved roadway geometrics:

Yes

Response (Limit 700 characters; approximately 100 words)

Intersection configuration will be four lanes divided, concrete median, dedicated right turn lane and dedicated dual left turn lanes. Existing traffic signal is obsolete, new signal will have improved signal heads, vehicle detection & lighting. Intersection will be reconstructed to improve operations, safety, water quality (storm sewer) & deterioration that occurred over the years. Dual left turn lanes will reduce red-light running and increase throughput on the roadways. Project will be designed to ensure that all roadway geometrics, such as turning radii, pavement depths & road widths accommodate the range of transit vehicles in operating service; and large trucks.

Access management enhancements:

Yes



Response (Limit 700 characters; approximately 100 words)

Project meets access spacing guidelines. Dakota County stipulates specific access spacing requirements for highway types through: 2030 Transportation Plan; Plat Commission; permits & corridor studies. Strategies to ensure access & mobility are properly balanced consistent with the function of the roadway will reduce delay, improve traffic movement & create a safer system through implementing access management principles to allow the highway system to perform at an acceptable level of service, thus preserve/maximize roadway safety/efficiency. County will pursue access spacing opportunities as new plats come under review/approval of the County Plat Commission.

Vertical/horizontal alignments improvements:

Yes

The projects horizontal and vertical alignments are consistent with the topography, preserve the developed properties along the road and incorporate community values. The project alignment follows the natural contours of the land and does not affect aesthetic, scenic, historic, or cultural resources. Vertical alignment will be determined by natural terrain, number of trucks or other heavy vehicles in the traffic stream, basic roadway cross-section, and avoidance where possible of natural environmental factors (wetlands, historic, cultural & community resources). The project will meet all applicable State & Federal design requirements.

Response (Limit 700 characters; approximately 100 words)

Improved stormwater mitigation:

Yes

Response (Limit 700 characters; approximately 100 words)

Reconstruction of the intersection provide a smooth surface & improves drainage. Drainage structures & utility manholes require adjustments to address settlement and deterioration that has occurred over the years. Existing curb & gutter is in need of replacement due to settlement and impacts from snow maintenance. Drainage improvements to the project will be constructed with the installation of additional turn lanes & new impervious surfaces including upgrading the existing storm sewer for capacity and providing necessary ponding per the National Pollutant Discharge Elimination System (NPDES) and Local Watershed requirements.

Signals/lighting upgrades:

Yes

The aging (1988) signal system/controller cabinet, has surpassed the useful life and be replaced as part of this project. The signal system will have P-T-Z cameras mounted to allow for real time intersection monitoring. Dual left turns will increase vehicle throughput. Intersection will be ADA compliant (pedestrian ramps, countdown timers, median islands, accessible pedestrian signals & crosswalk markings). This intersection will be fiber interconnected with 3-miles of CSAH 32 east/west signals & 4-miles of CSAH 31 north/south signals. New intersection lighting will be energy efficient LED technology that will help to increase safety/visibility at the intersection.

Response (Limit 700 characters; approximately 100 words)

Other Improvements

Yes

Response (Limit 700 characters; approximately 100 words)

The existing signage along the corridor is faded and requires replacement to improve wayfinding and driver compliance. The Dakota County East/West Transit Study has identified the CSAH 32 corridor as a transit corridor for analysis in the Study. CSAH 32 (Tier II) & CSAH 31 (Tier I) are identified in the proposed Regional Bicycle Transportation Network (RBTN) Corridor map. The trails along CSAH 31 & CSAH 32 connect directly to Lebanon Hills Regional Park as well as numerous city parks in the project area. Seven miles of fiber interconnected traffic signals will improve roadway operations.

### Measure A: Congestion Reduction/Air Quality

Total Peak Hour Delay Per Vehicle Without The Project	Total Peak Hour Delay Per Vehicle With The Project	Total Peak Hour Delay Per Vehicle Reduced by Project	Volume (Vehicles per hour)	Total Peak Hour Delay Reduced by the Project:	EXPLANATION of methodology used to calculate railroad crossing delay, if applicable.	Synchro or HCM Reports
43.0	32.0	11.0	3383	37213.0	n/a	14674803590 26_CH31CH3 2 Synchro - PM - Peak Hour Report.pdf

### Total Delay

Total Peak Hour Delay Reduced 37213.0

### Measure B: Roadway projects that do not include new roadway segments or railroad grade-separation elements

Total (CO, NOX, and VOC) Peak Hour Emissions Per Vehicle without the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions Per Vehicle with the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions Reduced Per Vehicle by the Project (Kilograms):	Volume (Vehicles Per Hour):	Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms):
0.005	0.004	0.001	3383.0	3.383
<b>0</b>	<b>0</b>		<b>3383</b>	<b>3</b>

## Total

Total Emissions Reduced:	3.383
Upload Synchro Report	1467480692078_CH31CH32 Synchro - PM - Peak Hour Report.pdf

## Measure B: Roadway projects that are constructing new roadway segments, but do not include railroad grade-separation elements (for Roadway Expansion applications only):

Total (CO, NOX, and VOC) Peak Hour Emissions Per Vehicle without the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions Per Vehicle with the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions Reduced Per Vehicle by the Project (Kilograms):	Volume (Vehicles Per Hour):	Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms):
0	0		0	0

## Total Parallel Roadways

Emissions Reduced on Parallel Roadways	0
Upload Synchro Report	

## New Roadway Portion:

Cruise speed in miles per hour with the project:	0
Vehicle miles traveled with the project:	0
Total delay in hours with the project:	0
Total stops in vehicles per hour with the project:	0
Fuel consumption in gallons:	0
Total (CO, NOX, and VOC) Peak Hour Emissions Reduced or Produced on New Roadway (Kilograms):	0

EXPLANATION of methodology and assumptions used:(Limit 1,400 characters; approximately 200 words)

Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms): 0.0

---

## Measure B: Roadway projects that include railroad grade-separation elements

Cruise speed in miles per hour without the project:	0
Vehicle miles traveled without the project:	0
Total delay in hours without the project:	0
Total stops in vehicles per hour without the project:	0
Cruise speed in miles per hour with the project:	0
Vehicle miles traveled with the project:	0
Total delay in hours with the project:	0
Total stops in vehicles per hour with the project:	0
Fuel consumption in gallons (F1)	0
Fuel consumption in gallons (F2)	0
Fuel consumption in gallons (F3)	0
Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms):	0

EXPLANATION of methodology and assumptions used:(Limit 1,400 characters; approximately 200 words)

---

## Transit Projects Not Requiring Construction

*If the applicant is completing a transit or TDM application that is operations only, check the box and do not complete the remainder of the form. These projects will receive full points for the Risk Assessment. Park-and-Ride and other transit construction projects require completion of the Risk Assessment below.*

**Check Here if Your Transit Project Does Not Require Construction**

---

## Measure A: Risk Assessment

### 1) Project Scope (5 Percent of Points)

Meetings or contacts with stakeholders have occurred

100%

Stakeholders have been identified Yes

40%

Stakeholders have not been identified or contacted

0%

**2)Layout or Preliminary Plan (5 Percent of Points)**

Layout or Preliminary Plan completed

100%

Layout or Preliminary Plan started

Yes

50%

Layout or Preliminary Plan has not been started

0%

Anticipated date or date of completion

12/01/2018

**3)Environmental Documentation (5 Percent of Points)**

EIS

EA

PM

Yes

**Document Status:**

Document approved (include copy of signed cover sheet)

100%

Document submitted to State Aid for review

75%

date submitted

Document in progress; environmental impacts identified; review request letters sent

50%

Document not started

Yes

0%

Anticipated date or date of completion/approval

06/01/2018

**4)Review of Section 106 Historic Resources (10 Percent of Points)**

No known historic properties eligible for or listed in the National Register of Historic Places are located in the project area, and project is not located on an identified historic bridge

100%

Historic/archeological review under way; determination of no historic properties affected or no adverse effect anticipated

Yes

80%

Historic/archaeological review under way; determination of adverse effect anticipated

40%

Unsure if there are any historic/archaeological resources in the project area

0%

Anticipated date or date of completion of historic/archeological review:

04/01/2018

**Project is located on an identified historic bridge**

**5)Review of Section 4f/6f Resources (10 Percent of Points)**

*4(f) Does the project impacts any public parks, public wildlife refuges, public golf courses, wild & scenic rivers or public private historic properties?*

*6(f) Does the project impact any public parks, public wildlife refuges, public golf courses, wild & scenic rivers or historic property that was purchased or improved with federal funds?*

**No Section 4f/6f resources located in the project area**

100%

**No impact to 4f property. The project is an independent bikeway/walkway project covered by the bikeway/walkway Negative Declaration statement; letter of support received**

100%

**Section 4f resources present within the project area, but no known adverse effects**

Yes

80%

**Project impacts to Section 4f/6f resources likely coordination/documentation has begun**

50%

**Project impacts to Section 4f/6f resources likely coordination/documentation has not begun**

30%

**Unsure if there are any impacts to Section 4f/6f resources in the project area**

0%

**6)Right-of-Way (15 Percent of Points)**

**Right-of-way, permanent or temporary easements not required**

100%

**Right-of-way, permanent or temporary easements has/have been acquired**

100%

**Right-of-way, permanent or temporary easements required, offers made**

75%

**Right-of-way, permanent or temporary easements required, appraisals made**

50%

**Right-of-way, permanent or temporary easements required, parcels identified**

Yes

25%

**Right-of-way, permanent or temporary easements required, parcels not identified**

0%

**Right-of-way, permanent or temporary easements identification has not been completed**

0%

**Anticipated date or date of acquisition**

12/01/2018

**7)Railroad Involvement (25 Percent of Points)**

**No railroad involvement on project**

Yes

100%

**Railroad Right-of-Way Agreement is executed (include signature page)**

100%

**Railroad Right-of-Way Agreement required; Agreement has been initiated**

60%

**Railroad Right-of-Way Agreement required; negotiations have begun**

40%

**Railroad Right-of-Way Agreement required; negotiations not begun**

0%

**Anticipated date or date of executed Agreement**

**8)Interchange Approval (15 Percent of Points)\***

*\*Please contact Karen Scheffing at MnDOT (Karen.Scheffing@state.mn.us or 651-234-7784) to determine if your project needs to go through the Metropolitan Council/MnDOT Highway Interchange Request Committee.*

**Project does not involve construction of a new/expanded interchange or new interchange ramps**

Yes

100%

**Interchange project has been approved by the Metropolitan Council/MnDOT Highway Interchange Request Committee**

100%

**Interchange project has not been approved by the Metropolitan Council/MnDOT Highway Interchange Request Committee**

0%

**9)Construction Documents/Plan (10 Percent of Points)**

**Construction plans completed/approved (include signed title sheet)**

100%

**Construction plans submitted to State Aid for review**

75%

**Construction plans in progress; at least 30% completion**

Yes

50%

**Construction plans have not been started**



0%

Anticipated date or date of completion 09/01/2018

**10)Letting**

Anticipated Letting Date 02/07/2019

---

**Measure A: Roadway Projects that do not Include Railroad Grade-Separation Elements**

Crash Modification Factor Used: 1543.0

Used CMF 1543,1544,1545 (unable to list all above)

Rationale for Crash Modification Selected:

Crash Modification Factors do not have star ratings and are not in the Highway Safety Manual. They were developed Gan et al for the Florida Transportation Department and included a survey of other State Departments of Transportation. Specific Values were chosen as they are very similar to those published in Chapter 12 of the Signalized Intersections: Informational Guide published by the FHWA.<http://www.fhwa.dot.gov/publications/research/safety/04091/12.cfm#c1212> (Attached 1543,1544,1545)

*(Limit 1400 Characters; approximately 200 words)*

Project Benefit (\$) from B/C Ratio \$1,886,973.00

Worksheet Attachment 1468336830709\_benefit-cost-worksheet-aug2015- CSAH 31 & CSAH 32.xls

---

**Roadway projects that include railroad grade-separation elements:**

Current AADT volume: 0

Average daily trains: 0

Crash Risk Exposure eliminated: 0

---

**Measure A: Multimodal Elements and Existing Connections**

Bike/Pedestrian trails and crosswalks will be upgraded to current ADA standards as part of the project. The 27 year old trails & traffic signal at CSAH 31 & CSAH 32 will be replaced with new signal system/controller cabinet, accessible & audible pedestrian signal, count down timers, & ADA standards being applied to provide safe pedestrian and bicycle movements through the intersection.

The bike/pedestrian trails on both sides of CSAH 31 (Tier I) and CSAH 32 (Tier II) are included in the proposed Regional Bicycle Transportation Network (RBTN) Corridors map. Trails connect people to housing, recreation (city parks, Lebanon Hills Regional Park, Big Rivers Regional Trail) employment (commercial, office park, retail, industrial) and transit. MVTA Eagan Transit Station is located directly to the north of the project area (across I-35). This Eagan Transit Station features parking deck, with some 750 parking spaces for bus passengers and retail patrons. The Blackhawk Park & Ride Station is 1.4 miles west of the intersection project. Dakota County is developing a comprehensive transit system, bicycle and pedestrian network and other non-automobile modes for people to maximize the efficiency of the transportation system by providing safe, timely and efficient connections between communities, activity generators and employment centers.

Response (Limit 2,800 characters; approximately 400 words)

Pedestrian and bicycle facilities in the cities of Dakota County are serving the dual role of providing recreational value as well as viable options for commuters (for work or shopping). The expansion of commuter pedestrian and bicycle use is expected into the future with the expansion of transit facilities, providing an alternative to increased costs of automobile travel. The County is working closely with local communities to improve walkability, and develop opportunities for residents to walk and bike for transportation and

recreation.

The County has begun a study to plan for new east-west transit connections in Dakota County. The CSAH 32 (Cliff Rd) corridor will be evaluated as part of this study. The demand for suburb-to-suburb routes in Dakota County has the potential to be high. According to U.S. census data from 2013 (most recent year available), nearly half of Dakota county workers also live in the county. Current transit in the metro region is "hub and spoke" to/from the core. There's more demand for services that don't follow this traditional model.

---

### Measure A: Cost Effectiveness

Total Project Cost (entered in Project Cost Form):	\$3,918,700.00
Enter Amount of the Noise Walls:	\$0.00
Total Project Cost subtract the amount of the noise walls:	\$3,918,700.00
Points Awarded in Previous Criteria	
Cost Effectiveness	\$0.00

---

### Other Attachments

File Name	Description	File Size
(CSAH 31) Pilot Knob Rd. @ (CSAH 32) Cliff Rd. (2013 - 2015).xls	MnDOT Crash	151 KB
1543.pdf	CRF 1543	125 KB
1544.pdf	CRF 1544	125 KB
1545.pdf	CRF 1545	125 KB
31 & 32 LAYOUT DUAL TURN LANES.pdf	Layout: CSAH 31 (Pilot Knob) at CSAH 32 (Cliff) Intersection in City of Eagan	3.0 MB
benefit-cost-worksheet-aug2015- CSAH 31 & CSAH 32.xls	Bene/Cost Worksheet	84 KB
CSAH31-10TonSystem.pdf	Dakota County 10 Ton System Project Location	444 KB
CSAH32-PlanCoverSheet.pdf	CSAH 31 (Pilot Knob) at CSAH 32 (Cliff Rd) intersection constructed in 1988 as part of larger roadway construction plan	927 KB
Dakota County Resolution June 21 2016.pdf	Dakota County Resolution	178 KB
Eagan - Fed Fund Support 31-32 June 2016.pdf	Eagan Letter - Fund/Support Project	39 KB
Existing_PM_Timing - Report.pdf	Existing PM Timing Report	41 KB
FHWA Publication- Dbl Lefts.pdf	FHWA Publication - Double Lefts	128 KB
MVTA-TransitRoutes.pdf	Minnesota Valley Transit Authority (MVTA) Transit Routes near CSAH 31 at CSAH 32 in Eagan	377 KB
Proposed_PM_Timing - Report.pdf	Proposed PM Timing Report	38 KB
RADCsah32DakoRM.pdf	RADCsah32DakoRM	223 KB
RBTN Corridors.pdf	CSAH 31 & CSAH 32 Intersection Project Location in relation to Regional Bicycle Transportation Network Corridors (Tier I & Tier II)	1.5 MB
RECCsah32DakoRM.pdf	RECCsah32DakoRM	293 KB
SECCsah32DakoRM.pdf	SECCsah32DakoRM	253 KB
Synchro - PM - Peak Hour Report.pdf	Synchro PM Peak Hour Report	80 KB
TRNCsah32DakoRM.pdf	TRNCsah32DakoRM	322 KB
Trucks-CSAH 31CSAH 32 6-14-16.pdf	Heavy Commercial Count June 14, 2016	39 KB

# Roadway Area Definition

## Results

Project Length: 0.36 miles

Project Area: 1.503 sq mi



○ Project Points    □ Project Area

— Project



Created: 6/17/2016  
LandscapeRSA1



For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



# Regional Economy

Roadway Reconstruction/Modernization Project: CSAH 32 at CSAH 31 Intersection Improvements | Map ID: 1466189428988

## Results

**WITHIN ONE MI of project:**

Totals by City:

### Apple Valley

Population: 596

Employment: 102

Mfg and Dist Employment: 0

### Eagan

Population: 10525

Employment: 1076

Mfg and Dist Employment: 43

### Rosemount


Population: 193

Employment: 9

Mfg and Dist Employment: 3

Postsecondary Students:

0



 Project Points  Project Area

 Project



Created: 6/17/2016  
LandscapeRSA5




For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



NCompass Technologies





Results

Transit with a Direct Connection to project:  
 -- NONE --

\*indicates Planned Alignments

- Project Points
- Project Area
- Project
- Blue Line
- Red Line
- BRT, Orange Line
- Arterial BRT
- BRT, Red Line - Phase 2
- Planned Alignments**



Created: 6/17/2016  
 LandscapeRSA3




For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>









NCompass Technologies

Results

Project located in a census tract that is below the regional average for population in poverty or populations of color, or includes children, people with disabilities, or the elderly:  
(0 to 12 Points)



-  Project Points
-  Project
-  Project Area
-  Area of Concentrated Poverty > 50% residents of color
-  Area of Concentrated Poverty
-  Above reg'l avg conc of race/poverty



Created: 6/17/2016  
LandscapeRSA2



For complete disclaimer of accuracy, please visit <http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



NCompass Technologies



---

54: CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

---

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	43
CO Emissions (kg)	10.87
NOx Emissions (kg)	2.12
VOC Emissions (kg)	2.52

54: CSAH 31 & CSAH 32

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	32
CO Emissions (kg)	10.32
NOx Emissions (kg)	2.01
VOC Emissions (kg)	2.39

5. Congestion Reduction / Air Quality RESPONSE A (Calculation):

CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total Peak Hour Delay/Vehicle without the Project (Seconds/Vehicle): 43 sec/veh
- Total Peak Hour Delay/Vehicle with the Project (Seconds/Vehicle): 32 sec/veh
- Total Peak Hour Delay/Vehicle Reduced by the Project (Seconds/Vehicle): 11 sec/veh
- Volume (Vehicles Per Hour): 3383 vph
- Total Peak Hour Delay Reduced by the Project (Seconds): 37213 sec

5. Congestion Reduction / Air Quality RESPONSE B (Calculation):

CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle without the Project (Kilograms): 0.0046 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle with the Project (Kilograms): 0.0044 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced/Vehicle by the Project (Kilograms): 0.0002 kg
- Volume (Vehicles Per Hour): 3383 vph
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms): 0.677 kg

---

54: CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

---

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	43
CO Emissions (kg)	10.87
NOx Emissions (kg)	2.12
VOC Emissions (kg)	2.52

54: CSAH 31 & CSAH 32

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	32
CO Emissions (kg)	10.32
NOx Emissions (kg)	2.01
VOC Emissions (kg)	2.39

5. Congestion Reduction / Air Quality RESPONSE A (Calculation):

CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total Peak Hour Delay/Vehicle without the Project (Seconds/Vehicle): 43 sec/veh
- Total Peak Hour Delay/Vehicle with the Project (Seconds/Vehicle): 32 sec/veh
- Total Peak Hour Delay/Vehicle Reduced by the Project (Seconds/Vehicle): 11 sec/veh
- Volume (Vehicles Per Hour): 3383 vph
- Total Peak Hour Delay Reduced by the Project (Seconds): 37213 sec

5. Congestion Reduction / Air Quality RESPONSE B (Calculation):

CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle without the Project (Kilograms): 0.0046 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle with the Project (Kilograms): 0.0044 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced/Vehicle by the Project (Kilograms): 0.0002 kg
- Volume (Vehicles Per Hour): 3383 vph
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms): 0.677 kg



## CMF / CRF Details

**CMF ID:** 1543

**Install left-turn lane (double)**

**Description:**

**Prior Condition:** *No Prior Condition(s)*

**Category:** Intersection geometry

**Study:** [Update of Florida Crash Reduction Factors and Countermeasures to Improve the Development of District Safety Improvement Projects, Gan et al., 2005](#)

**Star Quality Rating:**

[Cannot Be Rated](#)

### Crash Modification Factor (CMF)

**Value:** 0.71

**Adjusted Standard Error:**

**Unadjusted Standard Error:**

### Crash Reduction Factor (CRF)

<b>Value:</b>	29 (This value indicates a <b>decrease</b> in crashes)
<b>Adjusted Standard Error:</b>	
<b>Unadjusted Standard Error:</b>	

**Applicability**

<b>Crash Type:</b>	Rear end
<b>Crash Severity:</b>	Fatal,Serious injury,Minor injury
<b>Roadway Types:</b>	Not specified
<b>Number of Lanes:</b>	
<b>Road Division Type:</b>	
<b>Speed Limit:</b>	
<b>Area Type:</b>	
<b>Traffic Volume:</b>	
<b>Time of Day:</b>	

***If countermeasure is intersection-based***

<b>Intersection Type:</b>	
<b>Intersection Geometry:</b>	
<b>Traffic Control:</b>	
<b>Major Road Traffic Volume:</b>	

**Minor Road Traffic  
Volume:**

### Development Details

**Date Range of Data  
Used:**

**Municipality:**

**State:**

**Country:**

**Type of Methodology  
Used:**

Simple before/after

**Sample Size Used:**

### Other Details

**Included in Highway  
Safety Manual?**

No

**Date Added to  
Clearinghouse:**

**Comments:**

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained*

*in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*





## CMF / CRF Details

CMF ID: 1544

Install left-turn lane (double)

Description:

Prior Condition: *No Prior Condition(s)*

Category: Intersection geometry

Study: [Update of Florida Crash Reduction Factors and Countermeasures to Improve the Development of District Safety Improvement Projects, Gan et al., 2005](#)

Star Quality Rating:

[Cannot Be Rated](#)

### Crash Modification Factor (CMF)

Value: 0.68

Adjusted Standard Error:

Unadjusted Standard Error:

### Crash Reduction Factor (CRF)

<b>Value:</b>	32 (This value indicates a <b>decrease</b> in crashes)
<b>Adjusted Standard Error:</b>	
<b>Unadjusted Standard Error:</b>	

**Applicability**

<b>Crash Type:</b>	Rear end
<b>Crash Severity:</b>	Property damage only (PDO)
<b>Roadway Types:</b>	Not specified
<b>Number of Lanes:</b>	
<b>Road Division Type:</b>	
<b>Speed Limit:</b>	
<b>Area Type:</b>	
<b>Traffic Volume:</b>	
<b>Time of Day:</b>	

***If countermeasure is intersection-based***

<b>Intersection Type:</b>	
<b>Intersection Geometry:</b>	
<b>Traffic Control:</b>	
<b>Major Road Traffic Volume:</b>	

**Minor Road Traffic  
Volume:**

### Development Details

**Date Range of Data  
Used:**

**Municipality:**

**State:**

**Country:**

**Type of Methodology  
Used:**

Simple before/after

**Sample Size Used:**

### Other Details

**Included in Highway  
Safety Manual?**

No

**Date Added to  
Clearinghouse:**

**Comments:**

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained*

*in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*



## CMF / CRF Details

**CMF ID:** 1545

**Install left-turn lane (double)**

**Description:**

**Prior Condition:** *No Prior Condition(s)*

**Category:** Intersection geometry

**Study:** [Update of Florida Crash Reduction Factors and Countermeasures to Improve the Development of District Safety Improvement Projects, Gan et al., 2005](#)

**Star Quality Rating:**

[Cannot Be Rated](#)

### Crash Modification Factor (CMF)

**Value:** 0.8

**Adjusted Standard Error:**

**Unadjusted Standard Error:**

### Crash Reduction Factor (CRF)

<b>Value:</b>	20 ( <i>This value indicates a <b>decrease</b> in crashes</i> )
<b>Adjusted Standard Error:</b>	
<b>Unadjusted Standard Error:</b>	

**Applicability**

<b>Crash Type:</b>	Angle
<b>Crash Severity:</b>	Fatal,Serious injury,Minor injury
<b>Roadway Types:</b>	Not specified
<b>Number of Lanes:</b>	
<b>Road Division Type:</b>	
<b>Speed Limit:</b>	
<b>Area Type:</b>	
<b>Traffic Volume:</b>	
<b>Time of Day:</b>	

***If countermeasure is intersection-based***

<b>Intersection Type:</b>	
<b>Intersection Geometry:</b>	
<b>Traffic Control:</b>	
<b>Major Road Traffic Volume:</b>	

**Minor Road Traffic  
Volume:**

### Development Details

**Date Range of Data  
Used:**

**Municipality:**

**State:**

**Country:**

**Type of Methodology  
Used:**

Simple before/after

**Sample Size Used:**

### Other Details

**Included in Highway  
Safety Manual?**

No

**Date Added to  
Clearinghouse:**

**Comments:**

---


This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center





*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained*


*in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*



# C.S.A.H. 31 (PILOT KNOB ROAD) & C.S.A.H. 32 (CLIFF ROAD) INTERSECTION IMPROVEMENTS




LEGEND	
	CONCRETE SURFACE
	NEW PAVEMENT SURFACE
	BITUMINOUS TRAIL
	RETAINING WALL





# 10-Ton Highways



Prepared by:  
Dakota County Office of GIS, 1/2012.

STANDARD SYMBOLS (EXCEPT SIGNAL PLAN)

	EXISTING	PROPOSED
SECTION LINE	---	---
QUARTER LINE	---	---
SIXTEENTH LINE	---	---
LOT LINE	---	---
RIGHT OF WAY	---	---
CENTER LINE	---	---
POINT OF INTERSECTION	△	△
POINT ON LINE	○	○
EASEMENT	---	---
BITUMINOUS CURB	---	---
CONCRETE CURB & GUTTER	---	---
PRECAST CONCRETE CURB	---	---
CONCRETE SIDEWALK	---	---
BITUMINOUS PATHWAY BUILDING	---	---
(LABELED) FENCE	---	---
GUARDRAIL	---	---
SIGN	○	○
SOIL BORING	⊗	⊗
HANDHOLE	○	○
SIGNAL LIGHT	⊕	⊕
CONDUIT	---	---
MANHOLE	○	○
CATCHBASIN	○	○
STORM SEWER	---	---
SANITARY SEWER	---	---
BENCHMARK	⊙	⊙
GATE VALVE	⊗	⊗
FIRE HYDRANT	⊙	⊙
CURB STOP BOX	○	○
WATERMAIN	---	---
GAS VALVE	⊗	⊗
GAS LINE	---	---
TELE OR POWER MANHOLE	○	○
TELE OR POWER POLE	○	○
PETROLEUM PIPELINE	---	---
BARRIER POWER CONDUIT	---	---
CULVERT	---	---
BURIED TELEPHONE CABLE	---	---
BURIED TELEPHONE CONDUIT	---	---
POWER LINE	---	---
CABLE TV BOX	⊕	⊕
MAIL BOX	○	○
TELEPHONE PEDESTAL	⊕	⊕

\* SEE TECHNICAL MANUAL FOR PLAN SYMBOLS ON SIGNAL PLAN

# MINNESOTA DEPARTMENT OF TRANSPORTATION DAKOTA COUNTY

733


## CONSTRUCTION PLAN FOR GRADING, R/W, BITUMINOUS SURFACING, DRAINAGE, WATERMAIN, & SIGNALS

**S.A.P. 19 - 631 - 17** LOCATED ON PILOT KNOB ROAD FROM REBECCA LANE TO T.H. 35E

**S.A.P. 19 - 632 - 11** LOCATED ON CLIFF ROAD FROM LAKE PARK DRIVE TO CHES MAR DRIVE

**S.A.P. 19 - 630 - 03** LOCATED ON DIFFLEY ROAD FROM 2,100' (APPROXIMATELY) WEST OF PILOT KNOB RD. TO 2,600' (APPROXIMATELY) EAST OF PILOT KNOB RD.

STATE AID PROJ. NO.	MINN. PROJ. NO.	GROSS LENGTH	BRIDGES-LENGTH	EXCEPTIONS-LENGTH	NET LENGTH	MILE POINT
19-631-17	19-631-17	16,100 FEET 3.049 MILES	0.00 FEET 0.000 MILES	0.00 FEET 0.000 MILES	16,100 FEET 3.049 MILES	TO MILE POINT
19-632-11	19-632-11	2,525 FEET 0.478 MILES	0.00 FEET 0.000 MILES	0.00 FEET 0.000 MILES	2,525 FEET 0.478 MILES	TO MILE POINT
19-630-03	19-630-03	4,775 FEET 0.904 MILES	0.00 FEET 0.000 MILES	0.00 FEET 0.000 MILES	4,775 FEET 0.904 MILES	TO MILE POINT



PROJECT LOCATION,  
DAKOTA COUNTY  
OAKDALE DISTRICT

SCALES

PLAN	50'
PROFILE	50'
INDEX MAP	1 MILE
GENERAL LAYOUT	N/A

Design Speed 45 MPH  
Based on STOPPING Sight Distance  
Height of eye 3.50' Height of object 0.5'  
Design Speed not achieved at: DIFFLEY ROAD (SAP 19-630-03)

STA 124+00	TO STA 132+05	MPH 40
STA 133+25	TO STA 134+17	MPH 35
STA 145+90	TO STA 153+90	MPH 35
STA 112+56	TO STA 123+56	MPH 40

GOVERNING SPECIFICATIONS  
THE 1983 EDITION OF THE MINNESOTA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AS AMENDED BY SUPPLEMENTAL SPECIFICATION (CURRENT EDITION) SHALL GOVERN

DESIGN LOADING — 9 TON

MINN. PROJ. NO. \_\_\_\_\_

INDEX

1	TITLE SHEET
2-6	ESTIMATED QUANTITIES
7	STAGING LAYOUT GRADING AND CONSTRUCTION
8	EARTHWORK SUMMARY
9-10	PUBLIC UTILITIES TABULATIONS
11	PUBLIC UTILITIES AND STANDARD PLATES
12-24	QUANTITY TABULATIONS
25-26	EROSION CONTROL
27-30	UTILITY DETAILS
31	PAVING DETAILS
32	UNDERWATER EMBANKMENT, STONE RETAINING WALL AND MUCK EXCAVATION DETAILS
33-38	TYPICAL SECTIONS
39	MONUMENT TIES
40-65	R/W PLATS
66-84	PAVING PLANS
85-87	CROSS STREET PROFILES, CHES MAR IMPROVEMENT, WELL SITE PARK PLAN
88-106	STORM SEWER AND UTILITY PLANS
107-112	WATERMAIN PLANS
113-120A	DRAINAGE PROFILES
121-238	CROSS SECTIONS
239-247	TRAFFIC SIGNALS

NOTE:  
SHEET 120A HAS BEEN ADDED  
THIS PLAN CONTAINS 248 SHEETS

I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY REGISTERED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.

DATE 3/21/87 REG. NO. 12007 ENGR. Howard J. Barber

Approved David J. Curda 4-3-87  
DAKOTA COUNTY ENGINEER

Approved Thomas A. Balliet 5-21-1987  
CITY ENGINEER, CITY OF EAGAN

Recommended for Approval \_\_\_\_\_ 19\_\_\_\_  
DISTRICT STATE AID PLANS ENGINEER

Recommended for Approval Julia Skallman 7/12/87  
STATE AID PLANS AND SPECS ENGINEER

Approved H. Wittberg 7-2-1987  
MN/DOT TRAFFIC ENGINEER

Approved 7/14/87 \_\_\_\_\_  
STATE AID ENGINEER

Approved as revised 8-14-88 \_\_\_\_\_  
for State Aid Engineer

Right of Way Approval \_\_\_\_\_ 19\_\_\_\_  
DIRECTOR OF RIGHT OF WAY OPERATIONS

Recommended for Approval \_\_\_\_\_ 19\_\_\_\_  
HYDRAULICS ENGINEER

Recommended for Approval \_\_\_\_\_ 19\_\_\_\_  
DISTRICT ENGINEER

Recommended for Approval \_\_\_\_\_ 19\_\_\_\_  
TRANSPORTATION PLANS ENGINEER

Recommended for Approval \_\_\_\_\_ 19\_\_\_\_  
DESIGN SERVICES DIRECTOR

Approved \_\_\_\_\_ 19\_\_\_\_  
DIRECTOR, OFFICE OF ENGINEER SERVICES

DESIGN DESIGNATION	DESIGN DESIGNATION	DESIGN DESIGNATION
S.A.P. 19-631-17	S.A.P. 19-632-11	S.A.P. 19-630-03
ADT (Current Year) 1986 = 10,500	ADT (Current Year) 1986 = 10,000	ADT (Current Year) 1986 = 6,000
ADT (Future Year) 2006 = 24,300	ADT (Future Year) 2006 = 13,200	ADT (Future Year) 2006 = 17,400
DHV (Design Hr. Vol.) = 10%	DHV (Design Hr. Vol.) = 10%	DHV (Design Hr. Vol.) = 10%
D (Directional Distr.) = 60/40%	D (Directional Distr.) = 60/40	D (Directional Distr.) = 60/40
T (Heavy Commercial) = 75%	T (Heavy Commercial) = 75%	T (Heavy Commercial) = 75%
R-VALUE = 30	R-VALUE = 30	R-VALUE = 30
Σ N18 (20 Years) = 1,611,791	Σ N18 (20 Years) = 1,147,619	Σ N18 (20 Years) = 1,047,096

DEPARTMENT OF TRANSPORTATION  
FEDERAL HIGHWAY ADMINISTRATION  
APPROVED \_\_\_\_\_  
DIVISION ADMINISTRATOR DATE \_\_\_\_\_

**BOARD OF COUNTY COMMISSIONERS  
DAKOTA COUNTY, MINNESOTA**

June 21, 2016  
Motion by Commissioner Workman

Resolution No. 16-337  
Second by Commissioner Holberg

---

**Approval Of Grant Application Submittals For Transportation Advisory Board 2016 Federal Funding Solicitation Process**

WHEREAS, the Transportation Advisory Board (TAB) is requesting project submittals for federal funding under the Fixing America's Surface Transportation (FAST) Act; and

WHEREAS, these federal programs fund up to 80 percent of project construction costs; and

WHEREAS, federal funding of projects reduces the burden local taxpayers for regional improvements; and

WHEREAS, non-federal funds must be at least 20 percent of the project costs; and

WHEREAS, project submittals are due on July 15, 2016; and

WHEREAS, all projects proposed are consistent with the adopted Dakota County Comprehensive Plan; and

WHEREAS, subject to federal funding award, the Dakota County Board of Commissioners would be asked to consider authorization to execute a grant agreement at a future meeting.

NOW, THEREFORE, BE IT RESOLVED, That the Dakota County Board of Commissioners hereby approves the following County led projects for submittal to the TAB for federal funding:


1. 179th Street Extension from ½ mile west of County State Aid Highway (CSAH) 31 to CSAH 31 and the existing 179th Street intersection with Flagstaff Avenue in Lakeville
2. CSAH 9 (Dodd Boulevard) from Heritage Way to CSAH 50 in Lakeville
3. CSAH 26 (Lone Oak Road/70th Street) from Trunk Highway (TH) 55 to TH 3 (Robert Street) in Eagan and Inver Grove Heights
4. CSAH 32 (Cliff Road) at its intersection with CSAH 31 (Pilot Knob Road) in Eagan
5. CSAH 23 (Foliage Avenue) from CSAH 86 (280th Street) to County Road 96 (320th Street) in Greenvale Township
6. CSAH 50 (202nd Street) from Holyoke Avenue to CSAH 23 (Cedar Avenue) in Lakeville
7. CSAH 86 (280th Street) from CSAH 23 (Galaxie Avenue) to TH 3 in Eureka, Greenvale, Castle Rock, and Waterford Townships
8. Minnesota River Greenway – Eagan Gap Segment in Eagan
9. River to River Greenway – TH 149 Underpass in Mendota Heights
10. River to River Greenway – Robert Street Crossing Connections in West St Paul
11. North Creek Greenway – CSAH 42 Underpass east of Flagstaff in Apple Valley; and

**STATE OF MINNESOTA  
County of Dakota**

	<b>VOTE</b>
<b>Slavik</b>	Yes
<b>Gaylord</b>	Yes
<b>Egan</b>	Yes
<b>Schouweiler</b>	Yes
<b>Workman</b>	Yes
<b>Holberg</b>	Yes
<b>Gerlach</b>	Yes

I, Jennifer Reynolds, Clerk to the Board of the County of Dakota, State of Minnesota, do hereby certify that I have compared the foregoing copy of a resolution with the original minutes of the proceedings of the Board of County Commissioners, Dakota County, Minnesota, at their session held on the 21st day of June, 2016, now on file in the County Administration Department, and have found the same to be a true and correct copy thereof.

Witness my hand and official seal of Dakota County this 23rd day of June, 2016.



Clerk to the Board

12. CSAH 14 - Southview Boulevard from 20th Avenue to 3rd Avenue and 3rd Avenue from Southview Boulevard to Marie Avenue in South St. Paul; and

BE IT FURTHER RESOLVED, That the Dakota County Board of Commissioners hereby supports the following submittals by others:

13. 117th Street from CSAH 71 (Rich Valley Boulevard) to TH 52 – Lead Agency: Inver Grove Heights
14. Orange Line Extension – Lead Agency: Metro Transit
15. CSAH 73 (Oakdale Avenue) from CSAH 14 (Mendota Road) to CSAH 8 (Wentworth Avenue) – Lead Agency: West St. Paul
16. TH 149 (Dodd Road) from Mendota Heights Road to Decorah Lane and from Maple Street to Smith Avenue – Lead Agency: Mendota Heights
17. North Creek Greenway – Farmington Gap – Lead Agency: Farmington
18. CSAH 8 (Wentworth Avenue) from CSAH 63 (Delaware Avenue) to Humboldt Avenue – Lead Agency: West St. Paul
19. CSAH 8 (Wentworth Avenue) from TH 52 to 15th Avenue – Lead Agency: South St Paul; and


BE IT FURTHER RESOLVED, That, subject to federal funding award of the city led projects, the Dakota County Board of Commissioners will provide the local match for regional greenway projects, and for non-greenway projects will provide Dakota County’s share of the matching funds consistent with Dakota County transportation cost share policies.

**STATE OF MINNESOTA**  
**County of Dakota**

	<b>VOTE</b>
<b>Slavik</b>	Yes
<b>Gaylord</b>	Yes
<b>Egan</b>	Yes
<b>Schouweiler</b>	Yes
<b>Workman</b>	Yes
<b>Holberg</b>	Yes
<b>Gerlach</b>	Yes

I, Jennifer Reynolds, Clerk to the Board of the County of Dakota, State of Minnesota, do hereby certify that I have compared the foregoing copy of a resolution with the original minutes of the proceedings of the Board of County Commissioners, Dakota County, Minnesota, at their session held on the 21st day of June, 2016, now on file in the County Administration Department, and have found the same to be a true and correct copy thereof.

Witness my hand and official seal of Dakota County this 23rd day of June, 2016.



Clerk to the Board



# City of Eagan

Mike Maguire  
Mayor

Paul Bakken  
Cyndee Fields  
Gary Hansen  
Meg Tilley  
Council Members

David M. Osberg  
City Administrator

Municipal Center  
3830 Pilot Knob Road  
Eagan, MN 55122-1810  
651.675.5000 phone  
651.675.5012 fax  
651.454.8535 TDD

Maintenance Facility  
3501 Coachman Point  
Eagan, MN 55122  
651.675.5300 phone  
651.675.5360 fax  
651.454.8535 TDD

[www.cityofeagan.com](http://www.cityofeagan.com)

The Lone Oak Tree  
The symbol of  
strength and growth  
in our community.

June 13, 2016

Mr. Mark Krebsbach, P.E.  
Dakota County Transportation Director/Engineer :  
Western Service Center  
14955 Galaxie Avenue South  
Apple Valley, MN 55124

RE: Fixing America's Surface Transportation (FAST) Act  
Letter of Support for Dakota County CSAH 32 (Cliff Road) and CSAH 31 (Pilot  
Knob Road) Intersection Improvements (Roadway Reconstruction /  
Modernization) Project

Dear Mark:

The City of Eagan is supportive of Dakota County's application for federal funding for signal reconstruction and geometric improvements to the intersection of County State Aid Highway (CSAH) 32 (Cliff Road) and CSAH 31 (Pilot Knob Road). This project would be a joint effort between the City of Eagan and Dakota County.

The City of Eagan is aware of and understands the proposed project will affect Dakota County CSAH 32 and CSAH 31. Dakota County has jurisdiction over CSAH 32 and CSAH 31 and commits to operate and maintain this roadway for its design life.

The City of Eagan supports this proposed project for federal funding and agrees to provide a financial commitment for the improvements directly related to CSAH 32 and CSAH 31, consistent with the current County cost participation policy. Thank you for making us aware of this application effort and the opportunity to provide support.

Sincerely,

John Gorder, P.E.  
City Engineer



# Timings

## 54: CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

6/30/2016



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↘	↗	↘	↘	↗	↘	↘	↗	↘	↘	↗	↘
Traffic Volume (vph)	86	506	297	185	423	52	130	347	66	46	1128	117
Future Volume (vph)	86	506	297	185	423	52	130	347	66	46	1128	117
Turn Type	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm
Protected Phases	7	4		3	8		5	2		1	6	
Permitted Phases			4			8			2			6
Detector Phase	7	4	4	3	8	8	5	2	2	1	6	6
Switch Phase												
Minimum Initial (s)	5.0	12.0	12.0	5.0	12.0	12.0	5.0	12.0	12.0	5.0	12.0	12.0
Minimum Split (s)	10.0	19.0	19.0	10.0	19.0	19.0	10.0	19.0	19.0	10.0	19.0	19.0
Total Split (s)	11.0	19.0	19.0	14.0	22.0	22.0	12.0	36.0	36.0	11.0	35.0	35.0
Total Split (%)	13.8%	23.8%	23.8%	17.5%	27.5%	27.5%	15.0%	45.0%	45.0%	13.8%	43.8%	43.8%
Yellow Time (s)	3.0	5.0	5.0	3.0	5.0	5.0	3.0	4.5	4.5	3.0	4.5	4.5
All-Red Time (s)	2.0	1.5	1.5	2.0	1.5	1.5	2.0	1.5	1.5	2.0	1.5	1.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.0	6.5	6.5	5.0	6.5	6.5	5.0	6.0	6.0	5.0	6.0	6.0
Lead/Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?												
Recall Mode	None	None	None	None	None	None	None	C-Max	C-Max	None	C-Max	C-Max
Act Effct Green (s)	5.8	12.5	12.5	9.0	17.7	17.7	7.0	34.4	34.4	5.7	29.0	29.0
Actuated g/C Ratio	0.07	0.16	0.16	0.11	0.22	0.22	0.09	0.43	0.43	0.07	0.36	0.36
v/c Ratio	0.67	0.92	0.73	0.93	0.54	0.11	0.84	0.23	0.08	0.37	0.88	0.17
Control Delay	66.4	67.3	25.3	127.2	31.6	0.4	96.7	16.1	0.2	44.2	34.8	1.3
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	66.4	67.3	25.3	127.2	31.6	0.4	96.7	16.1	0.2	44.2	34.8	1.3
LOS	E	E	C	F	C	A	F	B	A	D	C	A
Approach Delay		53.2			55.9			33.5			32.1	
Approach LOS		D			E			C			C	

### Intersection Summary

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of 1st Green

Natural Cycle: 80

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.93

Intersection Signal Delay: 42.5


Intersection LOS: D

Intersection Capacity Utilization 81.4%

ICU Level of Service D

Analysis Period (min) 120

### Splits and Phases: 54: CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)



	shorter pedestrian delays due to shorter cycle length.	longer crossing time and exposure for pedestrians.
<b>Physical</b>	None identified.	Increased intersection size.
<b>Socioeconomic</b>	Travel time reduced. Vehicle emissions reduced.	Right-of-way and construction costs. Access restrictions to property.
<b>Enforcement, Education, and maintenance</b>	None identified.	None identified.

\* Applies to situations where the left-turn lane is added by physical widening rather than restriping.

## 12.1.2 Multiple Left-Turn Lanes

Multiple left-turn lanes are becoming more widely used at signalized intersections where traffic volumes have increased beyond the design volume of the original single left-turn lane.

Multiple left-turn lanes can be used to address left-turn volumes that exceed or are expected to exceed a single turn lane. Multiple left-turn lanes allow for the allocation of green time to other critical movements or use of a shorter cycle length.

### ***Applicability***

Double and triple left-turn lanes are appropriate at intersections with significantly high left-turn volumes that cannot be adequately served in a single lane. As a rule of thumb, dual left-turn lanes are generally considered when left-turn volumes exceed 300 vehicles per hour (assuming moderate levels of opposing through traffic and adjacent street traffic). A left-turn demand exceeding 600 vehicles per hour indicates a triple left-turn may be appropriate.

While effective in improving intersection capacity, double or triple lefts are not appropriate where:

- A high number of vehicle-pedestrian conflicts occur.
- Left-turning vehicles are not expected to evenly distribute themselves among the lanes.
- Channelization may be obscured.
- Sufficient right-of-way is not available to provide for the design vehicle.

### ***Design Features***

The design of multiple left-turn lanes is similar to that of single turn lanes. In addition, the interaction between vehicles in adjacent lanes and also width of the receiving lanes should be considered. The following are design considerations for triple left-turn lanes provided by Ackeret.<sup>(191)</sup> These same considerations apply for double left-turn lanes:

- Widths of receiving lanes.
- Width of intersection (to accommodate three vehicles abreast).
- Clearance between opposing left-turn movements during concurrent maneuvers.
- Pavement marking visibility.
- Placement of stop bars for left-turning and through vehicles.
- Weaving movements downstream of turn.
- Potential for pedestrian conflict.

The previous section provided criteria for selecting the type of signal phasing to be used. In general, protected-only left-turn phasing is used for most double-lane and triple-lane left-turn movements, although some agencies have used protected-permissive phasing for double left turns.

### ***Operational Features***

Drivers may be confused when attempting to determine their proper turn path on an approach with multiple left-turn lanes. Providing positive guidance for the driver in the form of pavement markings can help



eliminate driver confusion and eliminate vehicle conflict by channeling vehicles in their proper turn path.

Delineation of turn paths is especially useful to drivers making simultaneous opposing left turns, as well as in some cases where drivers turn right when a clear path is not readily apparent. This strategy is also appropriate when the roadway alignment may be confusing or unexpected.

Delineation of turn paths is expected to improve intersection safety, though the effectiveness has not been well evaluated. The additional guidance in the intersection will help separate vehicles making opposing left turns, as well as vehicles turning in adjacent turn lanes.

Additional operational features of dual and triple left-turn lanes are identified below.

- Prominent and well-placed signing should be used with triple left-turn movements, especially in advance of the intersection.
- The excess green time for left-turn movements resulting from the additional lane should be allocated to other critical movements or removed from the entire cycle to reduce the cycle length.
- See tables 118 and 119 for left-turn phasing guidelines.

## Safety Performance

A literature review shows that dual left-turn lanes with protected-only phasing generally operate with minimal negative safety impacts. Common crash types in multiple turn lanes are sideswipes between vehicles in the turn lanes. Turn path delineation guides drivers through their lane and can help reduce sideswipes at left-turn maneuvers.

A study of double and triple left-turn lanes in Las Vegas, NV, showed that about 8 percent of intersection-related sideswipes occur at double lefts, and 50 percent at triple lefts.<sup>(192)</sup> These sideswipes are 1.4 and 9.2 percent of all crashes at the intersections with double and triple lefts, respectively. Turn path geometry and elimination of downstream bottlenecks are important considerations for reducing sideswipes.

One study indicates that triple left-turn lanes have been shown to operate well, and drivers do not have trouble understanding the triple left turns.<sup>(193)</sup> In addition, construction of triple left-turn lanes has not resulted in unexpected or unacceptable crash experiences. Another study showed that 10 percent of the crashes at intersections with triple lefts occurred in the approach for the triple left. These are angle crashes that occur when left-turning vehicles collide with through traffic on the cross street. These crashes are attributed to short clearance intervals and limited sight distance, not operation of the triple left. Public education of the proper use of triple left turns will be necessary where these are being considered at an intersection.

Table 123 presents selected findings of the safety benefits of multiple left-turn lanes.

**Table 123. Safety benefits associated with multiple left-turn lanes: Selected findings.**

Treatment	Finding
Double left-turn lane <sup>(172)</sup>	29% estimated reduction in all fatal/injury collisions 26% estimated reduction in all PDO collisions 29% estimated reduction in fatal/injury rear-end collisions 47% estimated reduction in fatal/injury left-turn collisions 20% estimated reduction in angle fatal/injury collisions

## Operational Performance

Multiple left-turn lanes can improve intersection operations by reducing the time allocated to the signal phase for the left-turn movement. Triple left-turn lanes have been constructed to meet the left-turn capacity demand without having to construct an interchange. This configuration can accommodate left-turn volumes of more than 600 vehicles per hour. Vehicle delays, intersection queues, and green time for the left-turn movement are all reduced, improving operation of the entire intersection.

While dual left-turn lanes are largely operated with protected-only phasing, some agencies use protected-permissive signal phasing. This signal phasing improves capacity for the left-turn movements, particularly during nonpeak times when opposing traffic volumes are lower. Many agencies have safety concerns regarding permissive left-turns in a double turn lane. In fact, many agencies only allow dual left-turn lanes to


be run as protected-only phasing. However, some agencies overcome this concern by offsetting the dual left turn lanes.

Tucson, AZ, uses protected-permissive offset dual left-turns at approximately 30 intersections. The city has been using this treatment for about 30 years with limited reported problems, and continues to install them where needed. The protected-permissive "offset" dual lefts are used on very high volume city streets (with ADTs exceeding 80,000). The capacity of the left-turn movement increases 75 to 80 percent and left-turn crashes increase only insignificantly with the protected-permissive phasing is implemented. One potential issue is sight distance for the left-turning vehicles. The City of Tucson addresses this concern by offsetting the far lane by 1.2 to 1.5 m (4 to 5 ft) so that it has the same sight distance as a single left-turn lane, enabling drivers to see beyond the opposing left-turn vehicles, as shown in figure 119.<sup>(194)</sup>

For protected-permissive dual lefts, Tucson, AZ, also uses a lagging left-turn phase operation. The Arizona Insurance information association studied this operation in 2002.<sup>(195)</sup> The study found that Tucson, AZ, had lower crash rates than the leading left-turn operations in the Phoenix, AZ, area, and this benefit was attributed in part to the use of lagging left phases.

On the other hand, in a study of four non-offset intersections with dual left-turn lanes in Atlanta, GA, operating with protected-permissive signal phasing, it was shown that this signal phasing needs to be carefully considered.<sup>(196)</sup> The advantage of increased capacity compared to the disadvantage of increased vehicle conflicts illustrated that this type of phasing may not be appropriate. This study was based on a limited data set, and more sites should be studied to verify these results.

Portion of MVTA Route Map



Timings

54: CSAH 31 & CSAH 32


6/30/2016

Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	86	506	297	185	423	52	130	347	66	46	1128	117
Future Volume (vph)	86	506	297	185	423	52	130	347	66	46	1128	117
Turn Type	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm	Prot	NA	Perm
Protected Phases	7	4		3	8		5	2		1	6	
Permitted Phases			4			8			2			6
Detector Phase	7	4	4	3	8	8	5	2	2	1	6	6
Switch Phase												
Minimum Initial (s)	5.0	12.0	12.0	5.0	12.0	12.0	5.0	12.0	12.0	5.0	12.0	12.0
Minimum Split (s)	10.0	19.0	19.0	10.0	19.0	19.0	10.0	19.0	19.0	10.0	19.0	19.0
Total Split (s)	10.0	19.0	19.0	10.0	19.0	19.0	10.0	26.0	26.0	10.0	26.0	26.0
Total Split (%)	15.4%	29.2%	29.2%	15.4%	29.2%	29.2%	15.4%	40.0%	40.0%	15.4%	40.0%	40.0%
Yellow Time (s)	3.0	5.0	5.0	3.0	5.0	5.0	3.0	4.5	4.5	3.0	4.5	4.5
All-Red Time (s)	2.0	1.5	1.5	2.0	1.5	1.5	2.0	1.5	1.5	2.0	1.5	1.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.0	6.5	6.5	5.0	6.5	6.5	5.0	6.0	6.0	5.0	6.0	6.0
Lead/Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag	Lead	Lag	Lag
Lead-Lag Optimize?												
Recall Mode	None	None	None	None	None	None	None	C-Max	C-Max	None	C-Max	C-Max
Act Effct Green (s)	5.0	12.5	12.5	5.0	14.5	14.5	5.0	24.0	24.0	5.0	22.0	22.0
Actuated g/C Ratio	0.08	0.19	0.19	0.08	0.22	0.22	0.08	0.37	0.37	0.08	0.34	0.34
v/c Ratio	0.33	0.74	0.62	0.70	0.54	0.10	0.49	0.27	0.09	0.17	0.94	0.17
Control Delay	32.0	33.2	14.0	46.9	26.2	0.4	35.7	16.3	0.2	29.8	46.9	0.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	32.0	33.2	14.0	46.9	26.2	0.4	35.7	16.3	0.2	29.8	46.9	0.5
LOS	C	C	B	D	C	A	D	B	A	C	D	A
Approach Delay		26.7			30.0			19.0			42.1	
Approach LOS		C			C			B			D	

Intersection Summary

Cycle Length: 65  
 Actuated Cycle Length: 65  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of 1st Green  
 Natural Cycle: 65  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.94  
 Intersection Signal Delay: 32.0  
 Intersection LOS: C  
 Intersection Capacity Utilization 73.4%  
 ICU Level of Service D  
 Analysis Period (min) 120

Splits and Phases: 54: CSAH 31 & CSAH 32






# Roadway Area Definition




Roadway Expansion Project: 05308 Cсах 31 & 32 | Map ID: 1472043282812

## Results

Project Length: 2.008 miles


Project Area: 2.815 sq mi



 Project Points    Principal Arterials    A Minor Arterials Planned

 Project    A Minor Arterials

 Project Area    Principal Arterials Planned



Created: 8/24/2016  
LandscapeRSA1



For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>








# Regional Bicycle Transportation Network (RBTN) Corridors

**PROPOSED**

## RBTN Corridors with Alignments

-  Tier 1 Alignments
-  Tier 2 Alignments

## RBTN Corridors (Alignments Undefined)

-  Tier 1 Priority Regional Bicycle Transportation Corridor
-  Tier 2 Regional Bicycle Transportation Corridors




## Other Trail Systems


-  Regional Trails (Regional Parks Policy Plan)
-  Mississippi River Trail (US Route 45)
-  State Trails (DNR)

## Regional Destinations

-  Metropolitan Job Centers (50,000+ jobs)
-  Regional Job Centers (15,000 - 50,000 jobs)
-  Subregional Job Centers (7,000 - 15,000 jobs)
-  Large High Schools (2000+ Students)
-  Colleges & Universities (2000+ Students)
-  Major Sport & Entertainment Centers
-  Highly Visited Regional Parks (400,00+ visits per year)

## Reference Items

-  Principal Arterial Roads
-  Lakes and Rivers
-  City Boundary
-  County Boundary
-  2040 Municipal Urban Service Area MPO Area



CSAH 31 at CSAH 32  
Intersection Project Location



# Regional Economy

Roadway Expansion Project: 05308 CsaH 31 & 32 | Map ID: 1472043282812


## Results

**WITHIN ONE MI** of project:


Totals by City:

- Eagan**  
Population: 1550  
Employment: 8305  
Mfg and Dist Employment: 2580
- Inver Grove Heights**  
Population: 1328  
Employment: 210  
Mfg and Dist Employment: 25
- Mendota Heights**  
Population: 1553  
Employment: 78  
Mfg and Dist Employment: 20
- Sunfish Lake**  
Population: 485  
Employment: 14  
Mfg and Dist Employment: 8

Postsecondary Students:  
0



- Project Points
- Project Area
- Manufacturing/Distribution Centers
- PostSecondary Education Centers
- Job Concentration Centers



Created: 8/24/2016  
LandscapeRSA5




For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>




NCompass Technologies

Results

Project census tracts are above the regional average for population in poverty or population of color: (0 to 18 Points)



- Project Points
- Project Area
- Area of Concentrated Poverty > 50% residents of color
- Area of Concentrated Poverty
- Above reg'l avg conc of race/poverty



Created: 8/24/2016  
LandscapeRSA2



For complete disclaimer of accuracy, please visit <http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



NCompass Technologies



---

54: CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

---

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	43
CO Emissions (kg)	10.87
NOx Emissions (kg)	2.12
VOC Emissions (kg)	2.52

54: CSAH 31 & CSAH 32

Direction	All
Future Volume (vph)	3383
Total Delay / Veh (s/v)	32
CO Emissions (kg)	10.32
NOx Emissions (kg)	2.01
VOC Emissions (kg)	2.39

5. Congestion Reduction / Air Quality RESPONSE A (Calculation):


CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total Peak Hour Delay/Vehicle without the Project (Seconds/Vehicle): 43 sec/veh
- Total Peak Hour Delay/Vehicle with the Project (Seconds/Vehicle): 32 sec/veh
- Total Peak Hour Delay/Vehicle Reduced by the Project (Seconds/Vehicle): 11 sec/veh
- Volume (Vehicles Per Hour): 3383 vph
- Total Peak Hour Delay Reduced by the Project (Seconds): 37213 sec

5. Congestion Reduction / Air Quality RESPONSE B (Calculation):

CSAH 31 (Pilot Knob) & CSAH 32 (Cliff Rd)

- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle without the Project (Kilograms): 0.0046 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions/Vehicle with the Project (Kilograms): 0.0044 kg
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced/Vehicle by the Project (Kilograms): 0.0002 kg
- Volume (Vehicles Per Hour): 3383 vph
- Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms): 0.677 kg




Results

Transit with a Direct Connection to project:  
436 489

*\*indicates Planned Alignments*

○ Project Points   
   Project Area   
 **Planned Alignments**  
 Project   
 Transit Routes   
 Arterial BRT



Created: 8/24/2016  
LandscapeRSA3



For complete disclaimer of accuracy, please visit  
<http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



NCompass Technologies



# Traffic Data Inc

PO Box 16269  
St. Louis Park, MN 55416

File Name : 43 - CSAH 31 & CSAH 32, 6-14-16

Site Code : 43

Start Date : 6/14/2016

Page No : 5

CSAH 31 & CSAH 32  
Eagan, MN

