



Application

17063 - 2022 Roadway Modernization

17622 - Wabasha Street Reconstruction (7th St to 11th St)

Regional Solicitation - Roadways Including Multimodal Elements

Status: Submitted  
Submitted Date: 04/13/2022 10:13 PM

---

## Primary Contact

**Name:\*** Mr. Donald Pflaum  
Pronouns First Name Middle Name Last Name

**Title:** Engineer IV

**Department:** Public Works

**Email:** don.pflaum@ci.stpaul.mn.us

**Address:** 900 City Hall Annex  
25 West 4th Street

**\*** St. Paul Minnesota 55401  
City State/Province Postal Code/Zip

**Phone:\*** 651-266-9147  
Phone Ext.

**Fax:**

**What Grant Programs are you most interested in?** Regional Solicitation - Roadways Including Multimodal Elements

---

## Organization Information

**Name:** ST PAUL, CITY OF

Jurisdictional Agency (if different):

Organization Type:

City

Organization Website:

Address:

DEPT OF PUBLIC WORKS-CITY HALL ANNEX  
25 W 4TH ST #1500

\*

ST PAUL

Minnesota

55101

City

State/Province

Postal Code/Zip

County:

Ramsey

Phone:\*

651-266-9700

Ext.

Fax:

PeopleSoft Vendor Number

0000003222A22

---

## Project Information

Project Name

Wabasha Street Reconstruction (7th Street to 11th Street)

Primary County where the Project is Located

Ramsey

Cities or Townships where the Project is Located:

St. Paul

Jurisdictional Agency (If Different than the Applicant):

The Wabasha Street Reconstruction project will replace aging street infrastructure and reallocate space in the corridor to accommodate an off-road two-way bikeway facility (Capital City Bikeway) on a 0.2-mile segment of Wabasha Street between 7th Street (Trunk Highway (TH) 5) and 11th Street, while providing safer pedestrian travel, and two lanes of travel for motorists.

Wabasha Street is primarily an urban, two- to three-lane, one-way roadway, classified as an A Minor Arterial. Pedestrian facilities include deteriorating sidewalk on both sides of the street with little to no boulevard. In addition, there is on-street parking on both sides, with the exception of transit stop locations.

Project improvements will include:

**Brief Project Description (Include location, road name/functional class, type of improvement, etc.)**

- A two-way bikeway on the west side between 7th Street and 10th Street, raised at sidewalk height.
- A landscaped boulevard between the sidewalk and bikeway to provide a more comfortable pedestrian space along both sides of the corridor.
- Replacement of deteriorated pavement, pavement substructure, curb and gutter, and storm sewer
- New traffic signals at the 11th Street, 10th Street, Exchange Street, and 7th Street (TH 5) intersections
- Pedestrian improvements including ADA compliant ramps and sidewalks (free of obstructions), Accessible Pedestrian Signals (APS), high visibility crosswalk markings, curb extensions, and countdown timers.
- Stormwater treatment infrastructure

In the last 10 years there have been five pedestrian/vehicle crashes within the project limits. Two were minor injury crashes and three were possible injury crashes. The reconstruction project will significantly improve pedestrian and bicycle safety by adding curb extensions at all intersections, narrowing the driving space by removing parking on the west side, reducing travel lane widths, and constructing a separated two-way bikeway.

The goal of the Capital City Bikeway: Network Study and Design Guide completed in 2016 was to establish a network of bicycle facilities in the downtown core that will encourage bicycling and economic development. Each implemented segment of the bikeway "will not only make bicycling safer for people of all ages and abilities in St. Paul, but it will positively contribute to the overall experience and vitality of the City". Making investments in quality infrastructure improvements along the Bikeway will provide development opportunities by local businesses and increase local spending as people are encouraged to spend more time in downtown St. Paul. The Capital City Bikeway Interim Design Study completed in 2021 identified Wabasha Street as the preferred alignment for the Capital City Bikeway. Significant public and stakeholder engagement was completed throughout the study process that led to this recommendation.

*(Limit 2,800 characters; approximately 400 words)*

**TRANSPORTATION IMPROVEMENT PROGRAM (TIP)**  
**DESCRIPTION - will be used in TIP if the project is selected for funding. [See MnDOT's TIP description guidance.](#)**

Wabasha Street reconstruction from 7th Street (TH 5) to 11th Street (0.2 miles), Roadway reconstruction, ADA Improvements, off-street bikeway, landscaping, drainage, signage/stripping, signals, lighting, and stormwater management

*Include both the CSAH/MSAS/TH references and their corresponding street names in the TIP Description (see Resources link on Regional Solicitation webpage for examples).*

**Project Length (Miles)** 0.2

*to the nearest one-tenth of a mile*

---

## Project Funding

**Are you applying for competitive funds from another source(s) to implement this project?** No

**If yes, please identify the source(s)**

**Federal Amount** \$5,337,600.00

**Match Amount** \$1,334,400.00

*Minimum of 20% of project total*

**Project Total** \$6,672,000.00

*For transit projects, the total cost for the application is total cost minus fare revenues.*

**Match Percentage** 20.0%

*Minimum of 20%*

*Compute the match percentage by dividing the match amount by the project total*

**Source of Match Funds** City of St. Paul

*A minimum of 20% of the total project cost must come from non-federal sources; additional match funds over the 20% minimum can come from other federal sources*

### Preferred Program Year

**Select one:** 2027

*Select 2024 or 2025 for TDM and Unique projects only. For all other applications, select 2026 or 2027.*

### Additional Program Years:

*Select all years that are feasible if funding in an earlier year becomes available.*

---

## Project Information-Roadways

**County, City, or Lead Agency** City of St. Paul

**Functional Class of Road** A Minor Reliever

**Road System** MSAS

*TH, CSAH, MSAS, CO. RD., TWP. RD., CITY STREET*

**Road/Route No.** 235

*i.e., 53 for CSAH 53*

**Name of Road** Wabasha Street

*Example; 1st ST., MAIN AVE*

**Zip Code where Majority of Work is Being Performed** 55101

**(Approximate) Begin Construction Date** 04/01/2027

**(Approximate) End Construction Date** 11/01/2027

**TERMINI:(Termini listed must be within 0.3 miles of any work)**

**From:**  
**(Intersection or Address)**

**To:**  
**(Intersection or Address)**

*DO NOT INCLUDE LEGAL DESCRIPTION*

**Or At**

**Miles of Sidewalk (nearest 0.1 miles)** 0.4

**Miles of Trail (nearest 0.1 miles)** 0.2

**Miles of Trail on the Regional Bicycle Transportation Network (nearest 0.1 miles)** 0.2

**Primary Types of Work**

CURB AND GUTTER, BIT BASE, AGG BASE, LIGHTING, PED RAMPS, SIGNALS, STORM SEWER, BIKE PATH, SIDEWALK, LIGHTING, LANDSCAPING

*Examples: GRADE, AGG BASE, BIT BASE, BIT SURF, SIDEWALK, CURB AND GUTTER,STORM SEWER, SIGNALS, LIGHTING, GUARDRAIL, BIKE PATH, PED RAMPS, BRIDGE, PARK AND RIDE, ETC.*

**BRIDGE/CULVERT PROJECTS (IF APPLICABLE)**

**Old Bridge/Culvert No.:**

**New Bridge/Culvert No.:**

**Structure is Over/Under**  
**(Bridge or culvert name):**

---

## **Requirements - All Projects**

### **All Projects**

1. The project must be consistent with the goals and policies in these adopted regional plans: Thrive MSP 2040 (2014), the 2040 Transportation Policy Plan (2018), the 2040 Regional Parks Policy Plan (2018), and the 2040 Water Resources Policy Plan (2015).

**Check the box to indicate that the project meets this requirement. Yes**

2. The project must be consistent with the 2040 Transportation Policy Plan. Reference the 2040 Transportation Plan goals, objectives, and strategies that relate to the project.

Goal A: Transportation System Stewardship:

Objective: Efficiently preserve and maintain the regional transportation system in a state of good repair.

Objective: Operate the regional transportation system to efficiently and cost-effectively connect people and freight to destinations

Strategies: A1 and A2 (Page 2.6)

Goal B: Safety and Security:

Objective: Reduce crashes and improve safety and security for all modes of passenger travel and freight transportation.

Strategies: B1, B4, B5, and B6 (Page 2.7)

Goal C: Access to Destinations:

Objective: Increase the availability of multimodal travel options, especially in congested highway corridors.

Objective: Increase travel time reliability and predictability for travel on highway and transit systems.

Objective: Ensure access to freight terminals such as river ports, airports, and intermodal rail yards.

Objective: Increase transit ridership and share of trips taken using transit bicycling and walking.

Objective: improve multimodal travel options for people of all ages and abilities to connect to jobs and other opportunities, particularly for historically underrepresented populations.

**Briefly list the goals, objectives, strategies, and associated pages:**

Strategies: C1, C2, C4, C7, C8, C9, C11, C12, and C17 (Page 2.8-2.10)

#### Goal D: Competitive Economy

Objective: Improve multimodal access to regional job concentrations identified in Thrive MSP 2040.

Objective: Invest in a multimodal transportation system to attract and retain businesses and residents.

Strategies: D1, D3 (Page 2.11)

#### Goal E: Healthy Environment

Objective: Increase the availability and attractiveness of transit, bicycling, and walking to encourage healthy communities and active car-free lifestyles.

Objective: Provide a transportation system that promotes community cohesion and connectivity for historically underrepresented populations.

Strategies: E1, E2, E3, E5, E6, and E7 (Page 2.12-2.13)

#### Goal F: Leveraging Transportation Investments to Guide Land Use.

Objective: Focus regional growth in areas that support the full range of multimodal travel.

Objective: Encourage local land use design that integrates highways, streets, transit, walking, and bicycling.



Strategies: F1, F2, F3, F4, F5, F6, and F7 (Page 2.14-2.15)

*Limit 2,800 characters, approximately 400 words*

*3. The project or the transportation problem/need that the project addresses must be in a local planning or programming document. Reference the name of the appropriate comprehensive plan, regional/statewide plan, capital improvement program, corridor study document [studies on trunk highway must be approved by the Minnesota Department of Transportation and the Metropolitan Council], or other official plan or program of the applicant agency [includes Safe Routes to School Plans] that the project is included in and/or a transportation problem/need that the project addresses.*

City of St. Paul Bicycle Plan (2017):

- Identified the Capital City Bikeway alignment as a priority (pg. 62).

- Capital City Bikeway Interim Design Study (2021) which was a continuation of the Bicycle Plan identified Wabasha Street between 10th Street and 7th Street as the preferred alignment for the Capacity City Bikeway alignment. (pg. 25)  
[https://www.stpaul.gov/sites/default/files/2021-04/CCB\\_Presentation\\_033121%20-%20Final.pdf](https://www.stpaul.gov/sites/default/files/2021-04/CCB_Presentation_033121%20-%20Final.pdf)

City of St. Paul 2040 Comprehensive Plan (2020):

**List the applicable documents and pages: Unique projects are exempt from this qualifying requirement because of their innovative nature.**

- Policy T-2. Use surface condition and multimodal usage rates to prioritize transportation projects and ensure well-maintained infrastructure that benefits the most people (See Maps T-10 and T-12). (pg. 73)

-Policy T-9. Design the rights-of-way for all users, including older people, children and those with mobility constraints, as guided by the Street Design Manual and Safe Routes to School Plans, and by thoughtfully addressing streetscape issues such as curb cut design, level sidewalks, lighting, accessibility to/from bus stops, and the presence of benches and buffers between sidewalks and streets. (pg. 73)

*Limit 2,800 characters, approximately 400 words*

*4. The project must exclude costs for studies, preliminary engineering, design, or construction engineering. Right-of-way costs are only eligible as part of transit stations/stops, transit terminals, park-and-ride facilities, or pool-and-ride lots. Noise barriers, drainage projects, fences, landscaping, etc., are not eligible for funding as a standalone project, but can be included as part of the larger submitted project, which is otherwise eligible. Unique project costs are limited to those that are federally eligible.*

**Check the box to indicate that the project meets this requirement. Yes**

*5. Applicant is a public agency (e.g., county, city, tribal government, transit provider, etc.) or non-profit organization (TDM and Unique Projects applicants only). Applicants that are not State Aid cities or counties in the seven-county metro area with populations over 5,000 must contact the MnDOT Metro State Aid Office prior to submitting their application to determine if a public agency sponsor is required.*

**Check the box to indicate that the project meets this requirement. Yes**

6. Applicants must not submit an application for the same project elements in more than one funding application category.

**Check the box to indicate that the project meets this requirement. Yes**

7. The requested funding amount must be more than or equal to the minimum award and less than or equal to the maximum award. The cost of preparing a project for funding authorization can be substantial. For that reason, minimum federal amounts apply. Other federal funds may be combined with the requested funds for projects exceeding the maximum award, but the source(s) must be identified in the application. Funding amounts by application category are listed below in Table 1. For unique projects, the minimum award is \$500,000 and the maximum award is the total amount available each funding cycle (approximately \$4,000,000 for the 2022 funding cycle).

**Strategic Capacity (Roadway Expansion):** \$1,000,000 to \$10,000,000

**Roadway Reconstruction/Modernization:** \$1,000,000 to \$7,000,000

**Traffic Management Technologies (Roadway System Management):** \$500,000 to \$3,500,000

**Spot Mobility and Safety:** \$1,000,000 to \$3,500,000

**Bridges Rehabilitation/Replacement:** \$1,000,000 to \$7,000,000

**Check the box to indicate that the project meets this requirement. Yes**

8. The project must comply with the Americans with Disabilities Act (ADA).

**Check the box to indicate that the project meets this requirement. Yes**

9. In order for a selected project to be included in the Transportation Improvement Program (TIP) and approved by USDOT, the public agency sponsor must either have a current Americans with Disabilities Act (ADA) self-evaluation or transition plan that covers the public right of way/transportation, as required under Title II of the ADA. The plan must be completed by the local agency before the Regional Solicitation application deadline. For the 2022 Regional Solicitation funding cycle, this requirement may include that the plan is updated within the past five years.

**The applicant is a public agency that employs 50 or more people and has a completed ADA transition plan that covers the public right of way/transportation. Yes**

**(TDM and Unique Project Applicants Only) The applicant is not a public agency subject to the self-evaluation requirements in Title II of the ADA.**

**Date plan completed:** 01/13/2016

**Link to plan:** [https://www.stpaul.gov/sites/default/files/Media%20Root/ADA%20Transition%20Plan%20for%20Public%20Works\\_2016.pdf](https://www.stpaul.gov/sites/default/files/Media%20Root/ADA%20Transition%20Plan%20for%20Public%20Works_2016.pdf)

**The applicant is a public agency that employs fewer than 50 people and has a completed ADA self-evaluation that covers the public right of way/transportation.**

**Date self-evaluation completed:**

**Link to plan:**

**Upload plan or self-evaluation if there is no link**

Upload as PDF

10. The project must be accessible and open to the general public.

**Check the box to indicate that the project meets this requirement. Yes**

11. The owner/operator of the facility must operate and maintain the project year-round for the useful life of the improvement, per FHWA direction established 8/27/2008 and updated 6/27/2017. Unique projects are exempt from this qualifying requirement.

**Check the box to indicate that the project meets this requirement. Yes**

12. The project must represent a permanent improvement with independent utility. The term independent utility means the project provides benefits described in the application by itself and does not depend on any construction elements of the project being funded from other sources outside the regional solicitation, excluding the required non-federal match. Projects that include traffic management or transit operating funds as part of a construction project are exempt from this policy.

**Check the box to indicate that the project meets this requirement. Yes**

13. The project must not be a temporary construction project. A temporary construction project is defined as work that must be replaced within five years and is ineligible for funding. The project must also not be staged construction where the project will be replaced as part of future stages. Staged construction is eligible for funding as long as future stages build on, rather than replace, previous work.

**Check the box to indicate that the project meets this requirement. Yes**

14. The project applicant must send written notification regarding the proposed project to all affected state and local units of government prior to submitting the application.

**Check the box to indicate that the project meets this requirement. Yes**

---

## Roadways Including Multimodal Elements

1. All roadway and bridge projects must be identified as a principal arterial (non-freeway facilities only) or A-minor arterial as shown on the latest TAB approved roadway functional classification map.

**Check the box to indicate that the project meets this requirement. Yes**

### Roadway Strategic Capacity and Reconstruction/Modernization and Spot Mobility projects only:

2. The project must be designed to meet 10-ton load limit standards.

**Check the box to indicate that the project meets this requirement. Yes**

### Bridge Rehabilitation/Replacement and Strategic Capacity projects only:

3. Projects requiring a grade-separated crossing of a principal arterial freeway must be limited to the federal share of those project costs identified as local (non-MnDOT) cost responsibility using MnDOT's Cost Participation for Cooperative Construction Projects and Maintenance Responsibilities manual. In the case of a federally funded trunk highway project, the policy guidelines should be read as if the funded trunk highway route is under local jurisdiction.

**Check the box to indicate that the project meets this requirement.**

4. The bridge must carry vehicular traffic. Bridges can carry traffic from multiple modes. However, bridges that are exclusively for bicycle or pedestrian traffic must apply under one of the Bicycle and Pedestrian Facilities application categories. Rail-only bridges are ineligible for funding.

**Check the box to indicate that the project meets this requirement.**

### Bridge Rehabilitation/Replacement projects only:

5. The length of the bridge clear span must exceed 20 feet.

**Check the box to indicate that the project meets this requirement.**

6. The bridge must have a National Bridge Inventory Rating of 6 or less for rehabilitation projects and 4 or less for replacement projects.

**Check the box to indicate that the project meets this requirement.**

### Roadway Expansion, Reconstruction/Modernization, and Bridge Rehabilitation/Replacement projects only:

7. All roadway projects that involve the construction of a new/expanded interchange or new interchange ramps must have approval by the Metropolitan Council/MnDOT Interchange Planning Review Committee prior to application submittal. Please contact Michael Corbett at MnDOT (Michael.J.Corbett@state.mn.us or 651-234-7793) to determine whether your project needs to go through this process as described in Appendix F of the 2040 Transportation Policy Plan.

**Check the box to indicate that the project meets this requirement. Yes**

---

## Requirements - Roadways Including Multimodal Elements

---

### Specific Roadway Elements

<b>CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES</b>	<b>Cost</b>
Mobilization (approx. 5% of total cost)	\$144,000.00
Removals (approx. 5% of total cost)	\$46,700.00
Roadway (grading, borrow, etc.)	\$204,000.00
Roadway (aggregates and paving)	\$1,107,600.00
Subgrade Correction (muck)	\$0.00
Storm Sewer	\$245,000.00
Ponds	\$0.00
Concrete Items (curb & gutter, sidewalks, median barriers)	\$56,400.00
Traffic Control	\$144,000.00
Striping	\$26,000.00
Signing	\$7,000.00
Lighting	\$285,000.00
Turf - Erosion & Landscaping	\$93,000.00
Bridge	\$0.00
Retaining Walls	\$0.00
Noise Wall (not calculated in cost effectiveness measure)	\$0.00
Traffic Signals	\$1,600,000.00
Wetland Mitigation	\$0.00
Other Natural and Cultural Resource Protection	\$0.00
RR Crossing	\$0.00
Roadway Contingencies	\$1,456,000.00
Other Roadway Elements	\$201,000.00
<b>Totals</b>	<b>\$5,615,700.00</b>

---

### Specific Bicycle and Pedestrian Elements

<b>CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES</b>	<b>Cost</b>
Path/Trail Construction	\$249,400.00

Sidewalk Construction	\$332,900.00
On-Street Bicycle Facility Construction	\$0.00
Right-of-Way	\$0.00
Pedestrian Curb Ramps (ADA)	\$68,400.00
Crossing Aids (e.g., Audible Pedestrian Signals, HAWK)	\$0.00
Pedestrian-scale Lighting	\$0.00
Streetscaping	\$50,000.00
Wayfinding	\$0.00
Bicycle and Pedestrian Contingencies	\$274,000.00
Other Bicycle and Pedestrian Elements	\$81,600.00
<b>Totals</b>	<b>\$1,056,300.00</b>

## Specific Transit and TDM Elements

<b>CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES</b>	<b>Cost</b>
Fixed Guideway Elements	\$0.00
Stations, Stops, and Terminals	\$0.00
Support Facilities	\$0.00
Transit Systems (e.g. communications, signals, controls, fare collection, etc.)	\$0.00
Vehicles	\$0.00
Contingencies	\$0.00
Right-of-Way	\$0.00
Other Transit and TDM Elements	\$0.00
<b>Totals</b>	<b>\$0.00</b>

## Transit Operating Costs

Number of Platform hours	0
Cost Per Platform hour (full loaded Cost)	\$0.00
Subtotal	\$0.00
Other Costs - Administration, Overhead, etc.	\$0.00

## Totals

<b>Total Cost</b>	<b>\$6,672,000.00</b>
-------------------	-----------------------

Construction Cost Total	\$6,672,000.00
Transit Operating Cost Total	\$0.00

## Measure B: Project Location Relative to Jobs, Manufacturing, and Education

Existing Employment within 1 Mile:	81472
Existing Manufacturing/Distribution-Related Employment within 1 Mile:	3804
Existing Post-Secondary Students within 1 Mile:	5823
Upload Map	1649791892362_WabashaEconomyMap.pdf

Please upload attachment in PDF form.

## Measure C: Current Heavy Commercial Traffic

RESPONSE: Select one for your project, based on the updated 2021 Regional Truck Corridor Study:

### Along Tier 1:

Miles: 0  
(to the nearest 0.1 miles)

### Along Tier 2:

Miles: 0  
(to the nearest 0.1 miles)

### Along Tier 3:

Miles: 0  
(to the nearest 0.1 miles)

The project provides a direct and immediate connection (i.e., intersects) with either a Tier 1, Tier 2, or Tier 3 corridor: Yes

None of the tiers:

## Measure A: Current Daily Person Throughput

Location	North of 7th Street (TH 5)
Current AADT Volume	10300
Existing Transit Routes on the Project	Other
Upload Transit Connections Map	1649792014090_WabashaTransitMap.pdf

For New Roadways only, list transit routes that will likely be diverted to the new proposed roadway (if applicable).

Please upload attachment in PDF form.

## Response: Current Daily Person Throughput

Average Annual Daily Transit Ridership	0
Current Daily Person Throughput	13390.0

---

## Measure B: 2040 Forecast ADT

Use Metropolitan Council model to determine forecast (2040) ADT volume Yes

If checked, METC Staff will provide Forecast (2040) ADT volume

OR

Identify the approved county or city travel demand model to determine forecast (2040) ADT volume

Forecast (2040) ADT volume

---

## Measure A: Engagement

*i. Describe any Black, Indigenous, and People of Color populations, low-income populations, disabled populations, youth, or older adults within a ½ mile of the proposed project. Describe how these populations relate to regional context. Location of affordable housing will be addressed in Measure C.*

*ii. Describe how Black, Indigenous, and People of Color populations, low-income populations, persons with disabilities, youth, older adults, and residents in affordable housing were engaged, whether through community planning efforts, project needs identification, or during the project development process.*

*iii. Describe the progression of engagement activities in this project. A full response should answer these questions:*



As shown on the Socio-Economic map, the project's census tracts are above the regional average for population in poverty or population of color. Community engagement has through community planning efforts, starting with the St. Paul Bike Plan public hearing conducted in December 2014 - summary of the meeting at [www.stpaul.gov/bikeplan](http://www.stpaul.gov/bikeplan).

In 2016, the Capital City Bikeway: Network Study and Design Guide was completed, resulting in a downtown network of bikeways that are accessible for people of all ages, backgrounds, and abilities. During this study, several opportunities were provided to engage with equity populations within the project area:

**Response:**

- A four day "discovery workshop" was held in May 2015 with individual stakeholder interviews with community leaders, downtown business/property owners, cultural institution representatives, local organizations, City staff, and elected officials.
- A four-day design workshop was held in June 2015 with "open studio" hours for the public to provide input and react to the designs.
- Four pop-up events took place to gather additional project input on the project at Mears Park, Pedro Park, and Rondo Days, including a bike ride at Rondo Days with the NiceRide Neighborhood Group and Major Taylor Bicycling Club.

The Capital City Interim Design Study completed in 2021, resulted in Wabasha Street identified as the preferred alignment for the Capital City Bikeway. The following comprehensive public outreach was conducted for this study:

- Three public open houses (May 2019, October 2019 and February 2020) with a total of 235 in attendance.
- Three online surveys in coordination with the public open houses. A total of 420 responses were received.
- Other activities included direct mailings and emails, targeted stakeholder engagement, direct outreach to stakeholders and meetings with stakeholder groups.
- The City offered translated materials for those that requested them. According to 2019 ACS data in the project area, approximately 45 percent of the population identifies as BIPOC, 26 percent of the population has an income below the poverty threshold, and 24 percent of the population is under age 18 or over age 65.
- Final recommendations vetted through the public process detailed above were shared with the City Council at a public hearing on May 21, 2021.
- Additional details on this outreach can be found at <https://www.stpaul.gov/projects/public-works/pw2022ccbwest#project-documents>

As shown on the Equity Populations and Destinations map, low-income and senior populations living along or near Wabasha Street were included in these engagement activities related to the project.

*(Limit 2,800 characters; approximately 400 words):*

---

## **Measure B: Equity Population Benefits and Impacts**

*Describe the projects benefits to Black, Indigenous, and People of Color populations, low-income populations, children, people with disabilities, youth, and older adults. Benefits could relate to:*

*This is not an exhaustive list. A full response will support the benefits claimed, identify benefits specific to Equity populations residing or engaged in activities near the project area, identify benefits addressing a transportation issue affecting Equity populations specifically identified through engagement, and substantiate benefits with data.*

*Acknowledge and describe any negative project impacts to Black, Indigenous, and People of Color populations, low-income populations, children, people with disabilities, youth, and older adults. Describe measures to mitigate these impacts. Unidentified or unmitigated negative impacts may result in a reduction in points.*

*Below is a list of potential negative impacts. This is not an exhaustive list.*

The project is in an area above the regional average for population in poverty or people of color. The project will provide direct benefits to residents living in subsidized and senior apartments, persons with disabilities and youth to destinations in the area (see Equity Populations and Destinations map).

According to 2019 ACS population data in the project area, approximately 45 percent identifies as BIPOC, 26 percent has an income below the poverty threshold, and 24 percent is under 18 or over 65.

Benefits include:

Bicycle/Pedestrian Safety - Wabasha Street currently does not have a safe separated bike facility. The project provides a two-way bikeway raised to sidewalk height with a landscaped boulevard between the bikeway and sidewalk. In the past 10 years there have been five pedestrian/vehicle injury crashes along the project corridor. The sidewalk will be reconstructed, and all intersections will be upgraded to full ADA compliance to further improve bicycle and pedestrian safety. Bump outs will also be installed to reduce the crossing distance and visually narrow the roadway.

Access - The two-way bikeway and reconstructed sidewalk will provide access improvements for residents living in the low-income and senior housing along or near Wabasha Street, such as the Exchange Hi-Rise and Central Towers, to various area destinations.

The project improves access to the many

Response:

downtown St. Paul destinations. For equity populations relying on public transit as an alternative transportation mode, the improvements provide a better pedestrian connection to the downtown employment pool for daily commuter travel.

**New Modal Option and Public Health Benefits** - The two-way bikeway provides a new transportation option for equity populations with limited access to a car, while encouraging biking as a recreational activity and improving the health for all underserved communities. The Capital City Bikeway goal is to increase the mode share of bicycling. This provides the opportunity to use biking as a commuting option.

**Gap Closure** - The project includes a two-way bikeway between 7th and 10th Streets to implement the Capital City Bikeway and complete a gap in the St. Paul bicycle network and regional trail system.

**Leveraging Investments** - The City plans to construct the bikeway segment on Wabasha Street between Kellogg Boulevard and 7th Street in 2022. This project leverages another beneficial project planned for near-term construction.

There will be construction activities along Wabasha Street that will directly impact the traveling public and nearby residents and businesses. However, project construction will incorporate proper noise, dust, traffic management mitigation, access management and planned detour routes for all users.

(Limit 2,800 characters; approximately 400 words):

---

## **Measure C: Affordable Housing Access**

*Describe any affordable housing developments existing, under construction, or planned within ½ mile of the proposed project. The applicant should note the number of existing subsidized units, which will be provided on the Socio-Economic Conditions map. Applicants can also describe other types of affordable housing (e.g., naturally-occurring affordable housing, manufactured housing) and under construction or planned affordable housing that is within a half mile of the project. If applicable, the applicant can provide self-generated PDF maps to support these additions. Applicants are encouraged to provide a self-generated PDF map describing how a project connects affordable housing residents to destinations (e.g., childcare, grocery stores, schools, places of worship).*

*Describe the project's benefits to current and future affordable housing residents within ½ mile of the project. Benefits must relate to affordable housing residents. Examples may include:*

*This is not an exhaustive list. Since residents of affordable housing are more likely not to own a private vehicle, higher points will be provided to roadway projects that include other multimodal access improvements. A full response will support the benefits claimed, identify benefits specific to residents of affordable housing, identify benefits addressing a transportation issue affecting residents of affordable housing specifically identified through engagement, and substantiate benefits with data.*

As shown on the attached "Socio-Economic" map, there are 4,604 subsidized housing units in the census tracts within ½ mile of the project. As shown on the attached Affordable Housing and Destinations map, there are a significant amount of low-income housing located in the project area where Wabasha Street provides direct access to daily destinations and other alternative modes of travel:

- Wabasha Hi-Rise (71 units)
  
- Exchange Hi-Rise (194 units)
- Central Towers (197 units)
  
- Dorothy Day Residence Mary Hall (75 units)
- Dorothy Day Residence (177 units)
- Dorothy Day Phase I (193 units)
- Higher Ground I (193 units)
- Renaissance Box (70 units)
- Lyons Court Independent Living Facility (60 units)
- Sibley Court Apartments (52 units)
- Sibley Park Apartments (50 units)
- Heritage House (58 units)
- Mears Park Place (50 units)
- The Straus Building (34 units)
- American House (70 units)
- Crane Ordway (70 units)
- Northern Warehouse (52 units)
- Tilsner Building (65 units)
- Pioneer Press Building (143 units)
- Minnesota Place (137 units)
- Commerce Apartments Phase II (45 units)
- Commerce Apartments Phase I (55 units)
- Valley Hi-Rise (158 units)
- Cathedral Hill Homes (60 units)
- Ravoux Hi-Rise (220 units)
- Capitol Plaza (36 units)
- Neill Hi-Rise(103 units)

Response:

The two-way bikeway and reconstructed sidewalk will provide direct access improvements for residents living in the low-income and senior housing along or near Wabasha Street, such as the Exchange Hi-Rise and Central Towers, to various destinations in the area. It will also provide an improved connection for equity populations relying on public transit and walking as alternative modes of transportation to businesses and downtown employment destinations.

The project includes multimodal improvements for these residents of affordable housing that use bicycling and walking as their mode of transportation for short trips to the grocery store, church or health services. This project will reallocate space in the corridor to improve accommodations for people biking and walking with the addition of boulevard space (to provide separation from the roadway), lighting (to promote user comfort), and proven countermeasures such as raised medians and curb extensions (to promote safety along and across the corridor). The project will also add a two-way bikeway facility separated by a barrier on the west side of Wabasha Street. This bikeway will provide a new modal option and improve connections to important community destination and provides a direct connection to existing transit stops on 10th Street.

*(Limit 2,800 characters; approximately 400 words):*

---

## **Measure D: BONUS POINTS**

**Project is located in an Area of Concentrated Poverty:**

**Projects census tracts are above the regional average for population in poverty or population of color (Regional Environmental Justice Area):**

Yes



Project located in a census tract that is below the regional average for population in poverty or populations of color (Regional Environmental Justice Area):

Upload the Socio-Economic Conditions map used for this measure.

1649884926631\_WabashaSocioMap.pdf

---

### Measure A: Year of Roadway Construction

Year of Original Roadway Construction or Most Recent Reconstruction	Segment Length	Calculation	Calculation 2
1957	0.2	391.4	1957.0
	<b>0</b>	<b>391</b>	<b>1957</b>

---

### Total Project Length

Total Project Length (as entered in "Project Information" form) 0

---

### Average Construction Year

Weighted Year 1957

---

### Total Segment Length (Miles)

Total Segment Length 0.2

---

### Measure B: Geometric, Structural, or Infrastructure Improvements

Improved roadway to better accommodate freight movements: Yes

Response:

Wabasha Street is one of only a few Mississippi River crossings in downtown St. Paul. In addition, this corridor moves freight to 11th Street (on-ramp for I-94 eastbound and I-35E northbound) and 12th Street (on-ramp for I-94 westbound and I-35E southbound). Freight movements along the corridor will be greatly improved with the reconstruction of the deteriorated roadway pavement, installation of new traffic signals for better signal timing - hence reliable travel times and improved pedestrian visibility to minimize potential accidents.

*(Limit 700 characters; approximately 100 words)*

**Improved clear zones or sight lines:**

**Response:**

Yes

A variety of improvements will be made to improve clear zones and sight lines along the corridor:

- The addition of curb extensions will expand sight lines at intersections.
  
- Crossing improvements will be implemented on cross streets and along Wabasha Street where appropriate, to increase visibility of pedestrians and bicyclists at the intersections.
  
- All access points will be evaluated.
  
- Upgraded and consistent street and pedestrian scale lighting will improve night visibility and safety via CPTED (Crime Prevention Through Environmental Design) principles.
  
- Boulevards will provide clear zones.

*(Limit 700 characters; approximately 100 words)*

**Improved roadway geometrics:**

**Response:**

Yes

- Roadway geometric improvements such as optimized turning radii and lane widths, crossing improvements, curb extensions and other traffic calming improvements will reduce crossing distances and exposure for pedestrians and bicyclists while preserving auto movements.
  
- The construction of curb bump outs will also reduce the crossing distance and visually narrow the roadway to provide additional pedestrian safety.

*(Limit 700 characters; approximately 100 words)*

**Access management enhancements:**

Yes

**Response:**

Due to the downtown street system, access is already well managed with relatively few driveways along the Wabasha Street project corridor. Between 7th Street and Exchange Street, driveway access is limited to parking areas. Between Exchange Street and 11th Street, there are no existing access driveways. The project will maintain current conditions that minimizes driveway access along Wabasha Street.

*(Limit 700 characters; approximately 100 words)*

**Vertical/horizontal alignment improvements:**

Yes

The existing vertical alignment along Wabasha Street is relatively flat with adequate sight distance. Curb extensions will be added at all intersections along the corridor to minimize crossing distances thus reducing stopping sight distances needed by motorists reacting to pedestrian traffic crossing the intersections.

**Response:**

*(Limit 700 characters; approximately 100 words)*

**Improved stormwater mitigation:**

Yes

The project will include stormwater BMPs in accordance with the requirements of the Watershed District. Streetscape elements such as bio-retention features and other sustainable landscaping practices will be evaluated as needed to address localized stormwater retention and necessary stormwater quality requirements. Reconstructed curb and gutter will provide added drainage benefits.

**Response:**

*(Limit 700 characters; approximately 100 words)*

**Signals/lighting upgrades:**

Yes

**Response:**

The project will include full replacement of the traffic signals at 11th Street, 10th Street, Exchange Street and 7th Street (TH 5). All intersections will also be upgraded to full ADA compliance including ramps, traffic signals, countdown timers, and Accessible Pedestrian Signals to further improve bicycle and pedestrian safety. In addition, upgraded and consistent street lighting will improve night visibility and safety via CPTED principles.

*(Limit 700 characters; approximately 100 words)*

**Other Improvements**

Yes

The project will include full replacement of the traffic signals at 11th Street, 10th Street, Exchange Street and 7th Street (TH 5). All intersections will also be upgraded to full ADA compliance including ramps, traffic signals, countdown timers, and Accessible Pedestrian Signals to further improve bicycle and pedestrian safety. In addition, upgraded and consistent street lighting will improve night visibility and safety via CPTED principles.

**Response:**

*(Limit 700 characters; approximately 100 words)*

---

**Measure A: Congestion Reduction/Air Quality**

Total Peak Hour Delay Per Vehicle Without The Project (Seconds/Vehicle)	Total Peak Hour Delay Per Vehicle With The Project (Seconds/Vehicle)	Total Peak Hour Delay Per Vehicle Reduced by Project (Seconds/Vehicle)	Volume without the Project (Vehicles per hour)	Volume with the Project (Vehicles Per Hour):	Total Peak Hour Delay Reduced by the Project:	Total Peak Hour Delay Reduced by the Project:	EXPLANATION of methodology used to calculate railroad crossing delay, if applicable.	Synchro or HCM Reports
9.0	9.0	0	1732	1732	0	0	N/A	164979296 2951_Wab asha Traffic Analysis.pdf

11.0	11.0	0	1625	1625	0	0	N/A	164979299 0730_Wab asha Traffic Analysis.pdf
8.0	8.0	0	1286	1286	0	0	N/A	164979301 9659_Wab asha Traffic Analysis.pdf
15.0	15.0	0	2292	2292	0	0	N/A	164979304 5890_Wab asha Traffic Analysis.pdf
							<b>0</b>	

---

### Vehicle Delay Reduced

Total Peak Hour Delay Reduced	0
Total Peak Hour Delay Reduced	0

---

### Measure B: Roadway projects that do not include new roadway segments or railroad grade-separation elements

Total (CO, NOX, and VOC) Peak Hour Emissions without the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions with the Project (Kilograms):	Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms):
5.45	5.45	0
<b>5</b>	<b>5</b>	<b>0</b>

---

### Total

Total Emissions Reduced:	0
Upload Synchro Report	1649793198356_Wabasha Traffic Analysis.pdf

Please upload attachment in PDF form. (Save Form, then click 'Edit' in top right to upload file.)

---

### Measure B: Roadway projects that are constructing new roadway segments, but do not include railroad grade-separation elements (for Roadway Expansion applications only):

Total (CO, NOX, and VOC)  
Peak Hour Emissions  
without the Project  
(Kilograms):

0

Total (CO, NOX, and VOC)  
Peak Hour Emissions with  
the Project (Kilograms):

0

Total (CO, NOX, and VOC)  
Peak Hour Emissions  
Reduced by the Project  
(Kilograms):

0

---

## Total Parallel Roadway

Emissions Reduced on Parallel Roadways 0

Upload Synchro Report

*Please upload attachment in PDF form. (Save Form, then click 'Edit' in top right to upload file.)*

---

## New Roadway Portion:

Cruise speed in miles per hour with the project: 0

Vehicle miles traveled with the project: 0

Total delay in hours with the project: 0

Total stops in vehicles per hour with the project: 0

Fuel consumption in gallons: 0

Total (CO, NOX, and VOC) Peak Hour Emissions Reduced or  
Produced on New Roadway (Kilograms): 0

EXPLANATION of methodology and assumptions used:(Limit  
1,400 characters; approximately 200 words)

Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the  
Project (Kilograms): 0.0

---

## Measure B: Roadway projects that include railroad grade-separation elements

Cruise speed in miles per hour without the project: 0

Vehicle miles traveled without the project: 0

Total delay in hours without the project: 0

Total stops in vehicles per hour without the project: 0

Cruise speed in miles per hour with the project: 0

Vehicle miles traveled with the project: 0

Total delay in hours with the project: 0

Total stops in vehicles per hour with the project: 0

Fuel consumption in gallons (F1) 0

Fuel consumption in gallons (F2) 0

Fuel consumption in gallons (F3) 0

Total (CO, NOX, and VOC) Peak Hour Emissions Reduced by the Project (Kilograms): 0

EXPLANATION of methodology and assumptions used:(Limit 1,400 characters; approximately 200 words)

---

## Measure A: Roadway Projects that do not Include Railroad Grade-Separation Elements

Crash Modification Factor Used:

Install bicycle lane CMF and curb extension CMF were used. The curb extension CMF was provided by MnDOT from the Best Practices for Pedestrian Safety Manual, published January 2021. There was not a CMF available for this improvement within the CMF Clearinghouse website

*(Limit 700 Characters; approximately 100 words)*

Rationale for Crash Modification Selected:

Based on the proposed concept, this is the directly applicable CMF. These features will be installed throughout the length of the corridor and at the study intersections.

*(Limit 1400 Characters; approximately 200 words)*

Project Benefit (\$) from B/C Ratio	\$11,018,393.00
Total Fatal (K) Crashes:	0
Total Serious Injury (A) Crashes:	0
Total Non-Motorized Fatal and Serious Injury Crashes:	0
Total Crashes:	31
Total Fatal (K) Crashes Reduced by Project:	0
Total Serious Injury (A) Crashes Reduced by Project:	0
Total Non-Motorized Fatal and Serious Injury Crashes Reduced by Project:	0
Total Crashes Reduced by Project:	24
Worksheet Attachment	1649885165009_Wabasha Crash Analysis.pdf

*Please upload attachment in PDF form.*

---

## Roadway projects that include railroad grade-separation elements:

Current AADT volume:	0
Average daily trains:	0
Crash Risk Exposure eliminated:	0

---

## Measure A: Pedestrian Safety

**Determine if these measures do not apply to your project.** Does the project match either of the following descriptions?

If either of the items are checked yes, then **score for entire pedestrian safety measure is zero.** Applicant does not need to respond to the sub-measures and can proceed to the next section.

Project is primarily a freeway (or transitioning to a freeway) and does not provide safe and comfortable pedestrian facilities and crossings. No

Existing location lacks any pedestrian facilities (e.g., sidewalks, marked crossings, wide shoulders in rural contexts) and project does not add pedestrian elements (e.g., reconstruction of a roadway without sidewalks, that doesnt also add pedestrian crossings and sidewalk or sidepath on one or both sides). No

### **SUB-MEASURE 1: Project-Based Pedestrian Safety Enhancements and Risk Elements**

To receive maximum points in this category, pedestrian safety countermeasures selected for implementation in projects should be, to the greatest extent feasible, consistent with the countermeasure recommendations in the Regional Pedestrian Safety Action Plan and state and national best practices. Links to resources are provided on the Regional Solicitation Resources web page.

Please answer the following two questions with as much detail as possible based on the known attributes of the proposed design. If any aspect referenced in this section is not yet determined, describe the range of options being considered, to the greatest extent available. If there are project elements that may increase pedestrian risk, describe how these risks are being mitigated.

#### **1. Describe how this project will address the safety needs of people crossing the street at signalized intersections, unsignalized intersections, midblock locations, and roundabouts.**

Treatments and countermeasures should be well-matched to the roadways context (e.g., appropriate for the speed, volume, crossing distance, and other location attributes). Refer to the Regional Solicitation Resources web page for guidance links.



In the last 10 years there have been five pedestrian/vehicle crashes within the project limits. Two were minor injury crashes and three were possible injury crashes. The project improvements will have a direct impact on pedestrian and bicycle safety as described below.

The project will add curb extensions to reduce crossing distances and high visibility continental crosswalk markings to further enhance the pedestrian and bicycle safety along the corridor. Additionally, a boulevard space between the sidewalk and bikeway will be incorporated into the design to provide a more comfortable pedestrian space along both sides of the corridor. Finally, a two-way separated bikeway at sidewalk height will be added on the west side of Wabasha Street.

**Response:**

According to PEDSAFE, curb extensions improve pedestrian safety by reducing the pedestrian crossing distance, reducing the time that pedestrians are in the street, visually and physically narrowing the roadway, and improving the ability of pedestrians and motorists to see each other. MnDOT also recommends the incorporation of curb extensions as a best practice for increasing pedestrian and bicycle safety.

Another PEDSAFE countermeasure the project will include is reduced lane widths to improve the safety and comfort of pedestrians, and other modes of travel by shortening the crossing distance and lowering vehicle speeds. In addition, the short block lengths will naturally discourage mid-block crossings.

PEDSAFE also states designing streets for bicycle use helps create a more predictable traffic environment by reducing conflicts between all

modes of travel, whether the conflict is between bicyclists and motor vehicles or pedestrians and bicyclists. Dedicated bicycle facilities (e.g., bicycle lanes) on the roadway also help provide a buffer between pedestrians and motor vehicle traffic, encourage lower motor vehicle speeds, and reduce pedestrian exposure to motor vehicles at crossings. Bicycle lanes are also a proven safety countermeasure per FHWA by creating a safer and more comfortable environment for bicyclists and can mitigate or prevent interactions, conflicts and crashes between bicycles and motor vehicles.

Crosswalk visibility enhancements will be incorporated into the project through the implementation of upgraded lighting, signing, pavement markings and high-visibility continental crosswalk markings. Each of these items are proven safety countermeasures according to FHWA. FHWA notes that high-visibility crosswalks can reduce pedestrian injury crashes up to 40 percent and intersection lighting can reduce pedestrian crashes up to 42 percent.

*(Limit 2,800 characters; approximately 400 words)*

*Is the distance in between signalized intersections increasing (e.g., removing a signal)?*

**Select one:**

No

*If yes, describe what measures are being used to fill the gap between protected crossing opportunities for pedestrians (e.g., adding High-Intensity Activated Crosswalk beacons to help motorists yield and help pedestrians find a suitable gap for crossing, turning signal into a roundabout to slow motorist speed, etc.).*

**Response:**

*(Limit 1,400 characters; approximately 200 words)*

*Will your design increase the crossing distance or crossing time across any leg of an intersection? (e.g., by adding turn or through lanes, widening lanes, using a multi-phase crossing, prohibiting crossing on any leg of an intersection, pedestrian bridge requiring length detour, etc.). This does not include any increases to crossing distances solely due to the addition of bike lanes (i.e., no other through or turn lanes being added or widened).*

**Select one:**

No

*If yes,*

*How many intersections will likely be affected?*

**Response:**

Describe what measures are being used to reduce exposure and delay for pedestrians (e.g., median crossing islands, curb bulb-outs, etc.)

**Response:**

*(Limit 1,400 characters; approximately 200 words)*

*If grade separated pedestrian crossings are being added and increasing crossing time, describe any features that are included that will reduce the detour required of pedestrians and make the separated crossing a more appealing option (e.g., shallow tunnel that doesn't require much elevation change instead of pedestrian bridge with numerous switchbacks).*

**Response:**

*(Limit 1,400 characters; approximately 200 words)*

*If mid-block crossings are restricted or blocked, explain why this is necessary and how pedestrian crossing needs and safety are supported in other ways (e.g., nearest protected or enhanced crossing opportunity).*

**Response:**

*(Limit 1,400 characters; approximately 200 words)*

**2. Describe how motorist speed will be managed in the project design, both for through traffic and turning movements.** Describe any project-related factors that may affect speed directly or indirectly, even if speed is not the intended outcome (e.g., wider lanes and turning radii to facilitate freight movements, adding turn lanes to alleviate peak hour congestion, etc.). Note any strategies or treatments being considered that are intended to help motorists drive slower (e.g., visual narrowing, narrow lanes, truck aprons to mitigate wide turning radii, etc.) or protect pedestrians if increasing motorist speed (e.g., buffers or other separation from moving vehicles, crossing treatments appropriate for higher speed roadways, etc.).

The Wabasha Street reconstruction project will add a dedicated bicycle facility with the construction of a separated two-way bikeway on the west side of the roadway. According to PEDSAFE, dedicated bicycle facilities (e.g., bicycle lanes) on the roadway help provide a buffer between pedestrians and motor vehicle traffic, encourage lower motor vehicle speeds, and reduce pedestrian exposure to motor vehicles at crossings.

**Response:**

The project will also remove parking on the west side of the roadway between 7th Street and 10th Street and add curb extensions at all intersections. Both of these features will narrow the space for vehicles and calm traffic thereby naturally slowing vehicle speeds.

*(Limit 2,800 characters; approximately 400 words)*

*If known, what are the existing and proposed design, operation, and posted speeds? Is this an increase or decrease from existing conditions?*

**Response:**

The posted speed limit on Wabasha Street is 25 mph. The proposed project is not anticipated to change the posted speed limit on Wabasha Street.

*(Limit 1,400 characters; approximately 200 words)*

**SUB-MEASURE 2: Existing Location-Based Pedestrian Safety Risk Factors**

These factors are based on based on trends and patterns observed in pedestrian crash analysis done for the Regional Pedestrian Safety Action Plan. Check off how many of the following factors are present. Applicants receive more points if more risk factors are present.

Existing road configuration is a One-way, 3+ through lanes or Yes

Existing road configuration is a Two-way, 4+ through lanes

Existing road has a design speed, posted speed limit, or speed study/data showing 85th percentile travel speeds in excess of 30 MPH or more

Existing road has AADT of greater than 15,000 vehicles per day

List the AADT

**SUB-MEASURE 3: Existing Location-Based Pedestrian Safety Exposure Factors**

These factors are based on based on trends and patterns observed in pedestrian crash analysis done for the Regional Pedestrian Safety Action Plan. Check off how many of the following existing location exposure factors are present. Applicants receive more points if more risk factors are present.

Existing road has transit running on or across it with 1+ transit stops in the project area (If flag-stop route with no fixed stops, then 1+ locations in the project area where roadside stops are allowed. Do not count portions of transit routes with no stops, such as non-stop freeway sections of express or limited-stop routes. If service was temporarily reduced for the pandemic but is expected to return to 2019 levels, consider 2019 service for this item.) Yes

Existing road has high-frequency transit running on or across it and 1+ high-frequency stops in the project area (high-frequency defined as service at least every 15 minutes from 6am to 7pm weekdays and 9am to 6pm Saturdays. If service frequency was temporarily reduced for the pandemic but is expected to return to 2019 levels, consider 2019 frequency for this item.) Yes

Existing road is within 500 of 1+ shopping, dining, or entertainment destinations (e.g., grocery store, restaurant) Yes

If checked, please describe:

Downtown St. Paul offers a wide variety of performing arts venues, museums, and dining options to walk using the City's extensive sidewalk system. As shown in the attached "Affordable Housing and Destination" map there are numerous shopping, dining, and entertainment destinations within 500 feet of the project including, but not limited to the History Theatre, Fitzgerald Theater, Palace Theatre, Minnesota Children's Museum, Walgreens, Peters Market, Pho Vietnamese, Ruam Mit Thai + Lao Food, Subway, Mickey's Diner, and Afro Deli & Grill.

(Limit 1,400 characters; approximately 200 words)

Existing road is within 500 of other known pedestrian generators (e.g., school, civic/community center, senior housing, multifamily housing, regulatorily-designated affordable housing) Yes

If checked, please describe:

As shown in the attached "Affordable Housing and Destination" map there are known pedestrian generators within 500 feet of the project including numerous affordable housing (e.g., Exchange Hi-Rise, Wabasha Hi-Rise, Central Towers), schools (e.g., Upper Mississippi Academy), civic/community center (e.g., St. Paul Public Housing Agency, Fairview St. Josephs Campus), and several churches (e.g., Church of Scientology, Central Presbyterian Church).

*(Limit 1,400 characters; approximately 200 words)*

---

## Measure A: Multimodal Elements and Existing Connections

Wabasha Street is a high-density corridor with existing land use patterns that support active transportation and increasing development that demands it. The City's Complete Streets Policy will guide the design of this project, redistributing space within the right-of-way to the most vulnerable users: pedestrians, bicyclists, and transit users. The project will positively affect the multimodal system as described in detail below.

#### Bicycle and Pedestrian Elements and Connections

- The project is located in an RBTN Tier 1 Corridor and includes reconstruction of the deteriorated sidewalks and non-compliant curb ramps along Wabasha Street. All intersections will include ADA compliant curb ramps, curb extensions to reduce crossing distances, and high visibility continental crosswalk markings to further enhance the pedestrian and bicycle safety along the corridor. A buffered green space between the sidewalk and roadway will be incorporated into the design to provide a more comfortable pedestrian space along both sides of the corridor. Finally, a two-way separated bikeway at sidewalk height will be added on the west side of Wabasha Street. This bikeway facility is part of the Capacity City Bikeway corridor that connects bike trails, the Grand Round trails, and fills and gap in the citywide bike infrastructure. The Capital City Bikeway is consistent with the city goals and priorities identified in the St. Paul Bicycle Plan, the 2040 Comprehensive Plan, and the Climate Action and Resiliency Plan. The City is constructing the Capital City Bikeway segment between Kellogg Boulevard and 7th Street in 2022. This project will tie into this project at 7th Street and continue the bikeway north to 10th Street.

Transit Connections - The proposed project will enhance pedestrian and bicycle access to Metro Transit routes 3, 62, and 67 offer service along 11th

Response:

Street with a stop just west of the project area. Route 3 offers high-frequency weekday service and service every half hour on weekends between downtown Minneapolis and Union Depot in downtown St. Paul. The route also connects to the A Line BRT and Metro Green Line LRT. Route 62 offers weekday and weekend service between West St. Paul and Shoreview and connects to downtown Minneapolis and Target Field via the Metro Green Line LRT. Route 67 offers weekday and weekend service between Franklin Avenue in Minneapolis and downtown St. Paul. The route provides connection to the Metro Green LRT, Metro Blue LRT, and the A Line BRT.

*(Limit 2,800 characters; approximately 400 words)*

---

## Transit Projects Not Requiring Construction

*If the applicant is completing a transit application that is operations only, check the box and do not complete the remainder of the form. These projects will receive full points for the Risk Assessment.*

*Park-and-Ride and other transit construction projects require completion of the Risk Assessment below.*

**Check Here if Your Transit Project Does Not Require Construction**

---

## Measure A: Risk Assessment - Construction Projects

### 1. Public Involvement (20 Percent of Points)

*Projects that have been through a public process with residents and other interested public entities are more likely than others to be successful. The project applicant must indicate that events and/or targeted outreach (e.g., surveys and other web-based input) were held to help identify the transportation problem, how the potential solution was selected instead of other options, and the public involvement completed to date on the project. The focus of this section is on the opportunity for public input as opposed to the quality of input. NOTE: A written response is required and failure to respond will result in zero points.*

**Multiple types of targeted outreach efforts (such as meetings or online/mail outreach) specific to this project with the general public and partner agencies have been used to help identify the project need.**

100%

**At least one meeting specific to this project with the general public has been used to help identify the project need.**

Yes

50%

**At least online/mail outreach effort specific to this project with the general public has been used to help identify the project need.**

50%

**No meeting or outreach specific to this project was conducted, but the project was identified through meetings and/or outreach related to a larger planning effort.**

25%

**No outreach has led to the selection of this project.**

0%

*Describe the type(s) of outreach selected for this project (i.e., online or in-person meetings, surveys, demonstration projects), the method(s) used to announce outreach opportunities, and how many people participated. Include any public website links to outreach opportunities.*



Community engagement has occurred through community planning efforts, starting with the St. Paul Bike Plan public hearing conducted in December 2014 - summary of the meeting at [www.stpaul.gov/bikeplan](http://www.stpaul.gov/bikeplan).

The Capital City Bikeway: Network Study and Design Guide was completed in 2016. Outreach opportunities included:

- A four day "discovery workshop" was held in May 2015 with individual stakeholder interviews with community leaders, downtown business/property owners, cultural institution representatives, local organizations, City staff, and elected officials.
- A four-day design workshop was held in June 2015 with "open studio" hours for the public to provide input and react to the designs.
- Four pop-up events took place to gather additional project input on the project at Mears Park, Pedro Park, and Rondo Days, including a bike ride at Rondo Days with the NiceRide Neighborhood Group and Major Taylor Bicycling Club.

**Response:**

The Capital City Interim Design Study was completed in 2021 and included a comprehensive public outreach campaign as described below:

- Three public open houses (May 2019, October 2019 and February 2020) with a total of 235 in attendance.
- The City sent out direct mailings to adjacent residents and businesses, distributed a public notice, and sent out an email to the project contact list notifying the public of each of the open houses.
- The City also facilitated three online surveys in coordination with the public open houses. A total of

420 responses were received.

- Final recommendations were shared with the City Council at a public hearing on May 21, 2021.
- Targeted stakeholder engagement including direct outreach to stakeholders and meetings with stakeholder groups was completed.
- The study was guided by a Technical Advisory Committee.

Additional details on this outreach can be found here <https://www.stpaul.gov/projects/public-works/pw2022ccbwest#project-documents>

*(Limit 2,800 characters; approximately 400 words)*

## **2.Layout (25 Percent of Points)**

*Layout includes proposed geometrics and existing and proposed right-of-way boundaries. A basic layout should include a base map (north arrow; scale; legend;\* city and/or county limits; existing ROW, labeled; existing signals;\* and bridge numbers\*) and design data (proposed alignments; bike and/or roadway lane widths; shoulder width;\* proposed signals;\* and proposed ROW). An aerial photograph with a line showing the projects termini does not suffice and will be awarded zero points. \*If applicable*

**Layout approved by the applicant and all impacted jurisdictions (i.e., cities/counties/MnDOT. If a MnDOT trunk highway is impacted, approval by MnDOT must have occurred to receive full points. A PDF of the layout must be attached along with letters from each jurisdiction to receive points.**

100%

**A layout does not apply (signal replacement/signal timing, stand-alone streetscaping, minor intersection improvements). Applicants that are not certain whether a layout is required should contact Colleen Brown at MnDOT Metro State Aid [colleen.brown@state.mn.us](mailto:colleen.brown@state.mn.us).**

100%

**For projects where MnDOT trunk highways are impacted and a MnDOT Staff Approved layout is required. Layout approved by the applicant and all impacted local jurisdictions (i.e., cities/counties), and layout review and approval by MnDOT is pending. A PDF of the layout must be attached along with letters from each jurisdiction to receive points.**

75%

**Layout completed but not approved by all jurisdictions. A PDF of the layout must be attached to receive points.** Yes

50%

**Layout has been started but is not complete. A PDF of the layout must be attached to receive points.**

25%

**Layout has not been started**

0%

**Attach Layout**

1649889370440\_Wabasha\_Layout.pdf

Please upload attachment in PDF form.

**Additional Attachments**

Please upload attachment in PDF form.

**3.Review of Section 106 Historic Resources (15 Percent of Points)**

No known historic properties eligible for or listed in the National Register of Historic Places are located in the project area, and project is not located on an identified historic bridge Yes

100%

There are historical/archeological properties present but determination of no historic properties affected is anticipated.

100%

Historic/archeological property impacted; determination of no adverse effect anticipated

80%

Historic/archeological property impacted; determination of adverse effect anticipated

40%

Unsure if there are any historic/archaeological properties in the project area.

0%

Project is located on an identified historic bridge

**4.Right-of-Way (25 Percent of Points)**

Right-of-way, permanent or temporary easements, and MnDOT agreement/limited-use permit either not required or all have been acquired Yes

100%

Right-of-way, permanent or temporary easements, and/or MnDOT agreement/limited-use permit required - plat, legal descriptions, or official map complete

50%

Right-of-way, permanent or temporary easements, and/or MnDOT agreement/limited-use permit required - parcels identified

25%

Right-of-way, permanent or temporary easements, and/or MnDOT agreement/limited-use permit required - parcels not all identified

0%

**5.Railroad Involvement (15 Percent of Points)**

No railroad involvement on project or railroad Right-of-Way agreement is executed (include signature page, if applicable) Yes

100%

Signature Page

Please upload attachment in PDF form.

**Railroad Right-of-Way Agreement required; negotiations have begun**

50%

**Railroad Right-of-Way Agreement required; negotiations have not begun.**

0%

---

## Measure A: Cost Effectiveness

Total Project Cost (entered in Project Cost Form):	\$6,672,000.00
Enter Amount of the Noise Walls:	\$0.00
Total Project Cost subtract the amount of the noise walls:	\$6,672,000.00
Enter amount of any outside, competitive funding:	\$0.00
Attach documentation of award:	
Points Awarded in Previous Criteria	
Cost Effectiveness	\$0.00

---

## Other Attachments

File Name	Description	File Size
Wabasha Project Summary.pdf	1-page Project Summary	295 KB
WabashaCongestionMap.pdf	Met Council Congestion Map	2.5 MB
Wabasha_Existing photos.pdf	Existing Photos	751 KB
Wabasha_LOS_City.pdf	City Resolution	96 KB
Wabasha_LOS_MnDOT.pdf	MnDOT Letter of Support	262 KB

# Regional Economy

Roadway Reconstruction/Modernization Project: Wabasha Street | Map ID: 1648301685072


## Results

**WITHIN ONE MI** of project:  
Postsecondary Students: 5823


Totals by City:

### St. Paul

Population: 39948  
Employment: 81472  
Mfg and Dist Employment: 3804



- Project Points
- Postsecondary Education Centers
- Job Concentration Centers
- Manufacturing/Distribution Centers
- Project



Created: 3/26/2022  
LandscapeRSA5



For complete disclaimer of accuracy, please visit <http://giswebsite.metc.state.mn.us/gissitenew/notice.aspx>



# Transit Connections

Roadway Reconstruction/Modernization Project: Wabasha Street | Map ID: 1648301685072




## Results

Transit with a Direct Connection to project:  
3 62 67 75 902  
\*G Line

\*indicates Planned Alignments

Transit Market areas: 1

- |  |                            |  |                             |  |                             |  |                            |  |                             |  |                           |
|--|----------------------------|--|-----------------------------|--|-----------------------------|--|----------------------------|--|-----------------------------|--|---------------------------|
|  | Project Points             |  | Commuter Rail               |  | Commuter Rail               |  | Arterial Bus Rapid Transit |  | Undetermined                |  | Light Rail                |
|  | Project                    |  | Dedicated Bus Rapid Transit |  | Dedicated Bus Rapid Transit |  | Arterial Bus Rapid Transit |  | Undetermined                |  | Modern Streetcar          |
|  | Project Area               |  | Highway Bus Rapid Transit   |  | Highway Bus Rapid Transit   |  | Arterial Bus Rapid Transit |  | Commuter Rail               |  | Undetermined              |
|  | Active Stop                |  | Light Rail                  |  | Light Rail                  |  | Light Rail                 |  | Dedicated Bus Rapid Transit |  | Highway Bus Rapid Transit |
|  | Arterial Bus Rapid Transit |  | Arterial Bus Rapid Transit  |  | Transit Routes              |  | Modern Streetcar           |  | Highway Bus Rapid Transit   |  |                           |



Created: 3/26/2022  
LandscapeRSA3



For complete disclaimer of accuracy, please visit  
<https://giswebsite.metc.state.mn.us/gis/site/notice.aspx>




# Socio-Economic Conditions





Roadway Reconstruction/Modernization Project: Wabasha Street | Map ID: 1648301685072


## Results

Total of publicly subsidized rental housing units in census tracts within 1/2 mile: 4604

Project located in census tract(s) that are ABOVE the regional average for population in poverty or population of color.



-  Points
-  Area of Concentrated Poverty
-  Lines
-  Regional Environmental Justice Area




Created: 3/26/2022  
LandscapeRSA2











For complete disclaimer of accuracy, please visit <http://giswebsite.metc.state.mn.us/gis/site/notice.aspx>



L:\Projects\150001\5563\GIS - Projects\ArcGIS - Proj\RegionalSolutions\_2022.aprx



### Wabasha Street Reconstruction (7th Street to 11th Street) Equity Populations and Destinations

-  Proposed Project
-  Census Tracts
-  1/2 Mile Project Boundary
-  Place of Worship
-  School / Daycare
-  Senior Housing
-  Medical / Social Services
-  Affordable Housing











0 0.5 Miles



L:\Projects\150001\5563\GIS\_Projects\ArcGIS\_Pro\RegionalSolutions\_2022.aprx



### Wabasha Street Reconstruction (7th Street to 11th Street) Affordable Housing and Destinations

-  Proposed Project
-  Census Tracts
-  1/2 Mile Project Boundary
-  Place of Worship
-  Retail / Grocery
-  School / Daycare
-  Medical / Social Services
-  Restaurant
-  Affordable Housing
-  Entertainment

0 0.5 Miles

**Wabasha**

1 Wabasha Ave and 11th St		
Existing Volume	1732	vehicles
Existing Delay	9	sec/veh
Existing Total Delay	15588	seconds
Future Volume	1732	vehicles
Future Delay	9	sec/veh
Future Total Delay	15588	seconds
Total Delay Reduction	0	seconds

2 Wabasha Ave and 10th St		
Existing Volume	1625	vehicles
Existing Delay	11	sec/veh
Existing Total Delay	17875	seconds
Future Volume	1625	vehicles
Future Delay	11	sec/veh
Future Total Delay	17875	seconds
Total Delay Reduction	0	seconds

3 Wabasha Ave and Exchange St		
Existing Volume	1286	vehicles
Existing Delay	8	sec/veh
Existing Total Delay	10288	seconds
Future Volume	1286	vehicles
Future Delay	8	sec/veh
Future Total Delay	10288	seconds
Total Delay Reduction	0	seconds

4 Wabasha Ave and 7th St		
Existing Volume	2292	vehicles
Existing Delay	15	sec/veh
Existing Total Delay	34380	seconds
Future Volume	2292	vehicles
Future Delay	15	sec/veh
Future Total Delay	34380	seconds
Total Delay Reduction	0	seconds

<b>Total Network Delay Reduction</b>	<b>0 seconds</b>
--------------------------------------	------------------

**Emissions**

Existing	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

Build	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

<b>Reduction</b>	<b>0</b>
------------------	----------



Lane Group	EBT	NBT	NBR
Lane Configurations	↔↑	↑↑	↗
Traffic Volume (vph)	274	828	602
Future Volume (vph)	274	828	602
Turn Type	NA	NA	Perm
Protected Phases	4	2	
Permitted Phases			2
Detector Phase	4	2	2
Switch Phase			
Minimum Initial (s)	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5
Total Split (s)	22.6	37.4	37.4
Total Split (%)	37.7%	62.3%	62.3%
Yellow Time (s)	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5
Lead/Lag			
Lead-Lag Optimize?			
Recall Mode	None	C-Max	C-Max
Act Effct Green (s)	10.6	40.4	40.4
Actuated g/C Ratio	0.18	0.67	0.67
v/c Ratio	0.51	0.38	0.56
Control Delay	22.8	5.2	5.1
Queue Delay	0.0	0.5	1.3
Total Delay	22.8	5.8	6.4
LOS	C	A	A
Approach Delay	22.8	6.1	
Approach LOS	C	A	

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 60  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.56  
 Intersection Signal Delay: 9.0  
 Intersection Capacity Utilization 53.2%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 1: 11th St & Wabasha






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↶	↷	↶↷↶↷
Traffic Volume (vph)	253	102	42	1151
Future Volume (vph)	253	102	42	1151
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		16.0	16.0	20.0
Actuated g/C Ratio		0.36	0.36	0.44
v/c Ratio		0.79	0.12	0.58
Control Delay		26.4	7.9	6.7
Queue Delay		0.0	0.0	0.0
Total Delay		26.4	7.9	6.7
LOS		C	A	A
Approach Delay		26.4	7.9	6.7
Approach LOS		C	A	A

**Intersection Summary**

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.79  
 Intersection Signal Delay: 11.1  
 Intersection Capacity Utilization 56.8%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 2: Wabasha & 10th St






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	122	23	35	1055
Future Volume (vph)	122	23	35	1055
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		10.4	10.3	28.6
Actuated g/C Ratio		0.23	0.23	0.64
v/c Ratio		0.51	0.12	0.37
Control Delay		20.0	10.2	6.1
Queue Delay		0.0	0.0	0.0
Total Delay		20.0	10.2	6.1
LOS		B	B	A
Approach Delay		20.0	10.2	6.1
Approach LOS		B	B	A


Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.51  
 Intersection Signal Delay: 7.9  
 Intersection Capacity Utilization 43.3%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 3: Exchange St & Wabasha






Lane Group	EBL	EBT	WBT	WBR	NBL	NBT
Lane Configurations	↖	↑↑	↑↑	↗	↖	↑↑
Traffic Volume (vph)	174	613	526	176	84	660
Future Volume (vph)	174	613	526	176	84	660
Turn Type	pm+pt	NA	NA	Perm	Perm	NA
Protected Phases	7	4	8			2
Permitted Phases	4			8	2	
Detector Phase	7	4	8	8	2	2
Switch Phase						
Minimum Initial (s)	5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	9.5	22.5	22.5	22.5	22.5	22.5
Total Split (s)	9.6	32.1	22.5	22.5	22.9	22.9
Total Split (%)	17.5%	58.4%	40.9%	40.9%	41.6%	41.6%
Yellow Time (s)	3.5	3.5	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5	4.5	4.5	4.5
Lead/Lag	Lead		Lag	Lag		
Lead-Lag Optimize?	Yes		Yes	Yes		
Recall Mode	None	None	None	None	C-Max	C-Max
Act Effct Green (s)	23.0	23.0	15.3	15.3	23.0	23.0
Actuated g/C Ratio	0.42	0.42	0.28	0.28	0.42	0.42
v/c Ratio	0.59	0.45	0.58	0.36	0.12	0.53
Control Delay	16.9	11.8	19.3	8.4	12.9	14.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	16.9	11.8	19.3	8.4	12.9	14.8
LOS	B	B	B	A	B	B
Approach Delay		12.9	16.5			14.6
Approach LOS		B	B			B

Intersection Summary

Cycle Length: 55  
 Actuated Cycle Length: 55  
 Offset: 0 (0%), Referenced to phase 2:NBTL and 6:, Start of Green  
 Natural Cycle: 55  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.59  
 Intersection Signal Delay: 14.6  
 Intersection Capacity Utilization 55.6%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 4: Wabasha & 7th St



---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	11
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	8
CO Emissions (kg)	0.65
NOx Emissions (kg)	0.13
VOC Emissions (kg)	0.15

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕						↕↕	↗			
Traffic Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Future Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Initial Q (Qb), veh	0	0	0				0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00				1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00				1.00	1.00	1.00			
Work Zone On Approach		No						No				
Adj Sat Flow, veh/h/ln	1870	1870	0				0	1870	1870			
Adj Flow Rate, veh/h	30	298	0				0	900	654			
Peak Hour Factor	0.92	0.92	0.92				0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0				0	2	2			
Cap, veh/h	98	475	0				0	2499	1115			
Arrive On Green	0.15	0.15	0.00				0.00	0.70	0.70			
Sat Flow, veh/h	192	3319	0				0	3647	1585			
Grp Volume(v), veh/h	178	150	0				0	900	654			
Grp Sat Flow(s),veh/h/ln	1809	1617	0				0	1777	1585			
Q Serve(g_s), s	2.4	5.2	0.0				0.0	6.0	12.5			
Cycle Q Clear(g_c), s	5.5	5.2	0.0				0.0	6.0	12.5			
Prop In Lane	0.17		0.00				0.00		1.00			
Lane Grp Cap(c), veh/h	336	237	0				0	2499	1115			
V/C Ratio(X)	0.53	0.63	0.00				0.00	0.36	0.59			
Avail Cap(c_a), veh/h	611	488	0				0	2499	1115			
HCM Platoon Ratio	1.00	1.00	1.00				1.00	1.00	1.00			
Upstream Filter(l)	1.00	1.00	0.00				0.00	0.79	0.79			
Uniform Delay (d), s/veh	24.2	24.1	0.0				0.0	3.5	4.5			
Incr Delay (d2), s/veh	1.3	2.8	0.0				0.0	0.3	1.8			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0				0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	2.3	2.1	0.0				0.0	1.4	2.9			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.5	26.9	0.0				0.0	3.9	6.3			
LnGrp LOS	C	C	A				A	A	A			
Approach Vol, veh/h		328						1554				
Approach Delay, s/veh		26.1						4.9				
Approach LOS		C						A				
Timer - Assigned Phs		2		4								
Phs Duration (G+Y+Rc), s		46.7		13.3								
Change Period (Y+Rc), s		4.5		4.5								
Max Green Setting (Gmax), s		32.9		18.1								
Max Q Clear Time (g_c+I1), s		14.5		7.5								
Green Ext Time (p_c), s		9.0		1.3								
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay			8.6									
HCM 6th LOS			A									





Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕↕				
Traffic Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Future Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	275	111	0	0	46	29	24	1251	30			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	450	139	0	0	358	225	44	2423	60			
Arrive On Green	0.33	0.33	0.00	0.00	0.33	0.33	0.15	0.15	0.15			
Sat Flow, veh/h	938	418	0	0	1073	676	94	5192	129			
Grp Volume(v), veh/h	386	0	0	0	0	75	478	397	431			
Grp Sat Flow(s),veh/h/ln	1355	0	0	0	0	1749	1866	1702	1847			
Q Serve(g_s), s	10.9	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Cycle Q Clear(g_c), s	12.2	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Prop In Lane	0.71		0.00	0.00		0.39	0.05		0.07			
Lane Grp Cap(c), veh/h	589	0	0	0	0	583	871	794	862			
V/C Ratio(X)	0.66	0.00	0.00	0.00	0.00	0.13	0.55	0.50	0.50			
Avail Cap(c_a), veh/h	685	0	0	0	0	699	871	794	862			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.83	0.83	0.83			
Uniform Delay (d), s/veh	14.5	0.0	0.0	0.0	0.0	10.4	14.7	14.2	14.2			
Incr Delay (d2), s/veh	1.8	0.0	0.0	0.0	0.0	0.1	2.1	1.9	1.7			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	3.3	0.0	0.0	0.0	0.0	0.4	5.3	4.2	4.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	16.3	0.0	0.0	0.0	0.0	10.5	16.7	16.1	15.9			
LnGrp LOS	B	A	A	A	A	B	B	B	B			
Approach Vol, veh/h		386			75			1305				
Approach Delay, s/veh		16.3			10.5			16.3				
Approach LOS		B			B			B				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		25.5		19.5				19.5				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		12.7		14.2				3.3				
Green Ext Time (p_c), s		3.5		0.8				0.2				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				16.0								
HCM 6th LOS				B								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕				
Traffic Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Future Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	133	25	0	0	38	13	28	1147	14			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	316	44	0	0	222	76	53	2280	29			
Arrive On Green	0.17	0.17	0.00	0.00	0.17	0.17	0.63	0.63	0.63			
Sat Flow, veh/h	1016	263	0	0	1332	456	84	3598	46			
Grp Volume(v), veh/h	158	0	0	0	0	51	623	0	566			
Grp Sat Flow(s),veh/h/ln	1280	0	0	0	0	1788	1866	0	1862			
Q Serve(g_s), s	4.4	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Cycle Q Clear(g_c), s	5.5	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Prop In Lane	0.84		0.00	0.00		0.25	0.04		0.02			
Lane Grp Cap(c), veh/h	360	0	0	0	0	297	1183	0	1180			
V/C Ratio(X)	0.44	0.00	0.00	0.00	0.00	0.17	0.53	0.00	0.48			
Avail Cap(c_a), veh/h	691	0	0	0	0	715	1183	0	1180			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.85	0.00	0.85			
Uniform Delay (d), s/veh	18.2	0.0	0.0	0.0	0.0	16.1	4.5	0.0	4.3			
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.0	0.0	0.3	1.4	0.0	1.2			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.5	0.0	0.0	0.0	0.0	0.4	2.0	0.0	1.8			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	19.1	0.0	0.0	0.0	0.0	16.4	6.0	0.0	5.5			
LnGrp LOS	B	A	A	A	A	B	A	A	A			
Approach Vol, veh/h		158			51			1189				
Approach Delay, s/veh		19.1			16.4			5.8				
Approach LOS		B			B			A				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		33.0		12.0				12.0				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		10.3		7.5				3.1				
Green Ext Time (p_c), s		4.5		0.6				0.1				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				7.6								
HCM 6th LOS				A								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↗			↖	↗	↖	↗				
Traffic Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Future Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	189	666	0	0	572	191	91	717	64			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	358	1453	0	0	832	371	762	1411	126			
Arrive On Green	0.09	0.41	0.00	0.00	0.23	0.23	0.43	0.43	0.43			
Sat Flow, veh/h	1781	3647	0	0	3647	1585	1781	3300	294			
Grp Volume(v), veh/h	189	666	0	0	572	191	91	386	395			
Grp Sat Flow(s),veh/h/ln	1781	1777	0	0	1777	1585	1781	1777	1817			
Q Serve(g_s), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Cycle Q Clear(g_c), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Prop In Lane	1.00		0.00	0.00		1.00	1.00		0.16			
Lane Grp Cap(c), veh/h	358	1453	0	0	832	371	762	760	777			
V/C Ratio(X)	0.53	0.46	0.00	0.00	0.69	0.51	0.12	0.51	0.51			
Avail Cap(c_a), veh/h	358	1783	0	0	1163	519	762	760	777			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	1.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00			
Uniform Delay (d), s/veh	13.7	11.8	0.0	0.0	19.2	18.3	9.5	11.5	11.5			
Incr Delay (d2), s/veh	1.5	0.2	0.0	0.0	1.0	1.1	0.3	2.4	2.4			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.6	2.6	0.0	0.0	3.1	2.0	0.6	3.4	3.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	15.2	12.1	0.0	0.0	20.2	19.4	9.8	13.9	13.9			
LnGrp LOS	B	B	A	A	C	B	A	B	B			
Approach Vol, veh/h		855			763			872				
Approach Delay, s/veh		12.7			20.0			13.5				
Approach LOS		B			C			B				
Timer - Assigned Phs		2		4			7	8				
Phs Duration (G+Y+Rc), s		28.0		27.0			9.6	17.4				
Change Period (Y+Rc), s		4.5		4.5			4.5	4.5				
Max Green Setting (Gmax), s		18.4		27.6			5.1	18.0				
Max Q Clear Time (g_c+I1), s		10.7		9.5			6.2	10.1				
Green Ext Time (p_c), s		3.1		4.4			0.0	2.8				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				15.2								
HCM 6th LOS				B								

---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	12
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.72
NOx Emissions (kg)	0.14
VOC Emissions (kg)	0.17

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35

**Wabasha**

1	Wabasha Ave and 11th St	
Existing Volume	1732	vehicles
Existing Delay	9	sec/veh
Existing Total Delay	15588	seconds
Future Volume	1732	vehicles
Future Delay	9	sec/veh
Future Total Delay	15588	seconds
Total Delay Reduction	0	seconds

2	Wabasha Ave and 10th St	
Existing Volume	1625	vehicles
Existing Delay	11	sec/veh
Existing Total Delay	17875	seconds
Future Volume	1625	vehicles
Future Delay	11	sec/veh
Future Total Delay	17875	seconds
Total Delay Reduction	0	seconds

3	Wabasha Ave and Exchange St	
Existing Volume	1286	vehicles
Existing Delay	8	sec/veh
Existing Total Delay	10288	seconds
Future Volume	1286	vehicles
Future Delay	8	sec/veh
Future Total Delay	10288	seconds
Total Delay Reduction	0	seconds

4	Wabasha Ave and 7th St	
Existing Volume	2292	vehicles
Existing Delay	15	sec/veh
Existing Total Delay	34380	seconds
Future Volume	2292	vehicles
Future Delay	15	sec/veh
Future Total Delay	34380	seconds
Total Delay Reduction	0	seconds

<b>Total Network Delay Reduction</b>	<b>0 seconds</b>
--------------------------------------	------------------

**Emissions**

Existing	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

Build	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

<b>Reduction</b>	<b>0</b>
------------------	----------



Lane Group	EBT	NBT	NBR
Lane Configurations	↔↑	↑↑	↗
Traffic Volume (vph)	274	828	602
Future Volume (vph)	274	828	602
Turn Type	NA	NA	Perm
Protected Phases	4	2	
Permitted Phases			2
Detector Phase	4	2	2
Switch Phase			
Minimum Initial (s)	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5
Total Split (s)	22.6	37.4	37.4
Total Split (%)	37.7%	62.3%	62.3%
Yellow Time (s)	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5
Lead/Lag			
Lead-Lag Optimize?			
Recall Mode	None	C-Max	C-Max
Act Effct Green (s)	10.6	40.4	40.4
Actuated g/C Ratio	0.18	0.67	0.67
v/c Ratio	0.51	0.38	0.56
Control Delay	22.8	5.2	5.1
Queue Delay	0.0	0.5	1.3
Total Delay	22.8	5.8	6.4
LOS	C	A	A
Approach Delay	22.8	6.1	
Approach LOS	C	A	

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 60  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.56  
 Intersection Signal Delay: 9.0  
 Intersection Capacity Utilization 53.2%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 1: 11th St & Wabasha






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	253	102	42	1151
Future Volume (vph)	253	102	42	1151
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		16.0	16.0	20.0
Actuated g/C Ratio		0.36	0.36	0.44
v/c Ratio		0.79	0.12	0.58
Control Delay		26.4	7.9	6.7
Queue Delay		0.0	0.0	0.0
Total Delay		26.4	7.9	6.7
LOS		C	A	A
Approach Delay		26.4	7.9	6.7
Approach LOS		C	A	A

Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.79  
 Intersection Signal Delay: 11.1  
 Intersection Capacity Utilization 56.8%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 2: Wabasha & 10th St






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	122	23	35	1055
Future Volume (vph)	122	23	35	1055
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		10.4	10.3	28.6
Actuated g/C Ratio		0.23	0.23	0.64
v/c Ratio		0.51	0.12	0.37
Control Delay		20.0	10.2	6.1
Queue Delay		0.0	0.0	0.0
Total Delay		20.0	10.2	6.1
LOS		B	B	A
Approach Delay		20.0	10.2	6.1
Approach LOS		B	B	A

Intersection Summary


Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.51  
 Intersection Signal Delay: 7.9  
 Intersection Capacity Utilization 43.3%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 3: Exchange St & Wabasha








Lane Group	EBL	EBT	WBT	WBR	NBL	NBT
Lane Configurations	↖	↑↑	↑↑	↗	↖	↑↑
Traffic Volume (vph)	174	613	526	176	84	660
Future Volume (vph)	174	613	526	176	84	660
Turn Type	pm+pt	NA	NA	Perm	Perm	NA
Protected Phases	7	4	8			2
Permitted Phases	4			8	2	
Detector Phase	7	4	8	8	2	2
Switch Phase						
Minimum Initial (s)	5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	9.5	22.5	22.5	22.5	22.5	22.5
Total Split (s)	9.6	32.1	22.5	22.5	22.9	22.9
Total Split (%)	17.5%	58.4%	40.9%	40.9%	41.6%	41.6%
Yellow Time (s)	3.5	3.5	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5	4.5	4.5	4.5
Lead/Lag	Lead		Lag	Lag		
Lead-Lag Optimize?	Yes		Yes	Yes		
Recall Mode	None	None	None	None	C-Max	C-Max
Act Effct Green (s)	23.0	23.0	15.3	15.3	23.0	23.0
Actuated g/C Ratio	0.42	0.42	0.28	0.28	0.42	0.42
v/c Ratio	0.59	0.45	0.58	0.36	0.12	0.53
Control Delay	16.9	11.8	19.3	8.4	12.9	14.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	16.9	11.8	19.3	8.4	12.9	14.8
LOS	B	B	B	A	B	B
Approach Delay		12.9	16.5			14.6
Approach LOS		B	B			B

Intersection Summary

Cycle Length: 55  
 Actuated Cycle Length: 55  
 Offset: 0 (0%), Referenced to phase 2:NBTL and 6:, Start of Green  
 Natural Cycle: 55  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.59  
 Intersection Signal Delay: 14.6  
 Intersection Capacity Utilization 55.6%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 4: Wabasha & 7th St



---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	11
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	8
CO Emissions (kg)	0.65
NOx Emissions (kg)	0.13
VOC Emissions (kg)	0.15

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕						↕↕	↗			
Traffic Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Future Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Initial Q (Qb), veh	0	0	0				0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00				1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00				1.00	1.00	1.00			
Work Zone On Approach		No						No				
Adj Sat Flow, veh/h/ln	1870	1870	0				0	1870	1870			
Adj Flow Rate, veh/h	30	298	0				0	900	654			
Peak Hour Factor	0.92	0.92	0.92				0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0				0	2	2			
Cap, veh/h	98	475	0				0	2499	1115			
Arrive On Green	0.15	0.15	0.00				0.00	0.70	0.70			
Sat Flow, veh/h	192	3319	0				0	3647	1585			
Grp Volume(v), veh/h	178	150	0				0	900	654			
Grp Sat Flow(s),veh/h/ln	1809	1617	0				0	1777	1585			
Q Serve(g_s), s	2.4	5.2	0.0				0.0	6.0	12.5			
Cycle Q Clear(g_c), s	5.5	5.2	0.0				0.0	6.0	12.5			
Prop In Lane	0.17		0.00				0.00		1.00			
Lane Grp Cap(c), veh/h	336	237	0				0	2499	1115			
V/C Ratio(X)	0.53	0.63	0.00				0.00	0.36	0.59			
Avail Cap(c_a), veh/h	611	488	0				0	2499	1115			
HCM Platoon Ratio	1.00	1.00	1.00				1.00	1.00	1.00			
Upstream Filter(l)	1.00	1.00	0.00				0.00	0.79	0.79			
Uniform Delay (d), s/veh	24.2	24.1	0.0				0.0	3.5	4.5			
Incr Delay (d2), s/veh	1.3	2.8	0.0				0.0	0.3	1.8			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0				0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	2.3	2.1	0.0				0.0	1.4	2.9			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.5	26.9	0.0				0.0	3.9	6.3			
LnGrp LOS	C	C	A				A	A	A			
Approach Vol, veh/h		328						1554				
Approach Delay, s/veh		26.1						4.9				
Approach LOS		C						A				
Timer - Assigned Phs		2		4								
Phs Duration (G+Y+Rc), s		46.7		13.3								
Change Period (Y+Rc), s		4.5		4.5								
Max Green Setting (Gmax), s		32.9		18.1								
Max Q Clear Time (g_c+I1), s		14.5		7.5								
Green Ext Time (p_c), s		9.0		1.3								
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay			8.6									
HCM 6th LOS			A									



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↔			↕↕↕				
Traffic Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Future Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	275	111	0	0	46	29	24	1251	30			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	450	139	0	0	358	225	44	2423	60			
Arrive On Green	0.33	0.33	0.00	0.00	0.33	0.33	0.15	0.15	0.15			
Sat Flow, veh/h	938	418	0	0	1073	676	94	5192	129			
Grp Volume(v), veh/h	386	0	0	0	0	75	478	397	431			
Grp Sat Flow(s),veh/h/ln	1355	0	0	0	0	1749	1866	1702	1847			
Q Serve(g_s), s	10.9	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Cycle Q Clear(g_c), s	12.2	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Prop In Lane	0.71		0.00	0.00		0.39	0.05		0.07			
Lane Grp Cap(c), veh/h	589	0	0	0	0	583	871	794	862			
V/C Ratio(X)	0.66	0.00	0.00	0.00	0.00	0.13	0.55	0.50	0.50			
Avail Cap(c_a), veh/h	685	0	0	0	0	699	871	794	862			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.83	0.83	0.83			
Uniform Delay (d), s/veh	14.5	0.0	0.0	0.0	0.0	10.4	14.7	14.2	14.2			
Incr Delay (d2), s/veh	1.8	0.0	0.0	0.0	0.0	0.1	2.1	1.9	1.7			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	3.3	0.0	0.0	0.0	0.0	0.4	5.3	4.2	4.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	16.3	0.0	0.0	0.0	0.0	10.5	16.7	16.1	15.9			
LnGrp LOS	B	A	A	A	A	B	B	B	B			
Approach Vol, veh/h		386			75			1305				
Approach Delay, s/veh		16.3			10.5			16.3				
Approach LOS		B			B			B				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		25.5		19.5				19.5				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		12.7		14.2				3.3				
Green Ext Time (p_c), s		3.5		0.8				0.2				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				16.0								
HCM 6th LOS				B								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕				
Traffic Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Future Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	133	25	0	0	38	13	28	1147	14			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	316	44	0	0	222	76	53	2280	29			
Arrive On Green	0.17	0.17	0.00	0.00	0.17	0.17	0.63	0.63	0.63			
Sat Flow, veh/h	1016	263	0	0	1332	456	84	3598	46			
Grp Volume(v), veh/h	158	0	0	0	0	51	623	0	566			
Grp Sat Flow(s),veh/h/ln	1280	0	0	0	0	1788	1866	0	1862			
Q Serve(g_s), s	4.4	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Cycle Q Clear(g_c), s	5.5	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Prop In Lane	0.84		0.00	0.00		0.25	0.04		0.02			
Lane Grp Cap(c), veh/h	360	0	0	0	0	297	1183	0	1180			
V/C Ratio(X)	0.44	0.00	0.00	0.00	0.00	0.17	0.53	0.00	0.48			
Avail Cap(c_a), veh/h	691	0	0	0	0	715	1183	0	1180			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.85	0.00	0.85			
Uniform Delay (d), s/veh	18.2	0.0	0.0	0.0	0.0	16.1	4.5	0.0	4.3			
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.0	0.0	0.3	1.4	0.0	1.2			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.5	0.0	0.0	0.0	0.0	0.4	2.0	0.0	1.8			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	19.1	0.0	0.0	0.0	0.0	16.4	6.0	0.0	5.5			
LnGrp LOS	B	A	A	A	A	B	A	A	A			
Approach Vol, veh/h		158			51			1189				
Approach Delay, s/veh		19.1			16.4			5.8				
Approach LOS		B			B			A				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		33.0		12.0				12.0				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		10.3		7.5				3.1				
Green Ext Time (p_c), s		4.5		0.6				0.1				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				7.6								
HCM 6th LOS				A								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↗			↖	↗	↖	↗				
Traffic Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Future Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	189	666	0	0	572	191	91	717	64			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	358	1453	0	0	832	371	762	1411	126			
Arrive On Green	0.09	0.41	0.00	0.00	0.23	0.23	0.43	0.43	0.43			
Sat Flow, veh/h	1781	3647	0	0	3647	1585	1781	3300	294			
Grp Volume(v), veh/h	189	666	0	0	572	191	91	386	395			
Grp Sat Flow(s),veh/h/ln	1781	1777	0	0	1777	1585	1781	1777	1817			
Q Serve(g_s), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Cycle Q Clear(g_c), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Prop In Lane	1.00		0.00	0.00		1.00	1.00		0.16			
Lane Grp Cap(c), veh/h	358	1453	0	0	832	371	762	760	777			
V/C Ratio(X)	0.53	0.46	0.00	0.00	0.69	0.51	0.12	0.51	0.51			
Avail Cap(c_a), veh/h	358	1783	0	0	1163	519	762	760	777			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	1.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00			
Uniform Delay (d), s/veh	13.7	11.8	0.0	0.0	19.2	18.3	9.5	11.5	11.5			
Incr Delay (d2), s/veh	1.5	0.2	0.0	0.0	1.0	1.1	0.3	2.4	2.4			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.6	2.6	0.0	0.0	3.1	2.0	0.6	3.4	3.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	15.2	12.1	0.0	0.0	20.2	19.4	9.8	13.9	13.9			
LnGrp LOS	B	B	A	A	C	B	A	B	B			
Approach Vol, veh/h		855			763			872				
Approach Delay, s/veh		12.7			20.0			13.5				
Approach LOS		B			C			B				
Timer - Assigned Phs		2		4			7	8				
Phs Duration (G+Y+Rc), s		28.0		27.0			9.6	17.4				
Change Period (Y+Rc), s		4.5		4.5			4.5	4.5				
Max Green Setting (Gmax), s		18.4		27.6			5.1	18.0				
Max Q Clear Time (g_c+I1), s		10.7		9.5			6.2	10.1				
Green Ext Time (p_c), s		3.1		4.4			0.0	2.8				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				15.2								
HCM 6th LOS				B								

---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	12
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.72
NOx Emissions (kg)	0.14
VOC Emissions (kg)	0.17

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35

**Wabasha**

1 Wabasha Ave and 11th St		
Existing Volume	1732	vehicles
Existing Delay	9	sec/veh
Existing Total Delay	15588	seconds
Future Volume	1732	vehicles
Future Delay	9	sec/veh
Future Total Delay	15588	seconds
Total Delay Reduction	0	seconds

2 Wabasha Ave and 10th St		
Existing Volume	1625	vehicles
Existing Delay	11	sec/veh
Existing Total Delay	17875	seconds
Future Volume	1625	vehicles
Future Delay	11	sec/veh
Future Total Delay	17875	seconds
Total Delay Reduction	0	seconds

3 Wabasha Ave and Exchange St		
Existing Volume	1286	vehicles
Existing Delay	8	sec/veh
Existing Total Delay	10288	seconds
Future Volume	1286	vehicles
Future Delay	8	sec/veh
Future Total Delay	10288	seconds
Total Delay Reduction	0	seconds

4 Wabasha Ave and 7th St		
Existing Volume	2292	vehicles
Existing Delay	15	sec/veh
Existing Total Delay	34380	seconds
Future Volume	2292	vehicles
Future Delay	15	sec/veh
Future Total Delay	34380	seconds
Total Delay Reduction	0	seconds

<b>Total Network Delay Reduction</b>	<b>0 seconds</b>
--------------------------------------	------------------

**Emissions**

Existing	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

Build	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

<b>Reduction</b>	<b>0</b>
------------------	----------





Lane Group	EBT	NBT	NBR
Lane Configurations	↔↑	↑↑	↗
Traffic Volume (vph)	274	828	602
Future Volume (vph)	274	828	602
Turn Type	NA	NA	Perm
Protected Phases	4	2	
Permitted Phases			2
Detector Phase	4	2	2
Switch Phase			
Minimum Initial (s)	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5
Total Split (s)	22.6	37.4	37.4
Total Split (%)	37.7%	62.3%	62.3%
Yellow Time (s)	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5
Lead/Lag			
Lead-Lag Optimize?			
Recall Mode	None	C-Max	C-Max
Act Effct Green (s)	10.6	40.4	40.4
Actuated g/C Ratio	0.18	0.67	0.67
v/c Ratio	0.51	0.38	0.56
Control Delay	22.8	5.2	5.1
Queue Delay	0.0	0.5	1.3
Total Delay	22.8	5.8	6.4
LOS	C	A	A
Approach Delay	22.8	6.1	
Approach LOS	C	A	

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 60  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.56  
 Intersection Signal Delay: 9.0  
 Intersection Capacity Utilization 53.2%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 1: 11th St & Wabasha






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	253	102	42	1151
Future Volume (vph)	253	102	42	1151
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		16.0	16.0	20.0
Actuated g/C Ratio		0.36	0.36	0.44
v/c Ratio		0.79	0.12	0.58
Control Delay		26.4	7.9	6.7
Queue Delay		0.0	0.0	0.0
Total Delay		26.4	7.9	6.7
LOS		C	A	A
Approach Delay		26.4	7.9	6.7
Approach LOS		C	A	A

Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.79  
 Intersection Signal Delay: 11.1  
 Intersection Capacity Utilization 56.8%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 2: Wabasha & 10th St







Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	122	23	35	1055
Future Volume (vph)	122	23	35	1055
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		10.4	10.3	28.6
Actuated g/C Ratio		0.23	0.23	0.64
v/c Ratio		0.51	0.12	0.37
Control Delay		20.0	10.2	6.1
Queue Delay		0.0	0.0	0.0
Total Delay		20.0	10.2	6.1
LOS		B	B	A
Approach Delay		20.0	10.2	6.1
Approach LOS		B	B	A

**Intersection Summary**  
 Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.51  
 Intersection Signal Delay: 7.9  
 Intersection Capacity Utilization 43.3%  
 Analysis Period (min) 15  
 Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 3: Exchange St & Wabasha






Lane Group	EBL	EBT	WBT	WBR	NBL	NBT
Lane Configurations	↖	↑↑	↑↑	↗	↖	↑↑
Traffic Volume (vph)	174	613	526	176	84	660
Future Volume (vph)	174	613	526	176	84	660
Turn Type	pm+pt	NA	NA	Perm	Perm	NA
Protected Phases	7	4	8			2
Permitted Phases	4			8	2	
Detector Phase	7	4	8	8	2	2
Switch Phase						
Minimum Initial (s)	5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	9.5	22.5	22.5	22.5	22.5	22.5
Total Split (s)	9.6	32.1	22.5	22.5	22.9	22.9
Total Split (%)	17.5%	58.4%	40.9%	40.9%	41.6%	41.6%
Yellow Time (s)	3.5	3.5	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5	4.5	4.5	4.5
Lead/Lag	Lead		Lag	Lag		
Lead-Lag Optimize?	Yes		Yes	Yes		
Recall Mode	None	None	None	None	C-Max	C-Max
Act Effct Green (s)	23.0	23.0	15.3	15.3	23.0	23.0
Actuated g/C Ratio	0.42	0.42	0.28	0.28	0.42	0.42
v/c Ratio	0.59	0.45	0.58	0.36	0.12	0.53
Control Delay	16.9	11.8	19.3	8.4	12.9	14.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	16.9	11.8	19.3	8.4	12.9	14.8
LOS	B	B	B	A	B	B
Approach Delay		12.9	16.5			14.6
Approach LOS		B	B			B

Intersection Summary

Cycle Length: 55  
 Actuated Cycle Length: 55  
 Offset: 0 (0%), Referenced to phase 2:NBTL and 6:, Start of Green  
 Natural Cycle: 55  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.59  
 Intersection Signal Delay: 14.6  
 Intersection Capacity Utilization 55.6%  
 Analysis Period (min) 15

Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 4: Wabasha & 7th St



---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	11
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	8
CO Emissions (kg)	0.65
NOx Emissions (kg)	0.13
VOC Emissions (kg)	0.15

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕						↕↕	↗			
Traffic Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Future Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Initial Q (Qb), veh	0	0	0				0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00				1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00				1.00	1.00	1.00			
Work Zone On Approach		No						No				
Adj Sat Flow, veh/h/ln	1870	1870	0				0	1870	1870			
Adj Flow Rate, veh/h	30	298	0				0	900	654			
Peak Hour Factor	0.92	0.92	0.92				0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0				0	2	2			
Cap, veh/h	98	475	0				0	2499	1115			
Arrive On Green	0.15	0.15	0.00				0.00	0.70	0.70			
Sat Flow, veh/h	192	3319	0				0	3647	1585			
Grp Volume(v), veh/h	178	150	0				0	900	654			
Grp Sat Flow(s),veh/h/ln	1809	1617	0				0	1777	1585			
Q Serve(g_s), s	2.4	5.2	0.0				0.0	6.0	12.5			
Cycle Q Clear(g_c), s	5.5	5.2	0.0				0.0	6.0	12.5			
Prop In Lane	0.17		0.00				0.00		1.00			
Lane Grp Cap(c), veh/h	336	237	0				0	2499	1115			
V/C Ratio(X)	0.53	0.63	0.00				0.00	0.36	0.59			
Avail Cap(c_a), veh/h	611	488	0				0	2499	1115			
HCM Platoon Ratio	1.00	1.00	1.00				1.00	1.00	1.00			
Upstream Filter(l)	1.00	1.00	0.00				0.00	0.79	0.79			
Uniform Delay (d), s/veh	24.2	24.1	0.0				0.0	3.5	4.5			
Incr Delay (d2), s/veh	1.3	2.8	0.0				0.0	0.3	1.8			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0				0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	2.3	2.1	0.0				0.0	1.4	2.9			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.5	26.9	0.0				0.0	3.9	6.3			
LnGrp LOS	C	C	A				A	A	A			
Approach Vol, veh/h		328						1554				
Approach Delay, s/veh		26.1						4.9				
Approach LOS		C						A				
Timer - Assigned Phs		2		4								
Phs Duration (G+Y+Rc), s		46.7		13.3								
Change Period (Y+Rc), s		4.5		4.5								
Max Green Setting (Gmax), s		32.9		18.1								
Max Q Clear Time (g_c+I1), s		14.5		7.5								
Green Ext Time (p_c), s		9.0		1.3								
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay			8.6									
HCM 6th LOS			A									



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↔			↕↕↕				
Traffic Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Future Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	275	111	0	0	46	29	24	1251	30			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	450	139	0	0	358	225	44	2423	60			
Arrive On Green	0.33	0.33	0.00	0.00	0.33	0.33	0.15	0.15	0.15			
Sat Flow, veh/h	938	418	0	0	1073	676	94	5192	129			
Grp Volume(v), veh/h	386	0	0	0	0	75	478	397	431			
Grp Sat Flow(s),veh/h/ln	1355	0	0	0	0	1749	1866	1702	1847			
Q Serve(g_s), s	10.9	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Cycle Q Clear(g_c), s	12.2	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Prop In Lane	0.71		0.00	0.00		0.39	0.05		0.07			
Lane Grp Cap(c), veh/h	589	0	0	0	0	583	871	794	862			
V/C Ratio(X)	0.66	0.00	0.00	0.00	0.00	0.13	0.55	0.50	0.50			
Avail Cap(c_a), veh/h	685	0	0	0	0	699	871	794	862			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.83	0.83	0.83			
Uniform Delay (d), s/veh	14.5	0.0	0.0	0.0	0.0	10.4	14.7	14.2	14.2			
Incr Delay (d2), s/veh	1.8	0.0	0.0	0.0	0.0	0.1	2.1	1.9	1.7			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	3.3	0.0	0.0	0.0	0.0	0.4	5.3	4.2	4.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	16.3	0.0	0.0	0.0	0.0	10.5	16.7	16.1	15.9			
LnGrp LOS	B	A	A	A	A	B	B	B	B			
Approach Vol, veh/h		386			75			1305				
Approach Delay, s/veh		16.3			10.5			16.3				
Approach LOS		B			B			B				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		25.5		19.5				19.5				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		12.7		14.2				3.3				
Green Ext Time (p_c), s		3.5		0.8				0.2				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				16.0								
HCM 6th LOS				B								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕				
Traffic Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Future Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	133	25	0	0	38	13	28	1147	14			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	316	44	0	0	222	76	53	2280	29			
Arrive On Green	0.17	0.17	0.00	0.00	0.17	0.17	0.63	0.63	0.63			
Sat Flow, veh/h	1016	263	0	0	1332	456	84	3598	46			
Grp Volume(v), veh/h	158	0	0	0	0	51	623	0	566			
Grp Sat Flow(s),veh/h/ln	1280	0	0	0	0	1788	1866	0	1862			
Q Serve(g_s), s	4.4	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Cycle Q Clear(g_c), s	5.5	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Prop In Lane	0.84		0.00	0.00		0.25	0.04		0.02			
Lane Grp Cap(c), veh/h	360	0	0	0	0	297	1183	0	1180			
V/C Ratio(X)	0.44	0.00	0.00	0.00	0.00	0.17	0.53	0.00	0.48			
Avail Cap(c_a), veh/h	691	0	0	0	0	715	1183	0	1180			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.85	0.00	0.85			
Uniform Delay (d), s/veh	18.2	0.0	0.0	0.0	0.0	16.1	4.5	0.0	4.3			
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.0	0.0	0.3	1.4	0.0	1.2			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.5	0.0	0.0	0.0	0.0	0.4	2.0	0.0	1.8			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	19.1	0.0	0.0	0.0	0.0	16.4	6.0	0.0	5.5			
LnGrp LOS	B	A	A	A	A	B	A	A	A			
Approach Vol, veh/h		158			51			1189				
Approach Delay, s/veh		19.1			16.4			5.8				
Approach LOS		B			B			A				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		33.0		12.0				12.0				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		10.3		7.5				3.1				
Green Ext Time (p_c), s		4.5		0.6				0.1				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				7.6								
HCM 6th LOS				A								





Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↗			↖	↗	↖	↗				
Traffic Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Future Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	189	666	0	0	572	191	91	717	64			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	358	1453	0	0	832	371	762	1411	126			
Arrive On Green	0.09	0.41	0.00	0.00	0.23	0.23	0.43	0.43	0.43			
Sat Flow, veh/h	1781	3647	0	0	3647	1585	1781	3300	294			
Grp Volume(v), veh/h	189	666	0	0	572	191	91	386	395			
Grp Sat Flow(s),veh/h/ln	1781	1777	0	0	1777	1585	1781	1777	1817			
Q Serve(g_s), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Cycle Q Clear(g_c), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Prop In Lane	1.00		0.00	0.00		1.00	1.00		0.16			
Lane Grp Cap(c), veh/h	358	1453	0	0	832	371	762	760	777			
V/C Ratio(X)	0.53	0.46	0.00	0.00	0.69	0.51	0.12	0.51	0.51			
Avail Cap(c_a), veh/h	358	1783	0	0	1163	519	762	760	777			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	1.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00			
Uniform Delay (d), s/veh	13.7	11.8	0.0	0.0	19.2	18.3	9.5	11.5	11.5			
Incr Delay (d2), s/veh	1.5	0.2	0.0	0.0	1.0	1.1	0.3	2.4	2.4			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.6	2.6	0.0	0.0	3.1	2.0	0.6	3.4	3.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	15.2	12.1	0.0	0.0	20.2	19.4	9.8	13.9	13.9			
LnGrp LOS	B	B	A	A	C	B	A	B	B			
Approach Vol, veh/h		855			763			872				
Approach Delay, s/veh		12.7			20.0			13.5				
Approach LOS		B			C			B				
Timer - Assigned Phs		2		4			7	8				
Phs Duration (G+Y+Rc), s		28.0		27.0			9.6	17.4				
Change Period (Y+Rc), s		4.5		4.5			4.5	4.5				
Max Green Setting (Gmax), s		18.4		27.6			5.1	18.0				
Max Q Clear Time (g_c+I1), s		10.7		9.5			6.2	10.1				
Green Ext Time (p_c), s		3.1		4.4			0.0	2.8				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				15.2								
HCM 6th LOS				B								

---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	12
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.72
NOx Emissions (kg)	0.14
VOC Emissions (kg)	0.17

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35

**Wabasha**

1	Wabasha Ave and 11th St	
Existing Volume	1732	vehicles
Existing Delay	9	sec/veh
Existing Total Delay	15588	seconds
Future Volume	1732	vehicles
Future Delay	9	sec/veh
Future Total Delay	15588	seconds
Total Delay Reduction	0	seconds

2	Wabasha Ave and 10th St	
Existing Volume	1625	vehicles
Existing Delay	11	sec/veh
Existing Total Delay	17875	seconds
Future Volume	1625	vehicles
Future Delay	11	sec/veh
Future Total Delay	17875	seconds
Total Delay Reduction	0	seconds

3	Wabasha Ave and Exchange St	
Existing Volume	1286	vehicles
Existing Delay	8	sec/veh
Existing Total Delay	10288	seconds
Future Volume	1286	vehicles
Future Delay	8	sec/veh
Future Total Delay	10288	seconds
Total Delay Reduction	0	seconds

4	Wabasha Ave and 7th St	
Existing Volume	2292	vehicles
Existing Delay	15	sec/veh
Existing Total Delay	34380	seconds
Future Volume	2292	vehicles
Future Delay	15	sec/veh
Future Total Delay	34380	seconds
Total Delay Reduction	0	seconds

<b>Total Network Delay Reduction</b>	<b>0 seconds</b>
--------------------------------------	------------------

**Emissions**

Existing	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

Build	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

<b>Reduction</b>	<b>0</b>
------------------	----------



Lane Group	EBT	NBT	NBR
Lane Configurations	↔↑	↑↑	↗
Traffic Volume (vph)	274	828	602
Future Volume (vph)	274	828	602
Turn Type	NA	NA	Perm
Protected Phases	4	2	
Permitted Phases			2
Detector Phase	4	2	2
Switch Phase			
Minimum Initial (s)	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5
Total Split (s)	22.6	37.4	37.4
Total Split (%)	37.7%	62.3%	62.3%
Yellow Time (s)	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5
Lead/Lag			
Lead-Lag Optimize?			
Recall Mode	None	C-Max	C-Max
Act Effct Green (s)	10.6	40.4	40.4
Actuated g/C Ratio	0.18	0.67	0.67
v/c Ratio	0.51	0.38	0.56
Control Delay	22.8	5.2	5.1
Queue Delay	0.0	0.5	1.3
Total Delay	22.8	5.8	6.4
LOS	C	A	A
Approach Delay	22.8	6.1	
Approach LOS	C	A	

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 60  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.56  
 Intersection Signal Delay: 9.0  
 Intersection Capacity Utilization 53.2%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 1: 11th St & Wabasha






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	253	102	42	1151
Future Volume (vph)	253	102	42	1151
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		16.0	16.0	20.0
Actuated g/C Ratio		0.36	0.36	0.44
v/c Ratio		0.79	0.12	0.58
Control Delay		26.4	7.9	6.7
Queue Delay		0.0	0.0	0.0
Total Delay		26.4	7.9	6.7
LOS		C	A	A
Approach Delay		26.4	7.9	6.7
Approach LOS		C	A	A

Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.79  
 Intersection Signal Delay: 11.1  
 Intersection Capacity Utilization 56.8%  
 Analysis Period (min) 15

Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 2: Wabasha & 10th St







Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↕	↔	↕↕↕
Traffic Volume (vph)	122	23	35	1055
Future Volume (vph)	122	23	35	1055
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		10.4	10.3	28.6
Actuated g/C Ratio		0.23	0.23	0.64
v/c Ratio		0.51	0.12	0.37
Control Delay		20.0	10.2	6.1
Queue Delay		0.0	0.0	0.0
Total Delay		20.0	10.2	6.1
LOS		B	B	A
Approach Delay		20.0	10.2	6.1
Approach LOS		B	B	A

Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.51  
 Intersection Signal Delay: 7.9  
 Intersection Capacity Utilization 43.3%  
 Analysis Period (min) 15  
 Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 3: Exchange St & Wabasha






Lane Group	EBL	EBT	WBT	WBR	NBL	NBT
Lane Configurations	↖	↑↑	↑↑	↗	↖	↑↑
Traffic Volume (vph)	174	613	526	176	84	660
Future Volume (vph)	174	613	526	176	84	660
Turn Type	pm+pt	NA	NA	Perm	Perm	NA
Protected Phases	7	4	8			2
Permitted Phases	4			8	2	
Detector Phase	7	4	8	8	2	2
Switch Phase						
Minimum Initial (s)	5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	9.5	22.5	22.5	22.5	22.5	22.5
Total Split (s)	9.6	32.1	22.5	22.5	22.9	22.9
Total Split (%)	17.5%	58.4%	40.9%	40.9%	41.6%	41.6%
Yellow Time (s)	3.5	3.5	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5	4.5	4.5	4.5
Lead/Lag	Lead		Lag	Lag		
Lead-Lag Optimize?	Yes		Yes	Yes		
Recall Mode	None	None	None	None	C-Max	C-Max
Act Effct Green (s)	23.0	23.0	15.3	15.3	23.0	23.0
Actuated g/C Ratio	0.42	0.42	0.28	0.28	0.42	0.42
v/c Ratio	0.59	0.45	0.58	0.36	0.12	0.53
Control Delay	16.9	11.8	19.3	8.4	12.9	14.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	16.9	11.8	19.3	8.4	12.9	14.8
LOS	B	B	B	A	B	B
Approach Delay		12.9	16.5			14.6
Approach LOS		B	B			B

Intersection Summary

Cycle Length: 55  
 Actuated Cycle Length: 55  
 Offset: 0 (0%), Referenced to phase 2:NBTL and 6:, Start of Green  
 Natural Cycle: 55  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.59  
 Intersection Signal Delay: 14.6  
 Intersection Capacity Utilization 55.6%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 4: Wabasha & 7th St



---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	11
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	8
CO Emissions (kg)	0.65
NOx Emissions (kg)	0.13
VOC Emissions (kg)	0.15

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35





Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕						↕↕	↗			
Traffic Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Future Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Initial Q (Qb), veh	0	0	0				0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00				1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00				1.00	1.00	1.00			
Work Zone On Approach		No						No				
Adj Sat Flow, veh/h/ln	1870	1870	0				0	1870	1870			
Adj Flow Rate, veh/h	30	298	0				0	900	654			
Peak Hour Factor	0.92	0.92	0.92				0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0				0	2	2			
Cap, veh/h	98	475	0				0	2499	1115			
Arrive On Green	0.15	0.15	0.00				0.00	0.70	0.70			
Sat Flow, veh/h	192	3319	0				0	3647	1585			
Grp Volume(v), veh/h	178	150	0				0	900	654			
Grp Sat Flow(s),veh/h/ln	1809	1617	0				0	1777	1585			
Q Serve(g_s), s	2.4	5.2	0.0				0.0	6.0	12.5			
Cycle Q Clear(g_c), s	5.5	5.2	0.0				0.0	6.0	12.5			
Prop In Lane	0.17		0.00				0.00		1.00			
Lane Grp Cap(c), veh/h	336	237	0				0	2499	1115			
V/C Ratio(X)	0.53	0.63	0.00				0.00	0.36	0.59			
Avail Cap(c_a), veh/h	611	488	0				0	2499	1115			
HCM Platoon Ratio	1.00	1.00	1.00				1.00	1.00	1.00			
Upstream Filter(l)	1.00	1.00	0.00				0.00	0.79	0.79			
Uniform Delay (d), s/veh	24.2	24.1	0.0				0.0	3.5	4.5			
Incr Delay (d2), s/veh	1.3	2.8	0.0				0.0	0.3	1.8			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0				0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	2.3	2.1	0.0				0.0	1.4	2.9			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.5	26.9	0.0				0.0	3.9	6.3			
LnGrp LOS	C	C	A				A	A	A			
Approach Vol, veh/h		328						1554				
Approach Delay, s/veh		26.1						4.9				
Approach LOS		C						A				
Timer - Assigned Phs		2		4								
Phs Duration (G+Y+Rc), s		46.7		13.3								
Change Period (Y+Rc), s		4.5		4.5								
Max Green Setting (Gmax), s		32.9		18.1								
Max Q Clear Time (g_c+I1), s		14.5		7.5								
Green Ext Time (p_c), s		9.0		1.3								
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay			8.6									
HCM 6th LOS			A									



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕↕				
Traffic Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Future Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	275	111	0	0	46	29	24	1251	30			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	450	139	0	0	358	225	44	2423	60			
Arrive On Green	0.33	0.33	0.00	0.00	0.33	0.33	0.15	0.15	0.15			
Sat Flow, veh/h	938	418	0	0	1073	676	94	5192	129			
Grp Volume(v), veh/h	386	0	0	0	0	75	478	397	431			
Grp Sat Flow(s),veh/h/ln	1355	0	0	0	0	1749	1866	1702	1847			
Q Serve(g_s), s	10.9	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Cycle Q Clear(g_c), s	12.2	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Prop In Lane	0.71		0.00	0.00		0.39	0.05		0.07			
Lane Grp Cap(c), veh/h	589	0	0	0	0	583	871	794	862			
V/C Ratio(X)	0.66	0.00	0.00	0.00	0.00	0.13	0.55	0.50	0.50			
Avail Cap(c_a), veh/h	685	0	0	0	0	699	871	794	862			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.83	0.83	0.83			
Uniform Delay (d), s/veh	14.5	0.0	0.0	0.0	0.0	10.4	14.7	14.2	14.2			
Incr Delay (d2), s/veh	1.8	0.0	0.0	0.0	0.0	0.1	2.1	1.9	1.7			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	3.3	0.0	0.0	0.0	0.0	0.4	5.3	4.2	4.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	16.3	0.0	0.0	0.0	0.0	10.5	16.7	16.1	15.9			
LnGrp LOS	B	A	A	A	A	B	B	B	B			
Approach Vol, veh/h		386			75			1305				
Approach Delay, s/veh		16.3			10.5			16.3				
Approach LOS		B			B			B				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		25.5		19.5				19.5				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		12.7		14.2				3.3				
Green Ext Time (p_c), s		3.5		0.8				0.2				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				16.0								
HCM 6th LOS				B								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕				
Traffic Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Future Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	133	25	0	0	38	13	28	1147	14			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	316	44	0	0	222	76	53	2280	29			
Arrive On Green	0.17	0.17	0.00	0.00	0.17	0.17	0.63	0.63	0.63			
Sat Flow, veh/h	1016	263	0	0	1332	456	84	3598	46			
Grp Volume(v), veh/h	158	0	0	0	0	51	623	0	566			
Grp Sat Flow(s),veh/h/ln	1280	0	0	0	0	1788	1866	0	1862			
Q Serve(g_s), s	4.4	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Cycle Q Clear(g_c), s	5.5	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Prop In Lane	0.84		0.00	0.00		0.25	0.04		0.02			
Lane Grp Cap(c), veh/h	360	0	0	0	0	297	1183	0	1180			
V/C Ratio(X)	0.44	0.00	0.00	0.00	0.00	0.17	0.53	0.00	0.48			
Avail Cap(c_a), veh/h	691	0	0	0	0	715	1183	0	1180			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.85	0.00	0.85			
Uniform Delay (d), s/veh	18.2	0.0	0.0	0.0	0.0	16.1	4.5	0.0	4.3			
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.0	0.0	0.3	1.4	0.0	1.2			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.5	0.0	0.0	0.0	0.0	0.4	2.0	0.0	1.8			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	19.1	0.0	0.0	0.0	0.0	16.4	6.0	0.0	5.5			
LnGrp LOS	B	A	A	A	A	B	A	A	A			
Approach Vol, veh/h		158			51			1189				
Approach Delay, s/veh		19.1			16.4			5.8				
Approach LOS		B			B			A				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		33.0		12.0				12.0				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		10.3		7.5				3.1				
Green Ext Time (p_c), s		4.5		0.6				0.1				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				7.6								
HCM 6th LOS				A								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↗			↖	↗	↖	↗				
Traffic Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Future Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	189	666	0	0	572	191	91	717	64			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	358	1453	0	0	832	371	762	1411	126			
Arrive On Green	0.09	0.41	0.00	0.00	0.23	0.23	0.43	0.43	0.43			
Sat Flow, veh/h	1781	3647	0	0	3647	1585	1781	3300	294			
Grp Volume(v), veh/h	189	666	0	0	572	191	91	386	395			
Grp Sat Flow(s),veh/h/ln	1781	1777	0	0	1777	1585	1781	1777	1817			
Q Serve(g_s), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Cycle Q Clear(g_c), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Prop In Lane	1.00		0.00	0.00		1.00	1.00		0.16			
Lane Grp Cap(c), veh/h	358	1453	0	0	832	371	762	760	777			
V/C Ratio(X)	0.53	0.46	0.00	0.00	0.69	0.51	0.12	0.51	0.51			
Avail Cap(c_a), veh/h	358	1783	0	0	1163	519	762	760	777			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	1.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00			
Uniform Delay (d), s/veh	13.7	11.8	0.0	0.0	19.2	18.3	9.5	11.5	11.5			
Incr Delay (d2), s/veh	1.5	0.2	0.0	0.0	1.0	1.1	0.3	2.4	2.4			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.6	2.6	0.0	0.0	3.1	2.0	0.6	3.4	3.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	15.2	12.1	0.0	0.0	20.2	19.4	9.8	13.9	13.9			
LnGrp LOS	B	B	A	A	C	B	A	B	B			
Approach Vol, veh/h		855			763			872				
Approach Delay, s/veh		12.7			20.0			13.5				
Approach LOS		B			C			B				
Timer - Assigned Phs		2		4			7	8				
Phs Duration (G+Y+Rc), s		28.0		27.0			9.6	17.4				
Change Period (Y+Rc), s		4.5		4.5			4.5	4.5				
Max Green Setting (Gmax), s		18.4		27.6			5.1	18.0				
Max Q Clear Time (g_c+I1), s		10.7		9.5			6.2	10.1				
Green Ext Time (p_c), s		3.1		4.4			0.0	2.8				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				15.2								
HCM 6th LOS				B								

---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	12
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.72
NOx Emissions (kg)	0.14
VOC Emissions (kg)	0.17

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35

**Wabasha**

1	Wabasha Ave and 11th St	
Existing Volume	1732	vehicles
Existing Delay	9	sec/veh
Existing Total Delay	15588	seconds
Future Volume	1732	vehicles
Future Delay	9	sec/veh
Future Total Delay	15588	seconds
Total Delay Reduction	0	seconds

2	Wabasha Ave and 10th St	
Existing Volume	1625	vehicles
Existing Delay	11	sec/veh
Existing Total Delay	17875	seconds
Future Volume	1625	vehicles
Future Delay	11	sec/veh
Future Total Delay	17875	seconds
Total Delay Reduction	0	seconds

3	Wabasha Ave and Exchange St	
Existing Volume	1286	vehicles
Existing Delay	8	sec/veh
Existing Total Delay	10288	seconds
Future Volume	1286	vehicles
Future Delay	8	sec/veh
Future Total Delay	10288	seconds
Total Delay Reduction	0	seconds

4	Wabasha Ave and 7th St	
Existing Volume	2292	vehicles
Existing Delay	15	sec/veh
Existing Total Delay	34380	seconds
Future Volume	2292	vehicles
Future Delay	15	sec/veh
Future Total Delay	34380	seconds
Total Delay Reduction	0	seconds

<b>Total Network Delay Reduction</b>	<b>0 seconds</b>
--------------------------------------	------------------

**Emissions**

Existing	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

Build	1	2	3	4	Total
CO	0.8	0.88	0.65	1.5	3.83
NO	0.15	0.17	0.13	0.29	0.74
VOC	0.18	0.2	0.15	0.35	0.88
Network Total					5.45

<b>Reduction</b>	<b>0</b>
------------------	----------



Lane Group	EBT	NBT	NBR
Lane Configurations	↔↑	↑↑	↗
Traffic Volume (vph)	274	828	602
Future Volume (vph)	274	828	602
Turn Type	NA	NA	Perm
Protected Phases	4	2	
Permitted Phases			2
Detector Phase	4	2	2
Switch Phase			
Minimum Initial (s)	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5
Total Split (s)	22.6	37.4	37.4
Total Split (%)	37.7%	62.3%	62.3%
Yellow Time (s)	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5
Lead/Lag			
Lead-Lag Optimize?			
Recall Mode	None	C-Max	C-Max
Act Effct Green (s)	10.6	40.4	40.4
Actuated g/C Ratio	0.18	0.67	0.67
v/c Ratio	0.51	0.38	0.56
Control Delay	22.8	5.2	5.1
Queue Delay	0.0	0.5	1.3
Total Delay	22.8	5.8	6.4
LOS	C	A	A
Approach Delay	22.8	6.1	
Approach LOS	C	A	

**Intersection Summary**

Cycle Length: 60  
 Actuated Cycle Length: 60  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 60  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.56  
 Intersection Signal Delay: 9.0  
 Intersection Capacity Utilization 53.2%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 1: 11th St & Wabasha






Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↶	↷	↶↷↶↷
Traffic Volume (vph)	253	102	42	1151
Future Volume (vph)	253	102	42	1151
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		16.0	16.0	20.0
Actuated g/C Ratio		0.36	0.36	0.44
v/c Ratio		0.79	0.12	0.58
Control Delay		26.4	7.9	6.7
Queue Delay		0.0	0.0	0.0
Total Delay		26.4	7.9	6.7
LOS		C	A	A
Approach Delay		26.4	7.9	6.7
Approach LOS		C	A	A

**Intersection Summary**

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.79  
 Intersection Signal Delay: 11.1  
 Intersection Capacity Utilization 56.8%  
 Analysis Period (min) 15

Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 2: Wabasha & 10th St








Lane Group	EBL	EBT	WBT	NBT
Lane Configurations		↶	↷	↶↷
Traffic Volume (vph)	122	23	35	1055
Future Volume (vph)	122	23	35	1055
Turn Type	Perm	NA	NA	NA
Protected Phases		4	8	2
Permitted Phases	4			
Detector Phase	4	4	8	2
Switch Phase				
Minimum Initial (s)	5.0	5.0	5.0	5.0
Minimum Split (s)	22.5	22.5	22.5	22.5
Total Split (s)	22.5	22.5	22.5	22.5
Total Split (%)	50.0%	50.0%	50.0%	50.0%
Yellow Time (s)	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		4.5	4.5	4.5
Lead/Lag				
Lead-Lag Optimize?				
Recall Mode	None	None	None	C-Max
Act Effct Green (s)		10.4	10.3	28.6
Actuated g/C Ratio		0.23	0.23	0.64
v/c Ratio		0.51	0.12	0.37
Control Delay		20.0	10.2	6.1
Queue Delay		0.0	0.0	0.0
Total Delay		20.0	10.2	6.1
LOS		B	B	A
Approach Delay		20.0	10.2	6.1
Approach LOS		B	B	A


Intersection Summary

Cycle Length: 45  
 Actuated Cycle Length: 45  
 Offset: 0 (0%), Referenced to phase 2:NBT and 6:, Start of Green  
 Natural Cycle: 45  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.51  
 Intersection Signal Delay: 7.9  
 Intersection Capacity Utilization 43.3%  
 Analysis Period (min) 15

Intersection LOS: A  
 ICU Level of Service A

Splits and Phases: 3: Exchange St & Wabasha






Lane Group	EBL	EBT	WBT	WBR	NBL	NBT
Lane Configurations	↖	↑↑	↑↑	↗	↖	↑↑
Traffic Volume (vph)	174	613	526	176	84	660
Future Volume (vph)	174	613	526	176	84	660
Turn Type	pm+pt	NA	NA	Perm	Perm	NA
Protected Phases	7	4	8			2
Permitted Phases	4			8	2	
Detector Phase	7	4	8	8	2	2
Switch Phase						
Minimum Initial (s)	5.0	5.0	5.0	5.0	5.0	5.0
Minimum Split (s)	9.5	22.5	22.5	22.5	22.5	22.5
Total Split (s)	9.6	32.1	22.5	22.5	22.9	22.9
Total Split (%)	17.5%	58.4%	40.9%	40.9%	41.6%	41.6%
Yellow Time (s)	3.5	3.5	3.5	3.5	3.5	3.5
All-Red Time (s)	1.0	1.0	1.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.5	4.5	4.5	4.5	4.5	4.5
Lead/Lag	Lead		Lag	Lag		
Lead-Lag Optimize?	Yes		Yes	Yes		
Recall Mode	None	None	None	None	C-Max	C-Max
Act Effct Green (s)	23.0	23.0	15.3	15.3	23.0	23.0
Actuated g/C Ratio	0.42	0.42	0.28	0.28	0.42	0.42
v/c Ratio	0.59	0.45	0.58	0.36	0.12	0.53
Control Delay	16.9	11.8	19.3	8.4	12.9	14.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	16.9	11.8	19.3	8.4	12.9	14.8
LOS	B	B	B	A	B	B
Approach Delay		12.9	16.5			14.6
Approach LOS		B	B			B

Intersection Summary

Cycle Length: 55  
 Actuated Cycle Length: 55  
 Offset: 0 (0%), Referenced to phase 2:NBTL and 6:, Start of Green  
 Natural Cycle: 55  
 Control Type: Actuated-Coordinated  
 Maximum v/c Ratio: 0.59  
 Intersection Signal Delay: 14.6  
 Intersection Capacity Utilization 55.6%  
 Analysis Period (min) 15  
 Intersection LOS: B  
 ICU Level of Service B

Splits and Phases: 4: Wabasha & 7th St



---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	11
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	8
CO Emissions (kg)	0.65
NOx Emissions (kg)	0.13
VOC Emissions (kg)	0.15

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕						↕↕	↗			
Traffic Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Future Volume (veh/h)	28	274	0	0	0	0	0	828	602	0	0	0
Initial Q (Qb), veh	0	0	0				0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00				1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00				1.00	1.00	1.00			
Work Zone On Approach		No						No				
Adj Sat Flow, veh/h/ln	1870	1870	0				0	1870	1870			
Adj Flow Rate, veh/h	30	298	0				0	900	654			
Peak Hour Factor	0.92	0.92	0.92				0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0				0	2	2			
Cap, veh/h	98	475	0				0	2499	1115			
Arrive On Green	0.15	0.15	0.00				0.00	0.70	0.70			
Sat Flow, veh/h	192	3319	0				0	3647	1585			
Grp Volume(v), veh/h	178	150	0				0	900	654			
Grp Sat Flow(s),veh/h/ln	1809	1617	0				0	1777	1585			
Q Serve(g_s), s	2.4	5.2	0.0				0.0	6.0	12.5			
Cycle Q Clear(g_c), s	5.5	5.2	0.0				0.0	6.0	12.5			
Prop In Lane	0.17		0.00				0.00		1.00			
Lane Grp Cap(c), veh/h	336	237	0				0	2499	1115			
V/C Ratio(X)	0.53	0.63	0.00				0.00	0.36	0.59			
Avail Cap(c_a), veh/h	611	488	0				0	2499	1115			
HCM Platoon Ratio	1.00	1.00	1.00				1.00	1.00	1.00			
Upstream Filter(l)	1.00	1.00	0.00				0.00	0.79	0.79			
Uniform Delay (d), s/veh	24.2	24.1	0.0				0.0	3.5	4.5			
Incr Delay (d2), s/veh	1.3	2.8	0.0				0.0	0.3	1.8			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0				0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	2.3	2.1	0.0				0.0	1.4	2.9			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	25.5	26.9	0.0				0.0	3.9	6.3			
LnGrp LOS	C	C	A				A	A	A			
Approach Vol, veh/h		328						1554				
Approach Delay, s/veh		26.1						4.9				
Approach LOS		C						A				
Timer - Assigned Phs		2		4								
Phs Duration (G+Y+Rc), s		46.7		13.3								
Change Period (Y+Rc), s		4.5		4.5								
Max Green Setting (Gmax), s		32.9		18.1								
Max Q Clear Time (g_c+I1), s		14.5		7.5								
Green Ext Time (p_c), s		9.0		1.3								
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay			8.6									
HCM 6th LOS			A									



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕↕				
Traffic Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Future Volume (veh/h)	253	102	0	0	42	27	22	1151	28	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	275	111	0	0	46	29	24	1251	30			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	450	139	0	0	358	225	44	2423	60			
Arrive On Green	0.33	0.33	0.00	0.00	0.33	0.33	0.15	0.15	0.15			
Sat Flow, veh/h	938	418	0	0	1073	676	94	5192	129			
Grp Volume(v), veh/h	386	0	0	0	0	75	478	397	431			
Grp Sat Flow(s),veh/h/ln	1355	0	0	0	0	1749	1866	1702	1847			
Q Serve(g_s), s	10.9	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Cycle Q Clear(g_c), s	12.2	0.0	0.0	0.0	0.0	1.3	10.7	9.6	9.6			
Prop In Lane	0.71		0.00	0.00		0.39	0.05		0.07			
Lane Grp Cap(c), veh/h	589	0	0	0	0	583	871	794	862			
V/C Ratio(X)	0.66	0.00	0.00	0.00	0.00	0.13	0.55	0.50	0.50			
Avail Cap(c_a), veh/h	685	0	0	0	0	699	871	794	862			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.83	0.83	0.83			
Uniform Delay (d), s/veh	14.5	0.0	0.0	0.0	0.0	10.4	14.7	14.2	14.2			
Incr Delay (d2), s/veh	1.8	0.0	0.0	0.0	0.0	0.1	2.1	1.9	1.7			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	3.3	0.0	0.0	0.0	0.0	0.4	5.3	4.2	4.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	16.3	0.0	0.0	0.0	0.0	10.5	16.7	16.1	15.9			
LnGrp LOS	B	A	A	A	A	B	B	B	B			
Approach Vol, veh/h		386			75			1305				
Approach Delay, s/veh		16.3			10.5			16.3				
Approach LOS		B			B			B				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		25.5		19.5				19.5				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		12.7		14.2				3.3				
Green Ext Time (p_c), s		3.5		0.8				0.2				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				16.0								
HCM 6th LOS				B								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕↕				
Traffic Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Future Volume (veh/h)	122	23	0	0	35	12	26	1055	13	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	133	25	0	0	38	13	28	1147	14			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	316	44	0	0	222	76	53	2280	29			
Arrive On Green	0.17	0.17	0.00	0.00	0.17	0.17	0.63	0.63	0.63			
Sat Flow, veh/h	1016	263	0	0	1332	456	84	3598	46			
Grp Volume(v), veh/h	158	0	0	0	0	51	623	0	566			
Grp Sat Flow(s),veh/h/ln	1280	0	0	0	0	1788	1866	0	1862			
Q Serve(g_s), s	4.4	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Cycle Q Clear(g_c), s	5.5	0.0	0.0	0.0	0.0	1.1	8.3	0.0	7.2			
Prop In Lane	0.84		0.00	0.00		0.25	0.04		0.02			
Lane Grp Cap(c), veh/h	360	0	0	0	0	297	1183	0	1180			
V/C Ratio(X)	0.44	0.00	0.00	0.00	0.00	0.17	0.53	0.00	0.48			
Avail Cap(c_a), veh/h	691	0	0	0	0	715	1183	0	1180			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	0.00	0.00	0.00	0.00	1.00	0.85	0.00	0.85			
Uniform Delay (d), s/veh	18.2	0.0	0.0	0.0	0.0	16.1	4.5	0.0	4.3			
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.0	0.0	0.3	1.4	0.0	1.2			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.5	0.0	0.0	0.0	0.0	0.4	2.0	0.0	1.8			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	19.1	0.0	0.0	0.0	0.0	16.4	6.0	0.0	5.5			
LnGrp LOS	B	A	A	A	A	B	A	A	A			
Approach Vol, veh/h		158			51			1189				
Approach Delay, s/veh		19.1			16.4			5.8				
Approach LOS		B			B			A				
Timer - Assigned Phs		2		4				8				
Phs Duration (G+Y+Rc), s		33.0		12.0				12.0				
Change Period (Y+Rc), s		4.5		4.5				4.5				
Max Green Setting (Gmax), s		18.0		18.0				18.0				
Max Q Clear Time (g_c+I1), s		10.3		7.5				3.1				
Green Ext Time (p_c), s		4.5		0.6				0.1				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				7.6								
HCM 6th LOS				A								



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↗↗			↗↗	↖	↖	↗↗				
Traffic Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Future Volume (veh/h)	174	613	0	0	526	176	84	660	59	0	0	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0			
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00			
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Work Zone On Approach		No			No			No				
Adj Sat Flow, veh/h/ln	1870	1870	0	0	1870	1870	1870	1870	1870			
Adj Flow Rate, veh/h	189	666	0	0	572	191	91	717	64			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92			
Percent Heavy Veh, %	2	2	0	0	2	2	2	2	2			
Cap, veh/h	358	1453	0	0	832	371	762	1411	126			
Arrive On Green	0.09	0.41	0.00	0.00	0.23	0.23	0.43	0.43	0.43			
Sat Flow, veh/h	1781	3647	0	0	3647	1585	1781	3300	294			
Grp Volume(v), veh/h	189	666	0	0	572	191	91	386	395			
Grp Sat Flow(s),veh/h/ln	1781	1777	0	0	1777	1585	1781	1777	1817			
Q Serve(g_s), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Cycle Q Clear(g_c), s	4.2	7.5	0.0	0.0	8.1	5.8	1.7	8.7	8.7			
Prop In Lane	1.00		0.00	0.00		1.00	1.00		0.16			
Lane Grp Cap(c), veh/h	358	1453	0	0	832	371	762	760	777			
V/C Ratio(X)	0.53	0.46	0.00	0.00	0.69	0.51	0.12	0.51	0.51			
Avail Cap(c_a), veh/h	358	1783	0	0	1163	519	762	760	777			
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Upstream Filter(I)	1.00	1.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00			
Uniform Delay (d), s/veh	13.7	11.8	0.0	0.0	19.2	18.3	9.5	11.5	11.5			
Incr Delay (d2), s/veh	1.5	0.2	0.0	0.0	1.0	1.1	0.3	2.4	2.4			
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
%ile BackOfQ(50%),veh/ln	1.6	2.6	0.0	0.0	3.1	2.0	0.6	3.4	3.5			
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	15.2	12.1	0.0	0.0	20.2	19.4	9.8	13.9	13.9			
LnGrp LOS	B	B	A	A	C	B	A	B	B			
Approach Vol, veh/h		855			763			872				
Approach Delay, s/veh		12.7			20.0			13.5				
Approach LOS		B			C			B				
Timer - Assigned Phs		2		4			7	8				
Phs Duration (G+Y+Rc), s		28.0		27.0			9.6	17.4				
Change Period (Y+Rc), s		4.5		4.5			4.5	4.5				
Max Green Setting (Gmax), s		18.4		27.6			5.1	18.0				
Max Q Clear Time (g_c+I1), s		10.7		9.5			6.2	10.1				
Green Ext Time (p_c), s		3.1		4.4			0.0	2.8				
<b>Intersection Summary</b>												
HCM 6th Ctrl Delay				15.2								
HCM 6th LOS				B								

---

1: 11th St & Wabasha

---

Direction	All
Future Volume (vph)	1732
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.80
NOx Emissions (kg)	0.15
VOC Emissions (kg)	0.18

---

2: Wabasha & 10th St

---

Direction	All
Future Volume (vph)	1625
Total Delay / Veh (s/v)	12
CO Emissions (kg)	0.88
NOx Emissions (kg)	0.17
VOC Emissions (kg)	0.20

---

3: Exchange St & Wabasha

---

Direction	All
Future Volume (vph)	1286
Total Delay / Veh (s/v)	9
CO Emissions (kg)	0.72
NOx Emissions (kg)	0.14
VOC Emissions (kg)	0.17

---

4: Wabasha & 7th St

---

Direction	All
Future Volume (vph)	2292
Total Delay / Veh (s/v)	15
CO Emissions (kg)	1.50
NOx Emissions (kg)	0.29
VOC Emissions (kg)	0.35



**Traffic Safety Benefit-Cost Calculation**

Highway Safety Improvement Program (HSIP) Reactive Project



A. Roadway Description					
Route	Wabasha St	District	Metro	County	Ramsey
Begin RP		End RP		Miles	
Location	Wabasha St and 7th, Exchange, 10th, and 11th Street				

B. Project Description			
Proposed Work	Installation of Bicycle Lanes and Curb Extensions		
Project Cost*	\$6,672,000	Installation Year	2026
Project Service Life	20 years	Traffic Growth Factor	0.5%

\* exclude Right of Way from Project Cost

C. Crash Modification Factor			
0.24	Fatal (K) Crashes	Reference	Installation of Bicycle Lanes and Curb Extensions CMFs
0.24	Serious Injury (A) Crashes		
0.24	Moderate Injury (B) Crashes	Crash Type	All
0.24	Possible Injury (C) Crashes		
0.24	Property Damage Only Crashes		<a href="http://www.CMFClearinghouse.org">www.CMFClearinghouse.org</a>

D. Crash Modification Factor (optional second CMF)			
	Fatal (K) Crashes	Reference	
	Serious Injury (A) Crashes		
	Moderate Injury (B) Crashes	Crash Type	
	Possible Injury (C) Crashes		
	Property Damage Only Crashes		<a href="http://www.CMFClearinghouse.org">www.CMFClearinghouse.org</a>

E. Crash Data				
Begin Date	1/1/2019	End Date	12/31/2021	3 years
Data Source				
	Crash Severity	All	< optional 2nd CMF >	
	K crashes	0		
	A crashes	1		
	B crashes	2		
	C crashes	6		
	PDO crashes	22		

F. Benefit-Cost Calculation		
\$11,018,393	Benefit (present value)	<b>B/C Ratio = 1.66</b>
\$6,672,000	Cost	
Proposed project expected to reduce 8 crashes annually, 1 of which involving fatality or serious injury.		

### F. Analysis Assumptions

Crash Severity	Crash Cost
K crashes	\$1,500,000
A crashes	\$750,000
B crashes	\$230,000
C crashes	\$120,000
PDO crashes	\$13,000

Link: [mndot.gov/planning/program/appendix\\_a.html](http://mndot.gov/planning/program/appendix_a.html)

Real Discount Rate 0.7%  
 Traffic Growth Rate 0.5%  
 Project Service Life 20 years

### G. Annual Benefit

Crash Severity	Crash Reduction	Annual Reduction	Annual Benefit
K crashes	0.00	0.00	\$0
A crashes	0.76	0.25	\$190,000
B crashes	1.52	0.51	\$116,533
C crashes	4.56	1.52	\$182,400
PDO crashes	16.72	5.57	\$72,453

**\$561,387**

### H. Amortized Benefit

Year	Crash Benefits	Present Value
2026	\$561,387	\$561,387
2027	\$564,194	\$560,272
2028	\$567,015	\$559,159
2029	\$569,850	\$558,048
2030	\$572,699	\$556,940
2031	\$575,562	\$555,834
2032	\$578,440	\$554,730
2033	\$581,332	\$553,628
2034	\$584,239	\$552,529
2035	\$587,160	\$551,431
2036	\$590,096	\$550,336
2037	\$593,047	\$549,243
2038	\$596,012	\$548,152
2039	\$598,992	\$547,064
2040	\$601,987	\$545,977
2041	\$604,997	\$544,893
2042	\$608,022	\$543,810
2043	\$611,062	\$542,730
2044	\$614,117	\$541,652
2045	\$617,188	\$540,577
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0
0	\$0	\$0

**Total = \$11,018,393**

### Multiple CMF Calculation 1

CMF (K) = CMF 1 \* CMF 2 = 0.435 \* 0.55 = 0.2378

CMF (A) = CMF 1 \* CMF 2 = 0.435 \* 0.55 = 0.2378

CMF (B) = CMF 1 \* CMF 2 = 0.435 \* 0.55 = 0.2378

CMF (C) = CMF 1 \* CMF 2 = 0.435 \* 0.55 = 0.2378

CMF (PDO) = CMF 1 \* CMF 2 = 0.435 \* 0.55 = 0.2378

0.24	Fatal (K) Crashes
0.24	Serious Injury (A) Crashes
0.24	Moderate Injury (B) Crashes
0.24	Possible Injury (C) Crashes
0.24	Property Damage Only Crashes

Countermeasure: Install bicycle lanes

Compare	CMF	CRF(%)	Quality	Crash Type	Crash Severity	Area Type	Reference	Comments
<input type="checkbox"/>	0.435		★★★★★	All	All	Urban	, 2021	This CMF is for bicycle ... [READ MORE]
<input type="checkbox"/>	0.51	49	★★★★★	All	All	Urban	, 2021	This CMF is for bicycle ... [READ MORE]
<input type="checkbox"/>	0.734	26.6	★★★★★	All	All	Urban	, 2021	This CMF is for bicycle ... [READ MORE]
<input type="checkbox"/>	0.694	30.6	★★★★★	All	All	Urban	, 2021	This CMF is for bicycle ... [READ MORE]
<input type="checkbox"/>	0.649	35.1	★★★★★	All	All	Urban	, 2021	This CMF is for bicycle ... [READ MORE]

	Strategy	Pages	Crash Modification Factor (CMF)	Evidence (Proven/Tried/Experimental)	Candidate Locations	Construction Estimates
General Intersection Elements	Marked Crosswalks	4-7	Varies, Marked Crosswalks alone should not be considered a safety treatment	Tried	Signalized intersections, unsignalized locations with AADT below 15,000, school zone crossings, unsignalized locations with high pedestrian activity, and mid-block crossing locations.	\$3,000
	Medians and Crossing Islands	8-10	Medians - 0.54 CMF Crossing Islands - 0.46 CMF Source: <a href="https://safety.fhwa.dot.gov/provencountermeasures/ped_medians/">https://safety.fhwa.dot.gov/provencountermeasures/ped_medians/</a>	Proven	Mid-block crossing locations, high-priority pedestrian crossing location such as transit stop, school and parks, and on roads with four or more, speeds greater than 35 mph and AADT greater the 9,000.	\$25,000-\$50,000
	Curb Extensions and Curb Radii	11-14	Curb Extensions - 0.55 CMF Source - <a href="http://www.dot.state.mn.us/stateaid/trafficsafety/county/CRSPEnhancedCrosswalks.pdf">http://www.dot.state.mn.us/stateaid/trafficsafety/county/CRSPEnhancedCrosswalks.pdf</a>	Proven	Mid-block curb extensions or pinch points, offset curb extensions or chicanes, and bus stops.	\$2,000-\$3,500/corner; \$10,000-\$20,000/corner with storm sewer impacts
	Crosswalk Lighting	15-17	0.55 CMF Source: <a href="http://www.cmfclearinghouse.org/detail.cfm?facid=436">http://www.cmfclearinghouse.org/detail.cfm?facid=436</a>	Proven/Tried	Isolated intersections with crosswalks that are not along continuously lit roadways, and mid-block crosswalks.	\$10,000 per intersection to over \$40,000
	Raised Crosswalks	18-21	0.55 CMF Source: <a href="https://safety.fhwa.dot.gov/ped_bike/step/docs/TechSheet_RaisedCW_508compliant.pdf">https://safety.fhwa.dot.gov/ped_bike/step/docs/TechSheet_RaisedCW_508compliant.pdf</a>	Proven	Along 2-lane or 3-lane roadways with speeds 30 mph or less and with AADT of 9,000 or less, locations with high pedestrian or bicycle activity, roundabout crossing locations, and locations where shared use paths cross commercial driveways or ramps.	\$7,000 to \$40,000 each
	Intersection Geometric Design	22-24	Varies	Proven	Where on-street parking or bike lanes are present, where channelized right-turn lanes create more conflicts with pedestrians and bicyclists, where left turns are permitted to occur concurrent with bicycle or pedestrian movements, and at locations where the design must still accommodate turning movements by larger vehicles.	Varies depending on the specific treatment

Wabasha St and 11th St

INCIDENTID	RTESYS	COLRT	ENUMBE	MEASURE	COUNTY_S	CITY_NAM	TOWNSHIP	MNDOT_D	STATE_PAT	TRIBAL_GC	LOCALID	ACCIDENT_	CRASH_MC
777136	5	235	2.181	62	Saint Paul	M	24	20002903	2E+08	1			
700400	5	235	2.186	62	Saint Paul	M	24	19061775	1.91E+08	3			
974703	5	305	0.07	62	2396511		24	21240523	2.13E+08	11			
898844	5	305	0.07	62	Saint Paul	M	24	21067309	2.11E+08	4			
936911	5	305	0.072	62	Saint Paul	M	24	21178054	2.12E+08	8			

Wabasha and 10th St

INCIDENTID	RTESYS	COLRT	ENUMBE	MEASURE	COUNTY_S	CITY_NAM	TOWNSHIP	MNDOT_D	STATE_PAT	TRIBAL_GC	LOCALID	ACCIDENT_	CRASH_MC
756966	5	204	0.18	62	Saint Paul	M	24	19240255	1.93E+08	10			
821072	5	204	0.179	62	Saint Paul	M	24	20146659	2.02E+08	7			
733028	5	235	2.125	62	Saint Paul	M	24	19152453	1.92E+08	7			
797919	5	235	2.127	62	Saint Paul	M	24	20-032389	2E+08	2			
899259	5	235	2.129	62	Saint Paul	M	24	21069603	2.11E+08	4			

Wabasha and Exchange

INCIDENTID	RTESYS	COLRT	ENUMBE	MEASURE	COUNTY_S	CITY_NAM	TOWNSHIP	MNDOT_D	STATE_PAT	TRIBAL_GC	LOCALID	ACCIDENT_	CRASH_MC
907053	5	235	2.054	62	Saint Paul	M	24	21102102	2.11E+08	5			
674852	5	235	2.056	62	Saint Paul	M	24	19005827	1.9E+08	1			
971830	5	235	2.057	62	Saint Paul	M	24	21231690	2.13E+08	11			

Wabasha and 7th St

INCIDENTID	RTESYS	COLRT	ENUMBE	MEASURE	COUNTY_S	CITY_NAM	TOWNSHIP	MNDOT_D	STATE_PAT	TRIBAL_GC	LOCALID	ACCIDENT_	CRASH_MC
702723	3	5	70.083	62	Saint Paul	M	24	19072999	1.91E+08	4			
735990	3	5	70.102	62	Saint Paul	M	24	19163813	1.92E+08	7			
700999	3	5	70.105	62	Saint Paul	M	24	19065128	1.91E+08	3			
982174	3	5	70.106	62	Saint Paul	M	24	21259816	2.14E+08	12			
758898	3	5	70.108	62	Saint Paul	M	24	19246412	1.93E+08	11			
801590	3	5	70.109	62	Saint Paul	M	24	20043770	2.01E+08	3			
890934	3	5	70.111	62	Saint Paul	M	24	21032608	2.1E+08	2			
943403	3	5	70.118	62	Saint Paul	M	24	21203043	2.13E+08	9			
902280	5	235	1.978	62	Saint Paul	M	24	21082470	2.11E+08	4			
898779	5	235	1.985	62	Saint Paul	M	24	21067074	2.11E+08	3			

865893	5	235	1.987	62 Saint Paul	M	24	20254504	2.03E+08	11
835058	5	235	1.991	62 Saint Paul	M	24	20166971	2.02E+08	8
749236	5	235	1.994	62 Saint Paul	M	24	19214926	1.93E+08	9
917543	5	235	1.996	62 Saint Paul	M	24	21142133	2.12E+08	7
902710	5	235	1.998	62 Saint Paul	M	24	21084319	2.11E+08	4

CRASH_DA	CRASH_YE	CRASH_DA	CRASH_HO	DIVIDED	DRD	CRASHSEVI	NUMBERKI	NUMBERO	MANNERO	FIRSTHARV	RELATIONT	LIGHTCONI	WEATHERP
4	2020	Sat	23 N			5	0	2	13	10	3	4	1
26	2019	Tue	22			5	0	2	10	10	3	4	1
19	2021	Fri	22	98		5	0	2	5	10	10	4	1
2	2021	Fri	17 N			3	0	2	5	10	3	1	1
27	2021	Fri	17 E			5	0	2	5	10	3	1	3

CRASH_DA	CRASH_YE	CRASH_DA	CRASH_HO	DIVIDED	DRD	CRASHSEVI	NUMBERKI	NUMBERO	MANNERO	FIRSTHARV	RELATIONT	LIGHTCONI	WEATHERP
24	2019	Thu	17 E			5	0	2	15	10	3	1	1
22	2020	Wed	15			5	0	2	12	10	3	1	1
12	2019	Fri	12 N			4	0	4	12	10	2	1	1
14	2020	Fri	13 N			4	0	3	5	10	3	1	1
5	2021	Mon	15	98		5	0	2	12	10	3	1	1

CRASH_DA	CRASH_YE	CRASH_DA	CRASH_HO	DIVIDED	DRD	CRASHSEVI	NUMBERKI	NUMBERO	MANNERO	FIRSTHARV	RELATIONT	LIGHTCONI	WEATHERP
21	2021	Fri	17 N			5	0	2	10	10	3	1	1
7	2019	Mon	23 N			5	0	2	10	10	3	4	1
6	2021	Sat	12			4	0	2	12	10	3	1	1

CRASH_DA	CRASH_YE	CRASH_DA	CRASH_HO	DIVIDED	DRD	CRASHSEVI	NUMBERKI	NUMBERO	MANNERO	FIRSTHARV	RELATIONT	LIGHTCONI	WEATHERP
10	2019	Wed	13	98		5	0	2	5	10	3	1	4
25	2019	Thu	13			4	0	2	12	10	10	1	1
31	2019	Sun	12			5	0	2	12	10	3	1	99
20	2021	Mon	20			5	0	2	5	10	3	4	1
1	2019	Fri	17 N			5	0	2	12	10	3	1	1
1	2020	Sun	7	98		5	0	2	90	10	3	1	1
16	2021	Tue	15			5	0	2	13	10	3	1	1
27	2021	Mon	22			4	0	2	5	10	3	4	1
24	2021	Sat	23			5	0	2	12	10	3	4	1
18	2021	Thu	16	98		5	0	2	5	10	3	1	1

30	2020 Mon	11 E		3	0	2	5	10	3	1	1
13	2020 Thu	11	98	5	0	2	5	10	3	1	1
22	2019 Sun	12 W		2	0	2	5	10	3	1	1
11	2021 Sun	23		5	0	2	10	10	3	4	1
27	2021 Tue	20	98	5	0	2	12	10	3	4	1



WEATHERS	RDWYSURF	WORKZON	ROADWAY	INTERSECT	ROUTE_ID	BASIC_TYP	UNITTYPE	VEHICLETY	DIRECTION	PRECRASHI	AGEU1	SEXU1
			1	98 S WABASHA ST	050002396	10	2	4	3	21		18 F
			1	98 S WABASHA ST	050002396	5	2	2	3	28		31 F
			1	98 W 11TH ST	050002396	10	1		1	21		
			1	98 E 11TH ST	050002396	10	2	2	1	21		23 M
			2	98 E 11TH ST	050002396	10	2	2	3	21		44 M

WEATHERS	RDWYSURF	WORKZON	ROADWAY	INTERSECT	ROUTE_ID	BASIC_TYP	UNITTYPE	VEHICLETY	DIRECTION	PRECRASHI	AGEU1	SEXU1
			1	6 W 10TH ST	050002396	90	4	48	3	33		26 M
			1	98 W 10TH ST	050002396	7	1		3	21		
			1	98 S WABASHA ST	050002396	7	2	2	1	21		27 M
			1	98 S WABASHA ST	050002396	10	2	5	1	21		23 M
			1	98 S WABASH, W 10TH ST	050002396	7	1	2	1	21		

WEATHERS	RDWYSURF	WORKZON	ROADWAY	INTERSECT	ROUTE_ID	BASIC_TYP	UNITTYPE	VEHICLETY	DIRECTION	PRECRASHI	AGEU1	SEXU1
			1	98 S WABASHA ST	050002396	5	1	4	1	28		
			2	98 S WABASHA ST	050002396	5	1	4	1	24		
			1	98 S WABASHA ST	050002396	7	2	31	3	21		63 M

WEATHERS	RDWYSURF	WORKZON	ROADWAY	INTERSECT	ROUTE_ID	BASIC_TYP	UNITTYPE	VEHICLETY	DIRECTION	PRECRASHI	AGEU1	SEXU1
			2	98 W 7TH ST	030000000	10	1	2	4	21		
			1	98 W 7TH ST	030000000	7	2	4	3	21		52 F
			1	98 W 7TH ST	030000000	7	1	4	3	21		
			3	98 W 7TH ST	030000000	10	1	3	3	21		
			1	98 W 7TH ST	030000000	7	2	2	1	21		42 M
			1	98 W 7TH ST S WABASH,	030000000	90	2	2	3	21		34 M
			1	98 E 7TH ST	030000000	7	1	2	4	22		51 M
			1	98 E 7TH ST	030000000	10	2	4	4	21		33 M
			1	98 S WABASHA ST	050002396	7	1		3	21		
			1	98 S WABASHA ST	050002396	10	2	4	3	21		31 F

1	98 S WABASHA ST	050002396	9	2	2	3	24	62 F
1	1 S WABASHA ST	050002396	10	2	2	1	24	47 F
1	98 S WABASHA ST	050002396	10	2	2	4	24	37 F
1	98 S WABASH.W 7TH ST	050002396	5	1		4	23	
1	98 S WABASHA ST	050002396	7	1		99	24	

PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI	ALIGNMEN	GRADEU1	UNITTYPE	VEHICLETY	DIRECTION
5	99				11	20	30	11	21	2	2	1
5	2				11	20	30	11	21	2	4	3
					11	20	30	11	21	2	2	3
5	99				11	20	20	11	21	2	2	3
5	99				11	20	20	11	21	2	4	1

PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI	ALIGNMEN	GRADEU1	UNITTYPE	VEHICLETY	DIRECTION
5	11				12	20	20	11	21	2	2	3
					12	20	30	11	21	2	5	3
99	99				11	20	30	11	21	2	2	1
5	74				11	20	30	11	21	2	4	4
					11	99	35	11	21	2	2	1

PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI	ALIGNMEN	GRADEU1	UNITTYPE	VEHICLETY	DIRECTION
					11	20	20	11	21	2	4	1
					11	20	30	11	21	2	2	1
5	70				12	20	20	11	21	1	2	3

PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI	ALIGNMEN	GRADEU1	UNITTYPE	VEHICLETY	DIRECTION
					15	20	30	11	21	2	2	1
99	99				15	20	30	11	21	2	5	3
					13	20	30	11	21	2	2	3
					15	20	30	11	21	2	2	1
5	1				12	20	30	11	21	1	2	1
5	99				15	20	30	11	21	1	4	1
99	90				12	20	25			2	4	4
99	67	66			15	20	20	11	21	2	2	1
					15	20		11	21	2	2	3
5	63				13	20	30	11	21	2	2	1

5	2	15	20	30	11	21	2	2	4
5	2	15	20	30	11	21	4	4	4
5	2	15	20	30	11	21	2	31	4
		14	20	30	11	23	2	2	4
		12	20	30		21	2	4	1

PRECRASHI	AGEU2	SEXU2	PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI'	ALIGNMEN	GRADEU2
21	37	M	5	1				11	20	30	11	21
21	43	F	5	1				11	20		11	21
21	35	M	5	1				11	20	30	11	21
21	26	M	5	99				11	20	20	11	21
21	36	F	5	99				11	20	20	11	21

PRECRASHI	AGEU2	SEXU2	PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI'	ALIGNMEN	GRADEU2
34	49	F	5	1				12	20	20	11	21
21	22	M	5	1				12	20	30	11	21
21	32	F	99	1				11	20	30	11	21
21	37	F	5	1				12	20	30	11	21
26	57	F	5	99				11	99	35	11	21

PRECRASHI	AGEU2	SEXU2	PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI'	ALIGNMEN	GRADEU2
21	60	F	5	1				11	20	20	11	21
24	54	M	5	1				11	20	30	11	21
21								12	20	20	11	21

PRECRASHI	AGEU2	SEXU2	PHYSICALC	CONTRIBF#	CONTRIBF#	NONMOTC	NONMOTC	RDWYDESI	TRAFFICCO	SPEEDLIMI'	ALIGNMEN	GRADEU2
21	69	M	5	1				11	20	30	11	21
34	59	M	5	1				15	20	30	11	21
24	43	F	5	1				13	20	30	11	21
21	49	F	5	1				15	20	30	11	21
21								12	20	30	11	21
21								11	20	30	11	21
21	57	M	5	1				12	20	25	11	21
21	36	F	5	1				15	20	20	11	21
21	30	F	5	99				15	20	30	11	21
21	23	M	5	1				11	20	25	11	21

21	29 M		5	1	15	20	30	11	21
21	54 M		5	1	15	20	30	11	21
21	37 M		5	1	15	20	30	11	21
23	23 F		5	99	14	20	30	11	23
21	27	99	5	1	12	20	30	11	21

UNITTYPE|VEHICLE|TY|DIRECTION|PRECRASH|I|AGE|U3|SEX|U3|PHYSICAL|C|CONTRIB|F|CONTRIB|F|NONMOT|C|NONMOT|C|RDWYDESI|TRAFFIC|CO

UNITTYPE|VEHICLE|TY|DIRECTION|PRECRASH|I|AGE|U3|SEX|U3|PHYSICAL|C|CONTRIB|F|CONTRIB|F|NONMOT|C|NONMOT|C|RDWYDESI|TRAFFIC|CO

2	2	1	21	60 F	99	1			11	20
3	2	1	20						11	20

UNITTYPE|VEHICLE|TY|DIRECTION|PRECRASH|I|AGE|U3|SEX|U3|PHYSICAL|C|CONTRIB|F|CONTRIB|F|NONMOT|C|NONMOT|C|RDWYDESI|TRAFFIC|CO

UNITTYPE|VEHICLE|TY|DIRECTION|PRECRASH|I|AGE|U3|SEX|U3|PHYSICAL|C|CONTRIB|F|CONTRIB|F|NONMOT|C|NONMOT|C|RDWYDESI|TRAFFIC|CO





SPEEDLIMIT ALIGNMENT GRADE UNITTYPE VEHICLE TYPE DIRECTION PRECRASH IAGEU4 SEXU4 PHYSICAL CONTRIBUTION CONTRIBUTION NONMOTOR

SPEEDLIMIT ALIGNMENT GRADE UNITTYPE VEHICLE TYPE DIRECTION PRECRASH IAGEU4 SEXU4 PHYSICAL CONTRIBUTION CONTRIBUTION NONMOTOR

30	11	21	3	3	1	20			
30	11	21							

SPEEDLIMIT ALIGNMENT GRADE UNITTYPE VEHICLE TYPE DIRECTION PRECRASH IAGEU4 SEXU4 PHYSICAL CONTRIBUTION CONTRIBUTION NONMOTOR

SPEEDLIMIT ALIGNMENT GRADE UNITTYPE VEHICLE TYPE DIRECTION PRECRASH IAGEU4 SEXU4 PHYSICAL CONTRIBUTION CONTRIBUTION NONMOTOR



NONMOTC RDWYDESI	TRAFFICCO SPEEDLIMI	ALIGNMEN	GRADEU4	UTMX	UTMY	LATITUDE	LONGITUDI	CRASH_DA	STATUS	STATUS_NC
				492184.6	4977461	44.95055	-93.0991	#####	Accepted	Reportable
				492179.4	4977466	44.9506	-93.0991	#####	Accepted	Reportable
				492186.7	4977458	44.95051	-93.099	#####	Accepted	Reportable
				492187.1	4977458	44.95052	-93.0991	#####	Accepted	Reportable
				492188.9	4977459	44.95053	-93.099	#####	Accepted	Reportable

NONMOTC RDWYDESI	TRAFFICCO SPEEDLIMI	ALIGNMEN	GRADEU4	UTMX	UTMY	LATITUDE	LONGITUDI	CRASH_DA	STATUS	STATUS_NC	
				492223.4	4977381	44.94983	-93.0986	43762.73	Accepted	Reportable	
				492222.8	4977381	44.94983	-93.0986	44034.66	Accepted	Reportable	
11	20	30	11	21	492235.8	4977386	44.94988	-93.0984	43658.52	Accepted	Reportable
				492233.9	4977389	44.9499	-93.0985	43875.57	Accepted	Reportable	
				492231.8	4977392	44.94993	-93.0985	44291.63	Accepted	Reportable	

NONMOTC RDWYDESI	TRAFFICCO SPEEDLIMI	ALIGNMEN	GRADEU4	UTMX	UTMY	LATITUDE	LONGITUDI	CRASH_DA	STATUS	STATUS_NC
				492296.7	4977291	44.94902	-93.0977	44337.71	Accepted	Reportable
				492295.7	4977293	44.94903	-93.0977	43472.99	Accepted	Reportable
				492294.3	4977295	44.94905	-93.0977	44506.51	Accepted	Reportable

NONMOTC RDWYDESI	TRAFFICCO SPEEDLIMI	ALIGNMEN	GRADEU4	UTMX	UTMY	LATITUDE	LONGITUDI	CRASH_DA	STATUS	STATUS_NC
				492353.9	4977211	44.9483	-93.0969	43565.54	Accepted	Reportable
				492358.2	4977183	44.94804	-93.0969	43671.56	Accepted	Reportable
				492362.4	4977185	44.94807	-93.0968	43555.51	Accepted	Reportable
				492363.7	4977186	44.94808	-93.0968	44550.85	Accepted	Reportable
				492366.1	4977188	44.94809	-93.0968	43770.74	Accepted	Reportable
				492367.8	4977189	44.9481	-93.0968	43891.33	Accepted	Reportable
				492370.5	4977191	44.94812	-93.0967	44243.65	Accepted	Reportable
				492378.7	4977196	44.94817	-93.0966	44466.94	Accepted	Reportable
				492365.3	4977190	44.94811	-93.0968	44310.97	Accepted	Reportable
				492359.4	4977198	44.94818	-93.0969	44273.69	Accepted	Reportable

492357.1	4977201	44.94821	-93.0969	44165.46	Accepted	Reportable
492353.5	4977206	44.94826	-93.0969	44056.47	Accepted	Reportable
492350.8	4977210	44.94829	-93.097	43730.53	Accepted	Reportable
492348.9	4977213	44.94832	-93.097	44388.99	Accepted	Reportable
492346.9	4977216	44.94835	-93.097	44313.86	Accepted	Reportable

AGENCY\_O AGENCY\_O NARRATIVE

MN062090 Police On  
MN062090 Police Driver Unit 2 was E/B 11th Street approaching Wabasha in the left lane. Driver 1 was E/B 11th Street in the middle lane appro  
MN062090 Police Unit 1 was traveling NB on Wabasha St N when it ran the light and struck Unit 2 which was traveling EB on 11th St. Unit 1 fled  
MN062090 Police Upon  
MN062090 Police UNIT 1

AGENCY\_O AGENCY\_O NARRATIVE

MN062090 Police UNIT 1 was a work truck backing within a work zone, which was also an open roadway. The rear of UNIT 1 crashed into the pas  
MN062090 Police Veh #2 was on 10th ST W; west of Wabasha St N. Veh #2 was facing east bound on 10th ST W, towards Wabasha St N. Veh #1 w  
MN062090 Police Four car accident. Vehicle 1 was northbound Wabasha in the left lane approaching 10th St. Vehicle 1 struck vehicle 2. Vehicle  
MN062090 Police V1 drove through red light at intersection striking V2 which ran into light post. V1 caused V2 to strike vehicle 3 which was le  
MN062090 Police On 04.05.2021 at approximately 1500 hours, Unit 2 was traveling North on Wabasha approaching the intersection with 10th St

AGENCY\_O AGENCY\_O NARRATIVE

MN062090 Police UNIT 2 was traveling northbound in the left lane on WABASHA ST N at EXCHANGE ST.UNIT 1 was traveling northbound in the rig  
MN062090 Police UNIT 2 WAS TRAVELING NB ON WABASHA IN THE WESTERN LANE AND TURNED WB ONTO EXCHANGE. UNIT 1 WAS IN THE EA  
MN062090 Police Veh #1 is a motorcycle. Veh #1 was behind Veh #2.Veh #1's front struck Veh #2's rear bumper. Veh #1's driver was injured. Veh

AGENCY\_O AGENCY\_O NARRATIVE

MN062090 Police Vehicle #2 was travelling n/b Wabasha through 7th St, green lite. Vehicle #1 was w/b 7th, red lite. Driver #2 said he saw driver #  
MN062090 Police Unit # 2 was EB 7th St. at Wabasha stopped for the red lightUnit #1 was also EB 7th St. and rear ended Unit #2Driver of unit #1  
MN062090 Police On 03/31/2019 at approximately 1214 hours, driver of vehicle 1 was attempting to turn north onto Wabasha from east bound  
MN062090 Police Veh #2 was traveling N/B on Wabasha St onto 7th St. Veh #2 had the right of way. Veh #1 was traveling E/B on 7th St W onto W  
MN062090 Police NO ICC SQD #1665. BWC was activated and available for the responding Officer.On 11/01/2019 at approximately 1934 hours, S  
MN062090 Police Unit 1 was traveling east bound on 7th Street at Wabasha. Unit 2 was traveling northbound on Wabasha and struck Unit 1 as i  
MN062090 Police On 02/16/2021 at 1531 hours, Officers responded to the area of WABASHA ST N/7TH ST E for an accident hit and run. Unit 2 str  
MN062090 Police Veh #1 was pursued by police. Veh #1 drove WB in the EB lane of 7th St E into Wabasha St. Veh #2 was traveling NB on Wabash  
MN062090 Police The driver of UNIT 2 was traveling eastbound on W 7th St. As UNIT 2 approached Wabasha St, she looked in her rearview mirr  
MN062090 Police Driver of unit 2 said she was traveling NB on Wabasha St N crossing the intersection for 7th St W and Wabasha St N on a green

MN062090 Police  
MN062090 Police  
MN062090 Police  
MN062090 Police  
MN062090 Police

Driver unit#1 and witness both stated that unit#1 clipped unit#2 on the drivers side while turner left from e/b 7th to n/b Waba  
Driver of vehicle 1 was e/b on 7th St and attempted to make a n/b turn onto Wabasha but failed to yield the right of way to tra  
Vehicle 1, MN LIC 909RYJ,was making a left turn from EB 7th St to NB Wabasha and didn't see vehicle 2, MN lic 30241MJ, a mc  
On 07/11/2021 at approximately 2342 hours, Police responded to the area of 7th St/ Wabasha St for a AHR.On arrival I spoke v  
I Officer P. AGBARA (Squad 533) responded to the area of 7TH ST/WABASHA ST for an accident hit and run. Upon arrival I spoke

aching Wabasha. Driver Unit 1 said she attempted to change lanes to turn left to N/B Wabasha when she struck Unit 2. Driver Unit 1 said she did not the scene. No injuries reported.

ssenger side rear of UNIT 2. UNIT 2 was stopped at the red light on eastbound 10TH ST E at WABASHA ST N. UNIT 2 was in a valid lane, and not in any w as behind Veh #2. Veh #1's front struck Veh #2's rear. Veh #1's driver left the area without providing proper information. Veh #2's driver stated the driv e 2 then struck vehicle 3 and 4. St. Paul Medic 8 arrived and cleared as all medical treatment was denied, no medical report written as they were canc gally parked. V1 caused damage to V2, which struck light post at NW corner of intersection. V1/V2 caused damage to V3 as a result of being struck by t. Unit 2 saw two boys crossing the street in front of her and started to slow down. While Unit 2 was slowing, Unit 1 impacted the rear of Unit 2. Unit :

ght lane on WABASHA ST N at EXCHANGE ST. UNIT 1 swerved into the left lane and crashed into the front passenger side of UNIT 2. UNIT 1 kept driving r ASTERN LANE AND ATTEMPTED TO TURN WB AS WELL. UNIT 1 CRASHED INTO UNIT 2'S PASSENGER SIDE FRONT BUMPER. UNIT 1 FLED NB ON WABA' #2's driver drove away from the area without providing proper information. Veh #1's driver was transported to Regions Hospital to be treated for non-

#1 inching out into the intersection. Driver #2 said as he proceeded through the intersection on a green lite, Driver #1 went through the red lite and str was issued citation Unit #1 was towed to the city lot

7th Street. Vehicle 1 was yielding to vehicles who were traveling west on 7th Street when her vehicle was rear ended by vehicle 2. Driver of vehicle 2 fle 'abasha St. Veh #1 had the red light, thus not the right of way to enter the intersection. Veh #1's front struck Veh #2's rear driver side bumper. Veh #1's quad 273 responded to 367 Grove St ( Police Headquarter) for an accident property damage hit and run. Upon arrival I met and spoke with the complai it passed through the intersection. Unit 2 then fled the scene. A witness was able to obtain a plate for the striking vehicle, MN tag 168 REM. Unit 1 w ated that his vehicle was struck by Unit 1 vehicle. The driver of Unit #2 stated that He was driving east bound on 7th St from the intersection of St. Petri a St into 7th St E. Veh #1's front struck Veh #2's passenger side. Veh #1's driver was taken into custody by Stillwater PD (SW21010729). Veh #1 struck a or and observed the headlights of UNIT 1 approaching the rear of her vehicle at a high rate of speed. UNIT 1 struck UNIT 2 at the rear bumper then fl light. Driver of unit 2 said as he entered the intersection unit 1 was traveling EB on 7th St and entered the intersection on a red light striking unit 2. Driv

Wabasha Street causing unit#2 to rollover landing on its roof. the driver of unit#2 was transported to regions hospital with apparent minor injuries. driver 1 was heading w/b on 7th St. Driver 1 collided with driver 2 (fully marked police vehicle) at the driver's side rear wheel. Vehicle 1 sustained minor damage to the motorcycle, which was WB 7th St going through the intersection of Wabasha. Veh 1 struck the driver side of the motorcycle/left leg of the driver of Veh 2. Driver 2 was with the comp who identified herself via MN DL as ANNIKA CHANDA DUCH (DOB: 06/27/1998, 1679 Thornhill LN, Woodbury MN 55125, C/P: 651-387-1234) to the comp, MARPLE, who stated that his vehicle was struck by an unknown suspect vehicle. MARPLE stated He was driving north on WABASHA ST at the time of the collision.



: see Unit 2 in the lane adjacent to her.

work zone. There was minor, non-disabling damage to UNIT 2. There did not appear to be any damage to UNIT 1. There were no injuries. No arrests were made. The driver of Unit 1 was a "heavy set black male, in his twenties". Veh #1's driver could not describe Veh #1's license plate with certainty. See Original Report. No further information was obtained, no run number per Medic 8. Vehicle 4 was parked in far left lane which is dedicated curbside parking.

Unit 1 and Unit 2 put their hazards on and pulled over, while Unit 2 was going to exit the vehicle. Unit 2 saw Unit 1 make no attempt to stop and drove away. There were no injuries.

Unit 1 fled northbound on WABASHA ST N and fled eastbound on 11TH ST E toward entrances to 35E northbound and 94 westbound. It was unknown which high-occupancy vehicle was involved in the crash. NO VEHICLE DESCRIPTION ON UNIT 1

Unit 1 caused life threatening injuries. Veh #1 was cited for Misdemeanor Failure to Drive with Due Care, Misdemeanor No Proof of Insurance (Driver), and Misdemeanor

Unit 1 struck the passenger side near the rear door. Driver #1 fled the scene. Driver #2 was able to provide the license plate for vehicle #1. Investigative Notes: On 04-01-2019, I mailed a letter to the driver of Unit 1.

Unit 1 fled the scene without exchanging information. There were no reported injuries. No vehicles were towed. Investigative Notes: On 04-01-2019, I mailed a letter to the driver of Unit 1. The driver of Unit 1 drove away from the area without providing proper information. Officers were able to locate the suspect's vehicle in the area of 7th St E and Park St. The driver of Unit 1 was not located. Complainant is an employee of the Ecolab ( 1 Ecolab Pl, St Paul, MN 55102. Complainant was driving the company vehicle MN/LIC # 123456789. The vehicle was able to be driven away from the scene but it had extensive front end damage. Driver of Unit 1 stated he had a green light.

Unit 1 fled the scene. The driver of Unit #2 stated he observed a vehicle driving directly towards him, the wrong way, west on 7th St. The driver of Unit #2 stated he was not injured. The driver of Unit #2 stated he was not injured. St. Paul City owned light pole. Veh #2's driver and passenger were transported to the hospital to be treated for non-life threatening injuries. See Original Report. Unit 1 fled eastbound on W 7th St. The impact of the collision caused UNIT 2's airbags to deploy and UNIT 2's vehicle then struck the traffic control device on W 7th St. The driver of unit 2 said he exchanged information with the driver/RO of unit 1 at the time of the accident. Driver of unit 2 said he has not been able to make contact with the driver of unit 1.

· unit#1 was issued citation number 620907112080. see packetwriter report for further information.

· vehicle 1 and vehicle 2 also sustained minor damage. Driver 1 cited for unsafe change of course.

2. Vehicle 2 ended up crashing and the driver sustained severe injury to the left leg. St Paul Fire Medic 8, Run number 36740, transported the driver of (3478). DUCH stated that she was driving WB on 7th St attempting a RH turn onto NB Wabasha St when her vehicle was struck by another vehicle. DUC was crossing 7th ST in the inside lane. MARPLE said when he crossed 7TH ST the suspect vehicle that was in the right lane made a left turn and crashed into

no citations made or citations given as a result of this crash.END OF REPORT.  
for information.

was minor damage to the rear bumper of Unit 2. No injuries.

way UNIT 1 fled onto.UNIT 2 followed UNIT 1 for a few blocks until it pulled over on 11TH ST E.A witness told the driver of UNIT 2 he saw the license plate  
number 385 Silver 2019 Ford Escape Northbound on Wabasha St near 7th St W when his vehicle was rear ended by another vehicle. Unit two which was the driver of Unit 2 was unable to avoid this vehicle and they hit head on/side swiped. The driver of Unit #2 stated Unit #1 then continued through the intersection and car  
report.  
the south-east corner of the intersection. There was no damage to the traffic control device. Two passengers from UNIT 1 stated the following: They  
contact with the RO of unit 1. Driver of unit 2 wanted a report made and a case number for his insurance. At the time of this report there were no injuries.

On 04-11-2019, I mailed a ten day letter to the RO, Andrew Brehm, requesting insurance information. On 04-12-2019, I received an email between America

ten day letter to the RO, Lisa Enlow, requesting insurance information. The letter was returned by the USPS stamped Attempted-Not Known-Unable to  
Deliver to Addressee at 1111 Wabasha St W, Minneapolis, MN 55415. See original report.

CKR385 Silver 2019 Ford Escape Northbound on Wabasha St near 7th St W when his vehicle was rear ended by another vehicle. Unit two which was the driver of Unit 2 was unable to avoid this vehicle and they hit head on/side swiped. The driver of Unit #2 stated Unit #1 then continued through the intersection and car  
report.  
the south-east corner of the intersection. There was no damage to the traffic control device. Two passengers from UNIT 1 stated the following: They  
contact with the RO of unit 1. Driver of unit 2 wanted a report made and a case number for his insurance. At the time of this report there were no injuries.

wasn't able to avoid this vehicle and they hit head on/side swiped. The driver of Unit #2 stated Unit #1 then continued through the intersection and car  
report.  
the south-east corner of the intersection. There was no damage to the traffic control device. Two passengers from UNIT 1 stated the following: They  
contact with the RO of unit 1. Driver of unit 2 wanted a report made and a case number for his insurance. At the time of this report there were no injuries.

the south-east corner of the intersection. There was no damage to the traffic control device. Two passengers from UNIT 1 stated the following: They  
contact with the RO of unit 1. Driver of unit 2 wanted a report made and a case number for his insurance. At the time of this report there were no injuries.

Vehicle 2 to Regions Hospital. Both vehicles were towed. No citation at this time was issued to the driver of Vehicle on for failing to yield during a left turn. H stated the right turn lane was clear when she attempted to make the RH turn however a vehicle behind her turned quickly behind her into the turn lane. MARPLE stated the suspect vehicle fled west bound on 7th ST, he stated the suspect vehicle was a small white car. I observed the damage to

late and type of vehicle of UNIT 1 and gave the driver of UNIT 2 the information for police. Officers later called the witness and verified he indeed had

rican Family and Andrew Brehm. It provided the claim #01-001-436764.

Forward. I cited Enlow for No Proof of Insurance and forwarded the citation to the TVB.

ie suspect's vehicle fled the scene. Complainant's vehicle sustained minor damage to the rear end bumper. The complainant's vehicle was also insured l

me to a stop on 7th St, in the west bound traffic lanes. The driver of Unit #2 stated that Unit #1 drove off prior to police arrival. The driver of Unit #2 a

/ got into UNIT 1 at Truck Park Bar on W 7th St. They described the vehicle as a newer white BMW sedan. The driver of unit 1 was a bald black male v  
ries reported. I spoke to the RO of unit 1 via telephone. The RO of unit 1 said she was traveling EB on 7th St and stopped at a red light at the intersecti

rn, no insurance or violation of an instructional permit as Traffic and Accident will review it for further charges.

lane.DUCH stated she was partially in the right turn lane when her vehicle was struck. The suspect vehicle is described only as a black sedan, no suspect in MARPLE's vehicle and saw white pieces possibly belonging to the suspect vehicle lodged into the side of MARPLE's vehicle. MARPLE's vehicle sustain

the correct license plate for the vehicle he saw. The witness also said the driver was a black male, mid-20s YO, small to medium build, with short hair.

by the National Union Fire Ins Insurance company ( policy #CA9767380). Good Samaritan witnessed the accident and then provided the complainant w

also stated, it appeared the driver of Unit #1 may have been under the influence, just based on his observations. He stated the driver had a very sleepy

with an English accent wearing glasses and a red flannel shirt with flowers on it. They stated there were 9 people total in the vehicle and the driver of  
on of 7th St and Wabasha St. RO of unit 1 said she believed the light turned green and she accelerated through the intersection striking unit 2. RO of u

at description no make/model/year.DUCH'S vehicle sustained minor damage to the passenger side of the vehicle and passenger side view mirror.There  
ed moderate passenger side damage.No injuries were reported from the incident.



No injuries. No arrests made or citations given.END OF REPORT.

with the suspect's vehicle license plate ( MN/LIC CUX394, A gray Honda Insight, registered to HAMMOND, DAVID GEORGE/dob04/12/1958, 780 SHERW

/impaired look about him and was swerving all over the roadway as they drove towards each other. We checked the area and wer

UNIT 1 was driving way to fast (approximately 50-60 mph). Driver of UNIT 1 was swerving and changing lanes, but they were unsure how the acciden  
nit 2 said she attempted to exchange information with the driver of unit 2 but he was on the phone. RO of unit 1 said she


were no witnesses in the area and it is unknown if the crash was captured on CCTV cameras.DUCH was provided a business card with CN.

'OOD AVE, St Paul, MN 55106)

t



# CITY OF ST. PAUL - WABASHA STREET RECONSTRUCTION (7TH STREET TO 11TH STREET)





# PROJECT SUMMARY

---

**Project Name:** Wabasha Street Reconstruction (7th Street to 11th Street)

**Applicant:** City of Saint Paul

**Project Location:** Wabasha Street between 7th Street and 11th Street

**Total Project Cost:** \$ 6,672,000

**Requested Federal Dollars:** \$5,337,600

**Before Photo:** Northbound Wabasha Street south of 11th Street



## Project Description:

The Wabasha Street Reconstruction project will replace aging street infrastructure and reallocate space in the corridor to accommodate an off-road two-way bikeway facility between 7th Street and 11th Street, while improving safety for all modes of travel.


The project will include the reconstruction of deteriorating sidewalk with a landscaped boulevard between the sidewalk and bikeway to provide a more comfortable pedestrian space along both sides of the corridor. New traffic signals will be installed at the 11th Street, 10th Street, Exchange Street, and 7th Street (TH 5) intersections. Pedestrian improvements including ADA compliant ramps and sidewalks (free of obstructions), Accessible Pedestrian Signals (APS), high visibility crosswalk markings, curb extensions, and countdown timers.

## Project Benefits:


- Implements the Capital City Bikeway and complete a gap in the St. Paul bicycle network
- Improves safety along the corridor for all users and abilities
- Provides improved access to the many downtown St. Paul destinations
- Enhances pedestrian travel with ADA compliant sidewalks, pedestrian-scaled lighting, and streetscaping
- Encourages biking as an alternative mode of transportation for commuting or recreational activity

# Level of Congestion

Roadway Reconstruction/Modernization Project: Wabasha Street | Map ID: 1648301685072



- Project Points
- Principal Arterials
- Principal Arterials Planned
- Project
- A Minor Arterials
- A Minor Arterials Planned



Created: 3/26/2022  
LandscapeRSA1



For complete disclaimer of accuracy, please visit <https://giswebsite.metc.state.mn.us/gis/site/notice.aspx>













# City of Saint Paul

City Hall and Court  
House  
15 West Kellogg  
Boulevard  
Phone: 651-266-8560

## Signature Copy

Resolution: RES 22-334

---

**File Number: RES 22-334**

Authorizing the Departments of Public Works and Parks and Recreation to submit project applications for federal funding into the 2022 Metropolitan Council Regional Solicitation Program and to authorize the commitment of a twenty percent local funding match plus engineering for any project that is awarded federal funding.

WHEREAS, the Departments of Public Works and Parks and Recreation are proposing to submit twelve project applications for federal funding into the 2022 Metropolitan Council Regional Solicitation Program for funding in years 2026 and 2027; and

WHEREAS, there is a required twenty percent local funding match to any project awarded to an agency under the Regional Solicitation Program; and

WHEREAS, the City commits to ensuring that all sidewalks and bikeways included in these project applications will be fully open for use and cleared of snow throughout the winter, either by City staff or by adjacent property owners per existing City ordinances; and

WHEREAS, the projects to be submitted by the City under the Metropolitan Council Regional Solicitation are as follows:

- Wabasha Street Reconstruct - 7th to 11th (Roadways)
- Minnehaha Avenue Reconstruct - Payne to 7th (Roadways)
- Fairview Avenue Reconstruct - Edgumbe to Ford (Roadways)
- Cretin Avenue Reconstruct - I94 to Marshall (Roadways)
- Maryland Avenue Traffic Signal Modernization - Dale to White Bear (Traffic Management)
- Capital City Bikeway - Kellogg from W. 7th to John Ireland (Multiuse Trails)
- Capital City Bikeway - St. Peter/12th from 10th to John Ireland (Multiuse Trails)
- Point Douglas Regional Trail Phase 1 Construction (Multiuse Trails)
- Payne Avenue - Phalen Blvd to Maryland (Pedestrian Facilities)
- Arlington Avenue Sidewalk Infill - I35E to Edgerton (Pedestrian Facilities)
- Chelsea Heights Safe Routes to School (Safe Routes to School)
- Evie Carshare Expansion (Unique Projects 2024/2025 funding)

WHEREAS, these projects fall within appropriate funding categories and meet the conditions and requirements specified for eligibility of federal funding; now, therefore be it

RESOLVED, that the Council of the City of Saint Paul authorizes submission of the project applications for possible award of federal transportation funds through the Metropolitan Council Regional Solicitation Program; and be it finally

RESOLVED, that the Council of the City of Saint Paul authorizes the commitment of local funds on


a twenty percent match basis plus engineering for any project awarded federal funding under the Regional Solicitation Program.

Resolution RES 22-334 Passed Mayor's Office passed Signed 4/8/2024/6/2022 Signed | DAY THAT a meeting of the on , this Resolution was Signed.

**Yea:** 4 Councilmember Noecker, Councilmember Prince, Councilmember Jalali, and Councilmember Yang

**Nay:** 0

**Absent:** 3 Councilmember Brendmoen, Councilmember Thao, and Councilmember Tolbert

**Vote Attested by**   
**Council Secretary** Shari Moore

**Date** 4/6/2022

**Approved by the Mayor**   
Melvin Carter III

**Date** 4/8/2022



MnDOT Metro District  
1500 West County Road B-2  
Roseville, MN 55113

April 12, 2022

Don Pflaum  
Department of Public Works  
City of Saint Paul

**Re: MnDOT Letter for City of Saint Paul's Metropolitan Council/Transportation Advisory Board 2022 Regional Solicitation Funding Request for projects on Wabasha Street and Minnehaha Avenue**

Don Pflaum,

This letter documents MnDOT Metro District's recognition for City of Saint Paul to pursue funding for the Metropolitan Council/Transportation Advisory Board's (TAB) 2022 Regional Solicitation for the following improvements that have impacts to MnDOT right of way.

- **Wabasha Street from 7th Street and 11th Street**, including a portion of 7th Street (Hwy 5) intersection.
- **Minnehaha Avenue from Payne to E 7th St (Hwy 5)**

As proposed, these projects impact MnDOT right of way as described above. As the agency with jurisdiction over this system, MnDOT will allow the City to seek improvements proposed in the application. Details of any future maintenance agreement will need to be determined during project development to define how the improvements will be maintained for the project's useful life if the project receives funding.

There is no funding from MnDOT currently planned or programmed for this improvement. If your project receives funding, continue to work with MnDOT Area staff to coordinate needs and opportunities for cooperation.

MnDOT Metro District looks forward to continued cooperation with Saint Paul as this project moves forward and as we work together to improve safety and travel options within the Metro Area.

If you have questions or require additional information at this time, please reach out to North Area Manager Melissa Barnes at [melissa.barnes@state.mn.us](mailto:melissa.barnes@state.mn.us).

Sincerely,

Michael Barnes, PE  
Metro District Engineer

CC: Melissa Barnes, Metro District Area Manager; Dan Erickson, Metro State Aid Engineer; Molly McCartney, Metro Program Director